

# Professional LED Mains Voltage range

## Recommended dimmer compatibility list for Mains Voltage Lamps



### KEY

X - Y	Excellent dimming with X-Y lamps, however external factors can negatively influence the deep dimming performance
X - Y	See note below.
	Unexpected performance behavior, not in line with good dimming perception
N.A.	Dimmer lamp combination not applicable
T.B.D.	Dimmer lamp combination not tested

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab conditions and might contain faults

Brand	Type	Load
Berker   INSTA	286710	[RC] 20 – 360 W - Turn
Berker   INSTA	2973	[LED, R, L, C] 3 - 60W - Turn
Bticino   Legrand	BTN4411N (BTNT4411N, BTL4411N)	[LED] 3 - 75W - Tast
Busch Jaeger   ABB	2250 U	[R ] 60 – 600 W - Turn
Busch Jaeger   ABB	6513 U - 102	[RC] 40 – 420 W - Turn
Busch Jaeger   ABB	6523 U	[LED] 2 – 100 VA-LED - Turn
Busch Jaeger   ABB	6526 U	[LED] 2 – 100 VA-LED - Push (2wire)
Busch Jaeger   ABB	6523 U-102	[LED, R, L, C] 2 - 100W - Turn- Leading
Busch Jaeger   ABB	6523 U-102	[LED, R, L, C] 2 - 100W - Turn- Trailing
Busch Jaeger   ABB	6523 UR-103	[LED, R, L, C] 2 - 400W - Turn- Leading
Busch Jaeger   ABB	6523 UR-103	[LED, R, L, C] 2 - 400W - Turn- Trailing
ELKO   Schneider	SBD200LED (CCTEL10501)	[LED/RC] 4 - 200W(RC) 4-400W(RL)
ELKO   Schneider	SBD315RC (315 GLE )	[RC] 315W
SE LK   Schneider	LK FUGA LED-S 120VA (506Dx219)	[LED, RL] 4 - 120W - Slider
SE LK   Schneider	LK OPUS 66 LED-S 120VA (506Nx219)	[LED, RL] 4 - 120W - Slider
Eitako	EVD61NPN-UC	400W 3-wire Push Module
Eitako	EUD61NPL-230V	[LED, R, C] 4 - 200W - Module-Leading
Eitako	EUD61NPL-230V	[LED, R, C] 4 - 200W - Module-Trailing
Feller   Schneider	40200 (SBD200LED CCTCH10601)	[LED/RC] 4 - 200W(RC) 4-400W(RL)
Feller   Schneider	40300 (SBD315)	[RLC] 300W
Feller   Schneider	40200.LED.EB (CCT99100)	[LED, RL, RC] 4 - 20VA RL LED / 4 - 100VA RC LED
Gira	1176-00/01	[RLC] 50 – 420W
Gira	2390 00/ 100	[LED] 7 – 100W - Push (3wire)
Gira   INSTA	5401 00	[LED, R, L, C] 3 - 100W/200W- Tast
Gira   INSTA	2450 00	[LED, R, L, C] 3 - 60W - Turn
Hager	EVN 011	[RC] 300VA
Hager	EVN 012	[RC] 300W
Hager	EVN 004	[RL] 500VA
Jung	1271LEDDE	[LED] 3 – 100W - Push (3wire)
Jung   INSTA	1711DE	[LED, R, L, C] 3 - 100W/200W- Tast
Jung   INSTA	1730DD	[LED, R, L, C] 3 - 60W - Turn
Klik aan Klik uit	AWMD-250	[LED] 3- 24W
Klik aan Klik uit	ACM 300	300W - 3-wire Push LED Dimmer
Legrand	78401	[RLC] 40 – 500W
Legrand	67083	[RLC] 3 – 400W
Legrand	67084	[RLC] 8 - 300 VA - Push LED (3wire)
Legrand	67085 (078406)	[RLC] 8 - 300 VA - Push LED (3wire)
Legrand	L4402N	[R ] 60-500W
Merten   Schneider	SBD200LED (MEG5134-0000)	[LED/RC] 4 - 200W(RC) 4-400W(RL)
Merten   Schneider	SBD315RC (MEG5136-0000)	[RC] 315W
Merten   Schneider	MEG5300-0001 (CCT99100)	[LED, RL, RC] 4 - 20VA RL LED / 4 - 100VA RC LED
MK - Electric	K1535	[R] 65 – 450 W - Turn
MK - Electric	K1501 WHILV	[R] 60 – 500 W - Turn
MK - Electric	K4501 WHILV	[RLC] 180W
MK - Electric	K4500 WHILV	[RLC] 400W
NIKO	310-0280X	[LED] 2 – 100 VA
Niko	310-02901	[LED, R, L, C] 3 - 200W - Tast
Niko	310-03901	[LED, R, L, C] 3 - 200W - Turn
PEHA	431HAN	[RL] 6-120W [LED] 6-60W
Philips	UID8670	[LED] 2 – 100 VA-LED - Push (3wire)
RELCO	RP0977	[LED] 4-100W
RELCO	RM0545	[LED] 4-100W
Schneider	SBD315RC (SBD 315, SDD 315, ATD315, CCT011533)	[RC] 315W
Schneider	SBD200 (WDE 002299)	[ ] 4-400VA - Turn Universal (2wire)
Schneider	SAE dimmer puck CCT99100	[LED, RL, RC] 4 - 20VA RL LED / 4 - 100VA RC LED
VADSBO	ED 350	[RC] 50 – 350W
VADSBO	DU 250	[RC] 20 – 250W
VADSBO	VD300	[LED] 0 - 300VA - Turn
Varilight	HQ3W	[R] 60-400W
Varilight	ICT401 M	[RC] 20-400W
Vimar	20148	[RL] 500W
Vimar	20162	[RL] 40-300W
Vimar	Universal dimmer 20135.1	[LED] 3 - 200W - Tast
Vimar	Universal dimmer 20136.1	[LED] 3 - 200W - Turn- Leading
Vimar	Universal dimmer 20136.1	[LED] 3 - 200W - Turn- Trailing
Philips Dynalite	DDLE801	(100W per channel)
Philips Dynalite	DDMC802 (913703243509)	(x W per channel)-leading
Philips Dynalite	DDMC802 (913703243509)	(x W per channel)-Trailing

LED Bulb								
MAS LEDBulb DT3.4-40W E27 927A60C 9290030099			MAS LEDBulb DT5.9-60W E27 927A60CL G 9290030103			MAS LEDBulb DT7.2-75W E27 927A60CL G 9290030111		
MAS LEDBulb DT3.4-40W E27 927 A60 FR 9290030100			MAS LEDBulb DT5.9-60W E27 927 A60 FR G 9290030104			MAS LEDBulb DT7.2-75W B22 927A60CL G 9290030112		
MAS LEDBulb DT3.4-40W B22 927A60CL 9290030101			MAS LEDBulb DT5.9-60W B22 927A60CL G 9290030105			MAS LEDBulb DT7.2-75W E27 927 A60 FR G 9290030113		
MAS VLE LEDBulb 3.4-40W B22 A60 927FR 9290030102			MAS VLE LEDBulb 5.9-60W B22 A60 927FR G 9290030106			MAS VLE LEDBulb 7.2-75W B22 A60 927 FR G 9290030114		
			MAS LEDBulb DT5.9-60W E27 927ST64CLG 9290030107					
			MAS EDBulb DT5.9-60W B22 927 ST64CL G 9290030108					
			MAS LEDBulb DT5.9-60W E27 927G93CL G 9290030109					
			MAS EDBulb DT5.9-60W B22 927 G93CL G 9290030110					
Dimming Performance	Dimming Range	Glowing	Dimming Performance	Dimming Range	Glowing	Dimming Performance	Dimming Range	Glowing
1-20	100% - 0%		1-12	100% - 0%		1-10	100% - 0%	
1-18	97% - 0%		1-10	98% - 0%		1-8	100% - 0%	
1-20	100% - 0%		1-13	100% - 0%		1-10	100% - 0%	
2-20	100% - 0%		1-5	97% - 0%		1-17	100% - 0%	
1-20	100% - 0%		1-20	100% - 0%		1-17	100% - 0%	
1-20	99% - 0%		1-17	98% - 0%		1-14	99% - 0%	
1-20	99% - 0%		1-17	99% - 0%		1-14	100% - 0%	
1-20	100% - 0%		1-17	97% - 0%		1-14	100% - 0%	
1-20	100% - 0%		1-17	97% - 0%		1-14	100% - 0%	
1-20	100% - 0%		1-20	99% - 0%		1-20	100% - 0%	
1-20	100% - 0%		1-20	99% - 0%		1-20	100% - 0%	
1-20	98% - 0%		1-14	99% - 0%		1-11	100% - 0%	
1-19	100% - 0%		1-11	100% - 0%		1-9	100% - 0%	
1-20	100% - 0%		1-20	99% - 0%		1-17	100% - 0%	
1-20	100% - 0%		1-20	99% - 0%		1-17	100% - 0%	
1-20	80% - 34%		1-14	99% - 0%		1-11	100% - 0%	
1-20	100% - 0%		1-15	99% - 0%		1-20	99% - 0%	
1-20	100% - 0%		1-20	100% - 0%		1-20	100% - 0%	
1-20	98% - 0%		1-14	99% - 0%		1-11	100% - 0%	
1-19	100% - 0%		1-11	100% - 0%		1-9	100% - 0%	
1-6	99% - 71%		2-3	100% - 0%		1-3	99% - 0%	
1-20	62% - 0%		1-14	95% - 22%		1-12	98% - 6%	
1-20	98% - 0%		1-17	98% - 0%		1-14	100% - 0%	
1-18	97% - 0%		1-10	98% - 0%		1-8	100% - 0%	
1-18	100% - 0%		1-10	99% - 0%		1-8	99% - 0%	
	N.A.	N.A.	1-17	99% - 6%		1-14	100% - 0%	
1-20	100% - 0%		1-17	96% - 0%		1-14	99% - 0%	
1-20	98% - 0%		1-17	96% - 0%		1-14	99% - 0%	
1-20	98% - 0%		1-17	98% - 0%		1-14	100% - 0%	
1-18	97% - 0%		1-10	98% - 0%		1-8	100% - 0%	
1-7	100% - 0%		1-4	99% - 0%		1-3	100% - 0%	
	96% - 0%		1-3	96% - 0%		1-3	100% - 0%	
1-20	100% - 0%		1-14	99% - 0%		1-11	100% - 0%	
	N.A.	N.A.	1-10	100% - 0%		1-14	100% - 0%	
	N.A.	N.A.		N.A.	N.A.	1	100% - 0%	
1-20	98% - 0%		1-14	99% - 0%		1-11	100% - 0%	
1-19	100% - 0%		1-11	100% - 0%		1-9	100% - 0%	
1-6	99% - 71%		2-3	100% - 0%		1-3	99% - 0%	
2-20	100% - 0%		1-15	100% - 0%		1-13	99% - 0%	
1-20	99% - 0%		1-17	100% - 0%		1-14	100% - 0%	
1-11	100% - 0%		1-6	99% - 0%		1-5	100% - 0%	
2-20	100% - 0%		1-14	99% - 0%		1-11	99% - 0%	
1-20	98% - 0%		1-17	100% - 0%		1-14	100% - 0%	
1-20	100% - 0%		1-20	100% - 0%		1-20	100% - 0%	
1-20	100% - 0%		1-20	100% - 0%		1-20	100% - 0%	
1-18	100% - 0%		1-10	100% - 0%		2-8	100% - 0%	
1-20	99% - 0%		1-17	98% - 0%		1-14	99% - 0%	
1-20	99% - 3%		1-17	99% - 5%		1-14	100% - 2%	
1-20	100% - 0%		1-17	100% - 0%		1-14	100% - 0%	
1-19	100% - 0%		1-11	100% - 0%		1-9	100% - 0%	
1-20	98% - 0%		1-14	99% - 0%		1-11	100% - 0%	
1-6	99% - 71%		2-3	100% - 0%		1-3	99% - 0%	
	90% - 83%		1-3	99% - 0%		1-3	100% - 0%	
1-3	99% - 0%		1-3	99% - 0%		1-3	100% - 0%	
1-18	99% - 0%		1-10	99% - 0%		1-8	87% - 0%	
1-20	100% - 0%		1-14	93% - 0%		1-11	100% - 0%	
1-3	93% - 0%		1-3	99% - 0%		1-3	100% - 0%	
1-20	99% - 0%		1-17	97% - 0%		1-14	100% - 0%	
1-20	99% - 2%		1-20	97% - 3%		1-20	100% - 0%	
1-20	100% - 0%		1-20	99% - 0%		1-20	100% - 0%	
1-20	100% - 0%		1-20	100% - 0%		1-20	99% - 0%	
	99% - 55%		1-8	99% - 0%		1-6	99% - 0%	
1-3	99% - 0%		1-8	98% - 0%	2	1-10	99% - 0%	2
1-10	100% - 0%		1-10	99% - 0%		1-10	99% - 0%	

# Professional LED Mains Voltage range

## Recommended dimmer compatibility list for Mains Voltage Lamps



### KEY

X - Y	Excellent dimming with X-Y lamps, however external factors can negatively influence the deep dimming performance
X - Y	See note below.
	Unexpected performance behavior, not in line with good dimming perception
N.A.	Dimmer lamp combination not applicable
T.B.D.	Dimmer lamp combination not tested

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab conditions and might contain faults

Brand	Type	Load
Berker   INSTA	286710	[RC] 20 – 360 W - Turn
Berker   INSTA	2973	[LED, R, L, C] 3 – 60W - Turn
Bticino   Legrand	BTN4411N (BTNT4411N, BTL4411N)	[LED] 3 – 75W - Tast
Busch Jaeger   ABB	2250 U	[R ] 60 – 600 W - Turn
Busch Jaeger   ABB	6513 U - 102	[RC] 40 – 420 W - Turn
Busch Jaeger   ABB	6523 U	[LED] 2 – 100 VA-LED - Turn
Busch Jaeger   ABB	6526 U	[LED] 2 – 100 VA-LED - Push (2wire)
Busch Jaeger   ABB	6523 U-102	[LED, R, L, C] 2 – 100W - Turn- Leading
Busch Jaeger   ABB	6523 U-102	[LED, R, L, C] 2 – 100W - Turn- Trailing
Busch Jaeger   ABB	6523 UR-103	[LED, R, L, C] 2 – 400W - Turn- Leading
Busch Jaeger   ABB	6523 UR-103	[LED, R, L, C] 2 – 400W - Turn- Trailing
ELKO   Schneider	SBD200LED (CCTEL10501)	[LED/RC] 4 – 200W(RC) 4–400W(RL)
ELKO   Schneider	SBD315RC (315 GLE )	[RC] 315W
SE LK   Schneider	LK FUGA LED-S 120VA (506Dx219)	[LED, RL] 4 – 120W - Slider
SE LK   Schneider	LK OPUS 66 LED-S 120VA (506Nx219)	[LED, RL] 4 – 120W - Slider
Eitako	EVD61NPN-UC	400W 3-wire Push Module
Eitako	EUD61NPL-230V	[LED, R, C] 4 – 200W - Module-Leading
Eitako	EUD61NPL-230V	[LED, R, C] 4 – 200W - Module-Trailing
Feller   Schneider	40200 (SBD200LED CCTCH10601)	[LED/RC] 4 – 200W(RC) 4–400W(RL)
Feller   Schneider	40300 (SBD315)	[RLC] 300W
Feller   Schneider	40200.LED.EB (CCT99100)	[LED, RL, RC] 4 – 20VA RL LED / 4 – 100VA RC LED
Gira	1176-00/01	[RLC] 50 – 420W
Gira	2390 00/ 100	[LED] 7 – 100W - Push (3wire)
Gira   INSTA	5401 00	[LED, R, L, C] 3 – 100W/200W- Tast
Gira   INSTA	2450 00	[LED, R, L, C] 3 – 60W - Turn
Hager	EVN 011	[RC] 300VA
Hager	EVN 012	[RC] 300W
Hager	EVN 004	[RL] 500VA
Jung	1271LEDDE	[LED] 3 – 100W - Push (3wire)
Jung   INSTA	1711DE	[LED, R, L, C] 3 – 100W/200W- Tast
Jung   INSTA	1730DD	[LED, R, L, C] 3 – 60W - Turn
Klik aan Klik uit	AWMD-250	[LED] 3– 24W
Klik aan Klik uit	ACM 300	300W - 3-wire Push LED Dimmer
Legrand	78401	[RLC] 40 – 500W
Legrand	67083	[RLC] 3 – 400W
Legrand	67084	[RLC] 8 – 300 VA - Push LED (3wire)
Legrand	67085 (078406)	[RLC] 8 – 300 VA - Push LED (3wire)
Legrand	L4402N	[R ] 60–500W
Merten   Schneider	SBD200LED (MEG5134-0000)	[LED/RC] 4 – 200W(RC) 4–400W(RL)
Merten   Schneider	SBD315RC (MEG5136-0000)	[RC] 315W
Merten   Schneider	MEG5300-0001 (CCT99100)	[LED, RL, RC] 4 – 20VA RL LED / 4 – 100VA RC LED
MK - Electric	K1535	[R] 65 – 450 W - Turn
MK - Electric	K1501 WHILV	[R] 60 – 500 W - Turn
MK - Electric	K4501 WHILV	[RLC] 180W
MK - Electric	K4500 WHILV	[RLC] 400W
NIKO	310-0280X	[LED] 2 – 100 VA
Niko	310-02901	[LED, R, L, C] 3 – 200W - Tast
Niko	310-03901	[LED, R, L, C] 3 – 200W - Turn
PEHA	431HAN	[RL] 6–120W [LED] 6–60W
Philips	UID8670	[LED] 2 – 100 VA-LED - Push (3wire)
RELCO	RP0977	[LED] 4-100W
RELCO	RM0545	[LED] 4-100W
Schneider	SBD315RC (SBD 315, SDD 315, ATD315, CCT011533)	[RC] 315W
Schneider	SBD200 (WDE 002299)	[ ] 4–400VA - Turn Universal (2wire)
Schneider	SAE dimmer puck CCT99100	[LED, RL, RC] 4 – 20VA RL LED / 4 – 100VA RC LED
VADSBO	ED 350	[RC] 50 – 350W
VADSBO	DU 250	[RC] 20 – 250W
VADSBO	VD300	[LED] 0 – 300VA - Turn
Varilight	HQ3W	[R] 60–400W
Varilight	ICT401 M	[RC] 20-400W
Vimar	20148	[RL] 500W
Vimar	20162	[RL] 40–300W
Vimar	Universal dimmer 20135.1	[LED] 3 – 200W - Tast
Vimar	Universal dimmer 20136.1	[LED] 3 – 200W - Turn- Leading
Vimar	Universal dimmer 20136.1	[LED] 3 – 200W - Turn- Trailing
Philips Dynalite	DDLE801	(100W per channel)
Philips Dynalite	DDMC802 (913703243509)	(x W per channel)-leading
Philips Dynalite	DDMC802 (913703243509)	(x W per channel)-Trailing

LED Bulb								
MAS VLE LEDBulbD3.4W-40W E27 940 A60CL G 9290035266 MAS VLE LEDBulbD3.4W-40W E27 940 A60FR G 9290035270			MAS VLE LEDBulbD5.9W-60W E27 940 A60CL G 9290035267 MAS VLE LEDBulbD5.9W-60W E27 940 A60FR G 9290035271			MAS VLE LEDBulbD7.8W-75W E27 940 A60CL G 9290035268 MAS VLE LEDBulbD7.8W-75W E27 940 A60FR G 9290035272		
Dimming Performance	Dimming Range	Glowing	Dimming Performance	Dimming Range	Glowing	Dimming Performance	Dimming Range	Glowing
1-10	99% - 0%		1-10	100% - 0%		1-9	99% - 0%	
1-10	97% - 0%		1-10	97% - 0%		1-8	89% - 0%	
1-10	100% - 0%		1-10	100% - 0%		1-10	100% - 0%	
2-10	100% - 0%		2-10	99% - 0%		2-10	100% - 0%	
1-10	99% - 0%		1-10	99% - 0%		1-10	98% - 0%	
1-10	100% - 0%		1-10	99% - 0%		1-10	99% - 0%	
1-10	97% - 0%		1-10	96% - 0%		1-10	94% - 0%	
1-10	99% - 0%		1-10	100% - 0%		1-10	100% - 0%	
1-10	99% - 0%		2-10	98% - 0%		2-10	73% - 0%	
1-10	100% - 0%		1-10	99% - 0%		1-10	95% - 0%	
1-10	100% - 0%		2-10	96% - 0%		2-10	71% - 0%	
1-10	97% - 0%		1-10	99% - 0%		1-10	99% - 0%	
1-10	99% - 0%		1-10	99% - 0%		1-8	100% - 0%	
1-10	99% - 0%		1-10	100% - 0%		1-10	99% - 0%	
1-10	100% - 0%		1-10	99% - 0%		1-10	90% - 0%	
1-10	96% - 0%		1-10	100% - 0%		1-10	100% - 0%	
1-10	96% - 0%		1-10	96% - 0%		1-10	100% - 0%	
1-10	97% - 0%		1-10	99% - 0%		1-10	99% - 0%	
1-10	99% - 0%		1-10	100% - 0%		1-8	100% - 0%	
1-6	100% - 0%		1-3	100% - 0%		1-3	100% - 0%	
1-10	98% - 0%			N.A.	N.A.	1-10	70% - 0%	
1-10	98% - 0%		1-10	98% - 0%		1-10	83% - 0%	
1-10	97% - 0%		1-10	97% - 0%		1-8	89% - 0%	
1-10	98% - 0%		1-10	100% - 0%		1-8	100% - 0%	
	N.A.	N.A.		N.A.	N.A.	1-10	100% - 0%	
1-10	98% - 0%		1-10	97% - 0%		1-10	100% - 0%	
1-10	97% - 0%		1-10	97% - 0%		1-10	80% - 0%	
1-10	98% - 0%		1-10	98% - 0%		1-10	83% - 0%	
1-10	97% - 0%		1-10	97% - 0%		1-8	89% - 0%	
1-7	100% - 0%		1-4	100% - 0%		1-3	100% - 0%	
1-3	99% - 0%			N.A.	N.A.		N.A.	N.A.
1-10	99% - 0%		1-10	100% - 0%		1-10	100% - 0%	
	N.A.	N.A.		N.A.	N.A.		N.A.	N.A.
1-10	98% - 0%		1-10	98% - 0%		1-8	100% - 0%	
1-10	99% - 0%			N.A.	N.A.	1-10	98% - 0%	
1-10	99% - 0%		1-10	99% - 0%		1-8	100% - 0%	
1-6	100% - 0%		1-3	100% - 0%		1-3	99% - 0%	
2-10	99% - 0%		1-10	99% - 0%		2-10	98% - 0%	
1-10	99% - 0%		1-10	99% - 0%		1-10	98% - 0%	
1-10	100% - 0%		1-6	98% - 0%		1-5	99% - 0%	
1-10	99% - 0%		1-10	99% - 0%		1-10	98% - 0%	
1-10	99% - 0%		1-10	99% - 0%		1-10	93% - 0%	
1-10	99% - 0%		1-10	99% - 0%		1-10	100% - 0%	
1-10	99% - 0%		1-10	99% - 0%		1-10	100% - 0%	
1-10	99% - 0%			N.A.	N.A.	1-8	100% - 0%	
1-10	100% - 0%		1-10	99% - 0%		1-10	99% - 0%	
1-10	98% - 2%		1-10	99% - 2%		1-10	95% - 2%	
1-10	100% - 0%		1-10	100% - 0%		1-10	100% - 0%	
1-10	99% - 0%		1-10	99% - 0%		1-8	100% - 0%	
1-10	99% - 0%		1-10	99% - 0%		1-10	99% - 0%	
1-6	100% - 0%		1-3	100% - 0%		1-3	99% - 0%	
1-3	100% - 0%		1	100% - 0%		1	100% - 0%	
1-3	100% - 0%		1	100% - 0%		1	100% - 0%	
1-10	98% - 0%		1-10	100% - 0%		1-8	94% - 0%	
2-10	100% - 0%		2-10	100% - 0%		1-10	99% - 0%	
1-3	100% - 0%		1	100% - 0%		1	100% - 0%	
1-10	98% - 0%		1-10	98% - 0%		1-10	98% - 0%	
1-10	98% - 0%							
1-10	98% - 0%		1-10	96% - 0%		1-10	99% - 0%	
1-10	98% - 0%		1-10	95% - 0%		1-10	83% - 0%	
1-10	98% - 0%		1-10	96% - 0%		1-10	100% - 0%	
1-10	98% - 0%		1-8	100% - 0%		1-6	98% - 0%	
5-10	98% - 0%		3-10	100% - 0%		1, 3-10	98% - 0%	
1-10	98% - 0%		1-10	100% - 0%		2-10	98% - 0%	

# Professional LED Mains Voltage range

Recommended dimmer compatibility list for Mains Voltage Lamps



## KEY

X - Y	Excellent dimming with X-Y lamps, however external factors can negatively influence the deep dimming performance
X - Y	See note below.
	Unexpected performance behavior, not in line with good dimming perception
N.A.	Dimmer lamp combination not applicable
T.B.D.	Dimmer lamp combination not tested

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab conditions and might contain faults

Brand	Type	Load
Berker   INSTA	286710	[RC] 20 – 360 W - Turn
Berker   INSTA	2973	[LED, R, L, C] 3 - 60W - Turn
Bticino   Legrand	BTN4411N (BTNT4411N, BTL4411N)	[LED] 3 - 75W - Tast
Busch Jaeger   ABB	2250 U	[R ] 60 – 600 W - Turn
Busch Jaeger   ABB	6513 U - 102	[RC] 40 – 420 W - Turn
Busch Jaeger   ABB	6523 U	[LED] 2 – 100 VA-LED - Turn
Busch Jaeger   ABB	6526 U	[LED] 2 – 100 VA-LED - Push (2wire)
Busch Jaeger   ABB	6523 U-102	[LED, R, L, C] 2 - 100W - Turn- Leading
Busch Jaeger   ABB	6523 U-102	[LED, R, L, C] 2 - 100W - Turn- Trailing
Busch Jaeger   ABB	6523 UR-103	[LED, R, L, C] 2 - 400W - Turn- Leading
Busch Jaeger   ABB	6523 UR-103	[LED, R, L, C] 2 - 400W - Turn- Trailing
ELKO   Schneider	SBD200LED (CCTEL10501)	[LED/RC] 4 - 200W(RC) 4-400W(RL)
ELKO   Schneider	SBD315RC (315 GLE )	[RC] 315W
SE LK   Schneider	LK FUGA LED-S 120VA (506Dx219)	[LED, RL] 4 - 120W - Slider
SE LK   Schneider	LK OPUS 66 LED-S 120VA (506Nx219)	[LED, RL] 4 - 120W - Slider
Eitako	EVD61NPN-UC	400W 3-wire Push Module
Eitako	EUD61NPL-230V	[LED, R, C] 4 - 200W - Module-Leading
Eitako	EUD61NPL-230V	[LED, R, C] 4 - 200W - Module-Trailing
Feller   Schneider	40200 (SBD200LED CCTCH10601)	[LED/RC] 4 - 200W(RC) 4-400W(RL)
Feller   Schneider	40300 (SBD315)	[RLC] 300W
Feller   Schneider	40200.LED.EB (CCT99100)	[LED, RL, RC] 4 - 20VA RL LED / 4 - 100VA RC LED
Gira	1176-00/01	[RLC] 50 – 420W
Gira	2390 00/ 100	[LED] 7 – 100W - Push (3wire)
Gira   INSTA	5401 00	[LED, R, L, C] 3 - 100W/200W- Tast
Gira   INSTA	2450 00	[LED, R, L, C] 3 - 60W - Turn
Hager	EVN 011	[RC] 300VA
Hager	EVN 012	[RC] 300W
Hager	EVN 004	[RL] 500VA
Jung	1271LEDDE	[LED] 3 – 100W - Push (3wire)
Jung   INSTA	1711DE	[LED, R, L, C] 3 - 100W/200W- Tast
Jung   INSTA	1730DD	[LED, R, L, C] 3 - 60W - Turn
Klik aan Klik uit	AWMD-250	[LED] 3- 24W
Klik aan Klik uit	ACM 300	300W - 3-wire Push LED Dimmer
Legrand	78401	[RLC] 40 – 500W
Legrand	67083	[RLC] 3 – 400W
Legrand	67084	[RLC] 8 - 300 VA - Push LED (3wire)
Legrand	67085 (078406)	[RLC] 8 - 300 VA - Push LED (3wire)
Legrand	L4402N	[R ] 60-500W
Merten   Schneider	SBD200LED (MEG5134-0000)	[LED/RC] 4 - 200W(RC) 4-400W(RL)
Merten   Schneider	SBD315RC (MEG5136-0000)	[RC] 315W
Merten   Schneider	MEG5300-0001 (CCT99100)	[LED, RL, RC] 4 - 20VA RL LED / 4 - 100VA RC LED
MK - Electric	K1535	[R] 65 – 450 W - Turn
MK - Electric	K1501 WHILV	[R] 60 – 500 W - Turn
MK - Electric	K4501 WHILV	[RLC] 180W
MK - Electric	K4500 WHILV	[RLC] 400W
NIKO	310-0280X	[LED] 2 -100 VA
Niko	310-02901	[LED, R, L, C] 3 - 200W - Tast
Niko	310-03901	[LED, R, L, C] 3 - 200W - Turn
PEHA	431HAN	[RL] 6-120W [LED] 6-60W
Philips	UID8670	[LED] 2 – 100 VA-LED - Push (3wire)
RELCO	RP0977	[LED] 4-100W
RELCO	RM0545	[LED] 4-100W
Schneider	SBD315RC (SBD 315, SDD 315, ATD315, CCT011533)	[RC] 315W
Schneider	SBD200 (WDE 002299)	[ ] 4-400VA - Turn Universal (2wire)
Schneider	SAE dimmer puck CCT99100	[LED, RL, RC] 4 - 20VA RL LED / 4 - 100VA RC LED
VADSBO	ED 350	[RC] 50 – 350W
VADSBO	DU 250	[RC] 20 – 250W
VADSBO	VD300	[LED] 0 - 300VA - Turn
Varilight	HQ3W	[R] 60-400W
Varilight	ICT401 M	[RC] 20-400W
Vimar	20148	[RL] 500W
Vimar	20162	[RL] 40-300W
Vimar	Universal dimmer 20135.1	[LED] 3 - 200W - Tast
Vimar	Universal dimmer 20136.1	[LED] 3 - 200W - Turn- Leading
Vimar	Universal dimmer 20136.1	[LED] 3 - 200W - Turn- Trailing
Philips Dynalite	DDLE801	(100W per channel)
Philips Dynalite	DDMC802 (913703243509)	(x W per channel)-leading
Philips Dynalite	DDMC802 (913703243509)	(x W per channel)-Trailing

LED Bulb								
MAS VLE LEDCandleD3.4-40W E14 B35 927 CL G 9290030595 MAS VLE LEDCandleD3.4-40W E14 B35 927 FR G 9290030597 MAS VLE LEDLusterD3.4-40W E14 P45 927 CL G 9290030600 MAS VLE LEDLusterD3.4-40W E14 P45 927 FR G 9290030602 MAS VLE LEDLusterD3.4-40W E27 P45 927 CL G 9290030604 MAS VLE LEDLusterD3.4-40W E27 P45 927 FR G 9290030606			MAS VLE LEDBulbD3.4-40W E27 927 A60 CL G 9290030705 MAS VLE LEDBulbD3.4-40W E27 927 A60 FR G 9290030707			MAS VLE LEDBulbD11.2-100W E27 940A60CLG 9290035269 MAS VLE LEDBulbD11.2-100W E27 940A60FRG 9290035273		
Dimming Performance	Dimming Range	Glowing	Dimming Performance	Dimming Range	Glowing	Dimming Performance	Dimming Range	Glowing
1-10	99% - 0%		1-10	99% - 0%		2-6	99% - 13%	
1-10	97% - 0%		1-10	99% - 0%		1-5	99% - 0%	
1-10	100% - 0%		1-10	100% - 0%		2-7	99% - 1%	
2-10	100% - 0%		1-10	99% - 0%		1-11	99% - 0%	
1-10	99% - 0%		1-10	99% - 0%		2-11	99% - 13%	
1-10	100% - 0%		1-10	100% - 0%		1-9	100% - 0%	
1-10	97% - 0%		1-10	98% - 0%		1-9	99% - 0%	
1-10	99% - 0%		1-10	100% - 0%		1-9	98% - 2%	
1-10	99% - 0%		1-10	100% - 0%		1-9	99% - 8%	
1-10	100% - 0%		1-10	100% - 0%		1-20	99% - 0%	
1-10	100% - 0%		1-10	78% - 0%		1-20	100% - 0%	
1-10	97% - 0%		1-10	100% - 0%			N.A.	N.A.
1-10	99% - 0%		1-10	98% - 0%		1-6	99% - 1%	
1-10	99% - 0%		1-10	98% - 0%		1-11	100% - 10%	
1-10	99% - 0%		1-10	98% - 0%		1-11	100% - 10%	
1-10	100% - 0%		1-10	99% - 0%		1-7	100% - 1%	
1-10	96% - 0%		1-10	100% - 0%		1-18	99% - 0%	
1-10	96% - 0%		1-10	98% - 0%		1-18	99% - 1%	
1-10	97% - 0%		1-10	100% - 0%			N.A.	N.A.
1-10	99% - 0%		1-10	100% - 0%		1-6	99% - 1%	
1-6	100% - 0%		1-6	100% - 0%		1-2	98% - 9%	
1-10	98% - 0%		1-10	100% - 4%		1-8	99% - 18%	
1-10	98% - 0%		1-10	98% - 0%		1-9	98% - 5%	
1-10	97% - 0%		1-10	99% - 0%		1-5	100% - 7%	
1-10	98% - 0%		1-10	100% - 0%		1-5	99% - 0%	
	N.A.	N.A.		N.A.	N.A.	1-9	100% - 4%	
1-10	98% - 0%		1-10	100% - 0%		1-9	100% - 2%	
1-10	97% - 0%		1-10	97% - 0%		1-9	94% - 3%	
1-10	98% - 0%		1-10	98% - 0%		1-9	98% - 5%	
1-10	97% - 0%		1-10	99% - 0%		1-5	100% - 7%	
1-7	100% - 0%		1-7	100% - 0%		1-2	100% - 0%	
1-3	100% - 0%		1-3	98% - 0%		1	99% - 0%	
1-10	99% - 0%		1-10	100% - 0%		1-7	98% - 1%	
	N.A.	N.A.		N.A.	N.A.	1-5	100% - 0%	
1-10	98% - 0%		1-10	98% - 0%		1-5	99% - 0%	
1-10	99% - 0%		1-10	100% - 0%		2-9	100% - 0%	
1-10	99% - 0%		1-10	100% - 0%		1-7	99% - 1%	
1-10	99% - 0%		1-10	100% - 0%		1-6	99% - 1%	
1-6	100% - 0%		1-6	100% - 0%		1-2	98% - 9%	
2-10	99% - 0%		2-10	100% - 0%		2-8	97% - 1%	
1-10	99% - 0%		2-10	100% - 0%		1-9	100% - 10%	
1-10	100% - 0%		1-10	100% - 0%		1-3	98% - 6%	
1-10	99% - 0%		2-10	99% - 0%		1-7	100% - 15%	
1-10	99% - 0%		1-10	100% - 0%		1-9	98% - 0%	
1-10	99% - 0%		1-10	100% - 18%		1-18	100% - 70%	
1-10	99% - 0%		1-10	99% - 0%		1-18	100% - 70%	
1-10	99% - 0%		1-10	99% - 0%		1-5	99% - 0%	
1-10	100% - 0%		1-10	100% - 0%		1-9	100% - 0%	
1-10	98% - 2%		1-10	98% - 1%		1-9	100% - 0%	
1-10	100% - 0%		1-10	100% - 0%		1-9	98% - 6%	
1-10	99% - 0%		1-10	100% - 0%		1-6	99% - 1%	
1-10	99% - 0%		1-10	100% - 0%		1-7	99% - 1%	
1-6	100% - 0%		1-6	100% - 0%		1-2	98% - 9%	
1-3	100% - 0%		1-3	98% - 0%		1	97% - 35%	
1-3	100% - 0%		1-3	98% - 0%		1	95% - 19%	
1-10	98% - 0%		1-10	98% - 0%		1-5	99% - 0%	
2-10	100% - 0%		2-10	100% - 0%		1-7	99% - 15%	
1-3	100% - 0%		1-3	98% - 0%		1	96% - 3%	
1-10	98% - 0%		1-10	100% - 0%		1-9	100% - 1%	
1-10	98% - 0%		1-10	100% - 0%		1-18	99% - 1%	
1-10	98% - 0%		1-10	100% - 0%		1-18	99% - 0%	
1-10	98% - 0%		1-10	100% - 0%		1-18	100% - 0%	
1-10	98% - 0%			N.A.	N.A.	1-4	97% - 0%	
5-10	98% - 0%		6-10	93% - 0%		1, 5-8	99% - 0%	
1-10	98% - 0%		6-11	97% - 0%		1-8	99% - 0%	



# Professional LED Mains Voltage range

Recommended dimmer compatibility list for Mains Voltage Lamps



## KEY

X - Y	Excellent dimming with X-Y lamps, however external factors can negatively influence the deep dimming performance
X - Y	See note below.
	Unexpected performance behavior, not in line with good dimming perception
N.A.	Dimmer lamp combination not applicable
T.B.D.	Dimmer lamp combination not tested

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab conditions and might contain faults

Brand	Type	Load
Berker   INSTA	286710	[RC] 20 – 360 W - Turn
Berker   INSTA	2973	[LED, R, L, C] 3 – 60W - Turn
Bticino   Legrand	BTN4411N (BTNT4411N, BTL4411N)	[LED] 3 – 75W - Tast
Busch Jaeger   ABB	2250 U	[R ] 60 – 600 W - Turn
Busch Jaeger   ABB	6513 U - 102	[RC] 40 – 420 W - Turn
Busch Jaeger   ABB	6523 U	[LED] 2 – 100 VA-LED - Turn
Busch Jaeger   ABB	6526 U	[LED] 2 – 100 VA-LED - Push (2wire)
Busch Jaeger   ABB	6523 U-102	[LED, R, L, C] 2 – 100W - Turn- Leading
Busch Jaeger   ABB	6523 U-102	[LED, R, L, C] 2 – 100W - Turn- Trailing
Busch Jaeger   ABB	6523 UR-103	[LED, R, L, C] 2 – 400W - Turn- Leading
Busch Jaeger   ABB	6523 UR-103	[LED, R, L, C] 2 – 400W - Turn- Trailing
ELKO   Schneider	SBD200LED (CCTEL10501)	[LED/RC] 4 – 200W(RC) 4-400W(RL)
ELKO   Schneider	SBD315RC (315 GLE )	[RC] 315W
SE LK   Schneider	LK FUGA LED-S 120VA (506Dx219)	[LED, RL] 4 – 120W - Slider
SE LK   Schneider	LK OPUS 66 LED-S 120VA (506Nx219)	[LED, RL] 4 – 120W - Slider
Eitako	EVD61NPN-UC	400W 3-wire Push Module
Eitako	EUD61NPL-230V	[LED, R, C] 4 – 200W - Module-Leading
Eitako	EUD61NPL-230V	[LED, R, C] 4 – 200W - Module-Trailing
Feller   Schneider	40200 (SBD200LED CCTCH10601)	[LED/RC] 4 – 200W(RC) 4-400W(RL)
Feller   Schneider	40300 (SBD315)	[RLC] 300W
Feller   Schneider	40200.LED.EB (CCT99100)	[LED, RL, RC] 4 – 20VA RL LED / 4 – 100VA RC LED
Gira	1176-00/01	[RLC] 50 – 420W
Gira	2390 00/ 100	[LED] 7 – 100W - Push (3wire)
Gira   INSTA	5401 00	[LED, R, L, C] 3 – 100W/200W- Tast
Gira   INSTA	2450 00	[LED, R, L, C] 3 – 60W - Turn
Hager	EVN 011	[RC] 300VA
Hager	EVN 012	[RC] 300W
Hager	EVN 004	[RL] 500VA
Jung	1271LEDDE	[LED] 3 – 100W - Push (3wire)
Jung   INSTA	1711DE	[LED, R, L, C] 3 – 100W/200W- Tast
Jung   INSTA	1730DD	[LED, R, L, C] 3 – 60W - Turn
Klik aan Klik uit	AWMD-250	[LED] 3– 24W
Klik aan Klik uit	ACM 300	300W - 3-wire Push LED Dimmer
Legrand	78401	[RLC] 40 – 500W
Legrand	67083	[RLC] 3 – 400W
Legrand	67084	[RLC] 8 – 300 VA - Push LED (3wire)
Legrand	67085 (078406)	[RLC] 8 – 300 VA - Push LED (3wire)
Legrand	L4402N	[R ] 60-500W
Merten   Schneider	SBD200LED (MEG5134-0000)	[LED/RC] 4 – 200W(RC) 4-400W(RL)
Merten   Schneider	SBD315RC (MEG5136-0000)	[RC] 315W
Merten   Schneider	MEG5300-0001 (CCT99100)	[LED, RL, RC] 4 – 20VA RL LED / 4 – 100VA RC LED
MK - Electric	K1535	[R] 65 – 450 W - Turn
MK - Electric	K1501 WHILV	[R] 60 – 500 W - Turn
MK - Electric	K4501 WHILV	[RLC] 180W
MK - Electric	K4500 WHILV	[RLC] 400W
NIKO	310-0280X	[LED] 2 – 100 VA
Niko	310-02901	[LED, R, L, C] 3 – 200W - Tast
Niko	310-03901	[LED, R, L, C] 3 – 200W - Turn
PEHA	431HAN	[RL] 6-120W [LED] 6-60W
Philips	UID8670	[LED] 2 – 100 VA-LED - Push (3wire)
RELCO	RP0977	[LED] 4-100W
RELCO	RM0545	[LED] 4-100W
Schneider	SBD315RC (SBD 315, SDD 315, ATD315, CCT011533)	[RC] 315W
Schneider	SBD200 (WDE 002299)	[ ] 4-400VA - Turn Universal (2wire)
Schneider	SAE dimmer puck CCT99100	[LED, RL, RC] 4 – 20VA RL LED / 4 – 100VA RC LED
VADSBO	ED 350	[RC] 50 – 350W
VADSBO	DU 250	[RC] 20 – 250W
VADSBO	VD300	[LED] 0 – 300VA - Turn
Varilight	HQ3W	[R] 60-400W
Varilight	ICT401 M	[RC] 20-400W
Vimar	20148	[RL] 500W
Vimar	20162	[RL] 40-300W
Vimar	Universal dimmer 20135.1	[LED] 3 – 200W - Tast
Vimar	Universal dimmer 20136.1	[LED] 3 – 200W - Turn- Leading
Vimar	Universal dimmer 20136.1	[LED] 3 – 200W - Turn- Trailing
Philips Dynalite	DDLE801	(100W per channel)
Philips Dynalite	DDMC802 (913703243509)	(x W per channel)-leading
Philips Dynalite	DDMC802 (913703243509)	(x W per channel)-Trailing

LED Bulb			LED Candle		
Dimming Performance	Dimming Range	Glowing	Dimming Performance	Dimming Range	Glowing
1-7	97% - 16%		1-20	98% - 0%	1-20
1-6	97% - 7%		1-20	93% - 0%	1-18
1-7	97% - 4%		1-20	96% - 0%	1-20
1-11	97% - 0%		3-20	95% - 0%	1-20
1-11	98% - 15%		1-20	95% - 0%	1-20
1-10	98% - 3%		1-20	86% - 0%	1-20
1-10	96% - 0%		1-20	93% - 0%	1-20
1-10	97% - 10%		1-20	92% - 0%	1-20
1-10	97% - 3%		1-20	94% - 0%	1-20
1-15	97% - 0%		1-20	94% - 0%	1-20
1-20	97% - 0%		1-20	94% - 0%	1-20
1-8	96% - 13%		1-20	99% - 0%	1-20
1-6	97% - 4%		1-20	100% - 0%	1-19
1-11	97% - 12%		1-20	100% - 0%	1-20
1-11	97% - 12%		1-20	100% - 0%	1-20
1-8	98% - 0%		1-20	99% - 0%	1-20
2-10	97% - 8%		1-10	96% - 0%	1-10
1-19	97% - 0%		1-20	98% - 0%	1-20
1-8	96% - 13%		1-20	99% - 0%	1-20
1-6	97% - 4%		1-20	100% - 0%	1-19
1-2	97% - 12%		1-8	99% - 0%	1-6
1-8	97% - 18%		1-20	100% - 3%	1-20
1-10	98% - 0%		1-20	92% - 0%	1-20
1-6	97% - 7%		1-20	93% - 0%	1-18
1-6	97% - 7%		1-20	99% - 0%	1-18
1-10	98% - 23%		1-20	100% - 4%	1-20
1-10	100% - 9%		1-20	98% - 0%	1-20
1-8	99% - 0%		1-20	97% - 0%	1-20
1-10	98% - 0%		1-20	92% - 0%	1-20
1-6	97% - 7%		1-20	93% - 0%	1-18
1-2	96% - 21%		1-10	88% - 3%	1-7
1	98% - 0%		1-3	96% - 0%	1-3
1-8	98% - 4%		1-20	100% - 0%	1-20
1-6	99% - 0%		1-20	99% - 0%	1-18
2-10	99% - 37%		1	86% - 0%	1
1-8	96% - 13%		1-20	99% - 0%	1-20
1-6	97% - 4%		1-20	100% - 0%	1-19
1-2	97% - 12%		1-8	99% - 0%	1-6
1-9	98% - 11%		5-20	92% - 0%	2-20
1-10	98% - 12%		1-20	99% - 0%	2-20
1-3	98% - 7%		1-14	100% - 0%	1-11
1-8	98% - 15%		1-20	98% - 0%	1-20
1-10	97% - 2%		1-20	99% - 0%	1-20
1-19	96% - 1%		1-5	99% - 0%	1-20
1-19	96% - 1%		1-5	99% - 0%	1-20
1-6	97% - 0%	N.A.	N.A.	N.A.	1-18
1-10	98% - 3%		1-20	86% - 0%	1-20
	N.A.	N.A.	1-20	100% - 4%	1-20
1	96% - 8%	N.A.	1-20	100% - 0%	1-20
1-6	97% - 4%		1-20	100% - 0%	1-19
1-8	96% - 13%		1-20	99% - 0%	1-20
1-2	97% - 12%		1-8	99% - 0%	1-6
1	94% - 32%		1-3	98% - 1%	1-3
1	96% - 18%		1-3	89% - 0%	1-3
1-6	83% - 1%		1-20	63% - 0%	1-18
1-8	99% - 14%		1-20	99% - 0%	1-20
1-1	95% - 5%		1-3	87% - 0%	1-3
1-10	97% - 18%		1-20	92% - 0%	1-20
1-19	99% - 22%		1-20	98% - 3%	1-20
1-19	98% - 2%		1-20	98% - 0%	1-20
1-19	97% - 2%		1-20	98% - 0%	1-20
1-4	99% - 0%		1-10	90% - 0%	1-10
2-3	99% - 0%		1-10	97% - 0%	6-10
1-9	99% - 0%		5-10	97% - 0%	1-10

# Professional LED Mains Voltage range

## Recommended dimmer compatibility list for Mains Voltage Lamps



### KEY

X - Y	Excellent dimming with X-Y lamps, however external factors can negatively influence the deep dimming performance
X - Y	See note below.
	Unexpected performance behavior, not in line with good dimming perception
N.A.	Dimmer lamp combination not applicable
T.B.D.	Dimmer lamp combination not tested

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab conditions and might contain faults

Brand	Type	Load
Berker   INSTA	286710	[RC] 20 – 360 W - Turn
Berker   INSTA	2973	[LED, R, L, C] 3 - 60W - Turn
Bticino   Legrand	BTN4411N (BTNT4411N, BTL4411N)	[LED] 3 - 75W - Tast
Busch Jaeger   ABB	2250 U	[R ] 60 – 600 W - Turn
Busch Jaeger   ABB	6513 U - 102	[RC] 40 – 420 W - Turn
Busch Jaeger   ABB	6523 U	[LED] 2 – 100 VA-LED - Turn
Busch Jaeger   ABB	6526 U	[LED] 2 – 100 VA-LED - Push (2wire)
Busch Jaeger   ABB	6523 U-102	[LED, R, L, C] 2 - 100W - Turn- Leading
Busch Jaeger   ABB	6523 U-102	[LED, R, L, C] 2 - 100W - Turn- Trailing
Busch Jaeger   ABB	6523 UR-103	[LED, R, L, C] 2 - 400W - Turn- Leading
Busch Jaeger   ABB	6523 UR-103	[LED, R, L, C] 2 - 400W - Turn- Trailing
ELKO   Schneider	SBD200LED (CCTEL10501)	[LED/RC] 4 - 200W(RC) 4-400W(RL)
ELKO   Schneider	SBD315RC (315 GLE )	[RC] 315W
SE LK   Schneider	LK FUGA LED-S 120VA (506Dx219)	[LED, RL] 4 - 120W - Slider
SE LK   Schneider	LK OPUS 66 LED-S 120VA (506Nx219)	[LED, RL] 4 - 120W - Slider
Eitako	EVD61NPN-UC	400W 3-wire Push Module
Eitako	EUD61NPL-230V	[LED, R, C] 4 - 200W - Module-Leading
Eitako	EUD61NPL-230V	[LED, R, C] 4 - 200W - Module-Trailing
Feller   Schneider	40200 (SBD200LED CCTCH10601)	[LED/RC] 4 - 200W(RC) 4-400W(RL)
Feller   Schneider	40300 (SBD315)	[RLC] 300W
Feller   Schneider	40200.LED.EB (CCT99100)	[LED, RL, RC] 4 - 20VA RL LED / 4 - 100VA RC LED
Gira	1176-00/01	[RLC] 50 – 420W
Gira	2390 00/ 100	[LED] 7 – 100W - Push (3wire)
Gira   INSTA	5401 00	[LED, R, L, C] 3 - 100W/200W- Tast
Gira   INSTA	2450 00	[LED, R, L, C] 3 - 60W - Turn
Hager	EVN 011	[RC] 300VA
Hager	EVN 012	[RC] 300W
Hager	EVN 004	[RL] 500VA
Jung	1271LEDDE	[LED] 3 – 100W - Push (3wire)
Jung   INSTA	1711DE	[LED, R, L, C] 3 - 100W/200W- Tast
Jung   INSTA	1730DD	[LED, R, L, C] 3 - 60W - Turn
Klik aan Klik uit	AWMD-250	[LED] 3- 24W
Klik aan Klik uit	ACM 300	300W - 3-wire Push LED Dimmer
Legrand	78401	[RLC] 40 – 500W
Legrand	67083	[RLC] 3 – 400W
Legrand	67084	[RLC] 8 - 300 VA - Push LED (3wire)
Legrand	67085 (078406)	[RLC] 8 - 300 VA - Push LED (3wire)
Legrand	L4402N	[R ] 60-500W
Merten   Schneider	SBD200LED (MEG5134-0000)	[LED/RC] 4 - 200W(RC) 4-400W(RL)
Merten   Schneider	SBD315RC (MEG5136-0000)	[RC] 315W
Merten   Schneider	MEG5300-0001 (CCT99100)	[LED, RL, RC] 4 - 20VA RL LED / 4 - 100VA RC LED
MK - Electric	K1535	[R] 65 - 450 W - Turn
MK - Electric	K1501 WHILV	[R] 60 - 500 W - Turn
MK - Electric	K4501 WHILV	[RLC] 180W
MK - Electric	K4500 WHILV	[RLC] 400W
NIKO	310-0280X	[LED] 2 -100 VA
Niko	310-02901	[LED, R, L, C] 3 - 200W - Tast
Niko	310-03901	[LED, R, L, C] 3 - 200W - Turn
PEHA	431HAN	[RL] 6-120W [LED] 6-60W
Philips	UID8670	[LED] 2 – 100 VA-LED - Push (3wire)
RELCO	RP0977	[LED] 4-100W
RELCO	RM0545	[LED] 4-100W
Schneider	SBD315RC (SBD 315, SDD 315, ATD315, CCT011533)	[RC] 315W
Schneider	SBD200 (WDE 002299)	[ ] 4-400VA - Turn Universal (2wire)
Schneider	SAE dimmer puck CCT99100	[LED, RL, RC] 4 - 20VA RL LED / 4 - 100VA RC LED
VADSBO	ED 350	[RC] 50 – 350W
VADSBO	DU 250	[RC] 20 – 250W
VADSBO	VD300	[LED] 0 - 300VA - Turn
Varilight	HQ3W	[R] 60-400W
Varilight	ICT401 M	[RC] 20-400W
Vimar	20148	[RL] 500W
Vimar	20162	[RL] 40-300W
Vimar	Universal dimmer 20135.1	[LED] 3 - 200W - Tast
Vimar	Universal dimmer 20136.1	[LED] 3 - 200W - Turn- Leading
Vimar	Universal dimmer 20136.1	[LED] 3 - 200W - Turn- Trailing
Philips Dynalite	DDLE801	(100W per channel)
Philips Dynalite	DDMC802 (913703243509)	(x W per channel)-leading
Philips Dynalite	DDMC802 (913703243509)	(x W per channel)-Trailing

LED Bulb								
MAS VLE LEDBulb D11.2-100W E27 927 A60 CL G 9290030583 MAS VLE LEDBulb D11.2-100W E27 927 A60 FR G 9290030585			MAS VLE LEDBulb D5.9-60W E27 927 A60 CL G 9290030575 MAS VLE LEDBulb D5.9-60W E27 927 A60 FR G 9290030577 MAS VLE LEDBulb D5.9-60W E27 927 ST64 CL G 9290030594 MAS VLE LEDBulb D5.9-60W E27 927 G120 CL G 9290030593 MASVLELEDBulb D5.9-60W E27 927A60FR G UK 9290030577			MAS VLE LEDBulb D7.8-75W E27 927 A60 CL G 9290030579 MAS VLE LEDBulb D7.8-75W E27 927 A60 FR G 9290030581		
Dimming Performance	Dimming Range	Glowing	Dimming Performance	Dimming Range	Glowing	Dimming Performance	Dimming Range	Glowing
2-6	99% - 13%		1-10	100% - 0%		1-9	99% - 0%	
1-5	99% - 0%		1-10	97% - 0%		1-8	89% - 0%	
2-7	99% - 1%		1-10	100% - 0%		1-10	100% - 0%	
1-11	99% - 0%		2-10	99% - 0%		2-10	100% - 0%	
2-11	99% - 13%		1-10	99% - 0%		1-10	98% - 0%	
1-9	100% - 0%		1-10	99% - 0%		1-10	99% - 0%	
1-9	99% - 0%		1-10	96% - 0%		1-10	94% - 0%	
1-9	98% - 2%		1-10	100% - 0%		1-10	100% - 0%	
1-9	99% - 8%		2-10	98% - 0%		2-10	73% - 0%	
1-20	99% - 0%		1-10	99% - 0%		1-10	95% - 0%	
1-20	100% - 0%		2-10	96% - 0%		2-10	71% - 0%	
1-7	99% - 21%		1-10	99% - 0%		1-10	99% - 0%	
1-6	99% - 1%		1-10	99% - 0%		1-8	100% - 0%	
1-11	100% - 10%		1-10	100% - 0%		1-10	99% - 0%	
1-11	100% - 10%		1-10	100% - 0%		1-10	99% - 0%	
1-7	100% - 1%		1-10	99% - 0%		1-10	90% - 0%	
1-18	99% - 0%		1-10	100% - 0%		1-10	100% - 0%	
1-18	99% - 1%		1-10	96% - 0%		1-10	100% - 0%	
1-7	99% - 21%		1-10	99% - 0%		1-10	99% - 0%	
1-6	99% - 1%		1-10	100% - 0%		1-8	100% - 0%	
1-2	98% - 9%		1-3	100% - 0%		1-3	100% - 0%	
1-8	99% - 18%		1-10	100% - 0%		1-10	70% - 0%	
1-9	98% - 5%		1-10	98% - 0%		1-10	83% - 0%	
1-5	100% - 7%		1-10	97% - 0%		1-8	89% - 0%	
1-5	99% - 0%		1-10	100% - 0%		1-8	100% - 0%	
1-9	100% - 4%		1-10	100% - 0%		1-10	100% - 0%	
1-9	100% - 2%		1-10	97% - 0%		1-10	100% - 0%	
1-9	94% - 3%		1-10	97% - 0%		1-10	80% - 0%	
1-9	98% - 5%		1-10	98% - 0%		1-10	83% - 0%	
1-5	100% - 7%		1-10	97% - 0%		1-8	89% - 0%	
1-2	100% - 0%		1-4	100% - 0%		1-3	100% - 0%	
1	99% - 0%			N.A.	N.A.		N.A.	N.A.
1-7	98% - 1%		1-10	100% - 0%		1-10	100% - 0%	
1-5	101% - 0%	N.A.		N.A.	N.A.		N.A.	N.A.
1-5	99% - 0%		1-10	98% - 0%		1-8	100% - 0%	
2-9	100% - 0%			N.A.	N.A.	1-10	98% - 0%	
1-7	99% - 1%		1-10	99% - 0%		1-10	99% - 0%	
1-6	99% - 1%		1-10	99% - 0%		1-8	100% - 0%	
1-2	98% - 9%		1-3	100% - 0%		1-3	99% - 0%	
2-8	97% - 1%		1-10	99% - 0%		2-10	98% - 0%	
1-9	100% - 10%		1-10	99% - 0%		1-10	98% - 0%	
1-3	98% - 6%		1-6	98% - 0%		1-5	99% - 0%	
1-7	100% - 15%		1-10	99% - 0%		1-10	98% - 0%	
1-9	98% - 0%		1-10	99% - 0%		1-10	93% - 0%	
1-18	100% - 70%		1-10	99% - 0%		1-10	100% - 0%	
1-18	100% - 70%		1-10	99% - 0%		1-10	100% - 0%	
1-5	99% - 0%			N.A.	N.A.	1-8	100% - 0%	
1-9	100% - 0%		1-10	99% - 0%		1-10	99% - 0%	
1-9	100% - 0%		1-10	99% - 2%		1-10	95% - 2%	
1-9	98% - 6%		1-10	100% - 0%		1-10	100% - 0%	
1-6	99% - 1%		1-10	99% - 0%		1-8	100% - 0%	
1-7	99% - 1%		1-10	99% - 0%		1-10	99% - 0%	
1	97% - 35%		1	98% - 0%		1	0% - 0%	
1	95% - 19%		1	98% - 0%		1	0% - 0%	
1-5	99% - 0%		1-10	100% - 0%		1-8	94% - 0%	
1-7	99% - 15%		2-10	100% - 0%		1-10	99% - 0%	
1	96% - 3%		1	98% - 0%		1	100% - 0%	
1-9	100% - 1%		1-10	98% - 0%		1-10	98% - 0%	
1-18	99% - 1%		1-10	96% - 0%		1-10	99% - 0%	
1-18	99% - 0%		1-10	95% - 0%		1-10	83% - 0%	
1-18	100% - 0%		1-10	96% - 0%		1-10	100% - 0%	
1-4	97% - 0%		1-8	100% - 0%		1-6	98% - 0%	
1-8	99% - 0%	2-4	3-10	100% - 0%		1, 3-10	98% - 0%	
1-8	99% - 0%		1-10	100% - 0%		2-10	98% - 0%	

# Professional LED Mains Voltage range

Recommended dimmer compatibility list for Mains Voltage Lamps



## KEY

X - Y	Excellent dimming with X-Y lamps, however external factors can negatively influence the deep dimming performance
X - Y	See note below.
	Unexpected performance behavior, not in line with good dimming perception
N.A.	Dimmer lamp combination not applicable
T.B.D.	Dimmer lamp combination not tested

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab conditions and might contain faults

Brand	Type	Load
Berker   INSTA	286710	[RC] 20 – 360 W - Turn
Berker   INSTA	2973	[LED, R, L, C] 3 - 60W - Turn
Bticino   Legrand	BTN4411N (BTNT4411N, BTL4411N)	[LED] 3 - 75W - Tast
Busch Jaeger   ABB	2250 U	[R ] 60 – 600 W - Turn
Busch Jaeger   ABB	6513 U - 102	[RC] 40 – 420 W - Turn
Busch Jaeger   ABB	6523 U	[LED] 2 – 100 VA-LED - Turn
Busch Jaeger   ABB	6526 U	[LED] 2 – 100 VA-LED - Push (2wire)
Busch Jaeger   ABB	6523 U-102	[LED, R, L, C] 2 - 100W - Turn- Leading
Busch Jaeger   ABB	6523 U-102	[LED, R, L, C] 2 - 100W - Turn- Trailing
Busch Jaeger   ABB	6523 UR-103	[LED, R, L, C] 2 - 400W - Turn- Leading
Busch Jaeger   ABB	6523 UR-103	[LED, R, L, C] 2 - 400W - Turn- Trailing
ELKO   Schneider	SBD200LED (CCTEL10501)	[LED/RC] 4 - 200W(RC) 4-400W(RL)
ELKO   Schneider	SBD315RC (315 GLE )	[RC] 315W
SE LK   Schneider	LK FUGA LED-S 120VA (506Dx219)	[LED, RL] 4 - 120W - Slider
SE LK   Schneider	LK OPUS 66 LED-S 120VA (506Nx219)	[LED, RL] 4 - 120W - Slider
Eitako	EVD61NPN-UC	400W 3-wire Push Module
Eitako	EUD61NPL-230V	[LED, R, C] 4 - 200W - Module-Leading
Eitako	EUD61NPL-230V	[LED, R, C] 4 - 200W - Module-Trailing
Feller   Schneider	40200 (SBD200LED CCTCH10601)	[LED/RC] 4 - 200W(RC) 4-400W(RL)
Feller   Schneider	40300 (SBD315)	[RLC] 300W
Feller   Schneider	40200.LED.EB (CCT99100)	[LED, RL, RC] 4 - 20VA RL LED / 4 - 100VA RC LED
Gira	1176-00/01	[RLC] 50 – 420W
Gira	2390 00/ 100	[LED] 7 – 100W - Push (3wire)
Gira   INSTA	5401 00	[LED, R, L, C] 3 - 100W/200W- Tast
Gira   INSTA	2450 00	[LED, R, L, C] 3 - 60W - Turn
Hager	EVN 011	[RC] 300VA
Hager	EVN 012	[RC] 300W
Hager	EVN 004	[RL] 500VA
Jung	1271LEDDE	[LED] 3 – 100W - Push (3wire)
Jung   INSTA	1711DE	[LED, R, L, C] 3 - 100W/200W- Tast
Jung   INSTA	1730DD	[LED, R, L, C] 3 - 60W - Turn
Klik aan Klik uit	AWMD-250	[LED] 3- 24W
Klik aan Klik uit	ACM 300	300W - 3-wire Push LED Dimmer
Legrand	78401	[RLC] 40 – 500W
Legrand	67083	[RLC] 3 – 400W
Legrand	67084	[RLC] 8 - 300 VA - Push LED (3wire)
Legrand	67085 (078406)	[RLC] 8 - 300 VA - Push LED (3wire)
Legrand	L4402N	[R ] 60-500W
Merten   Schneider	SBD200LED (MEG5134-0000)	[LED/RC] 4 - 200W(RC) 4-400W(RL)
Merten   Schneider	SBD315RC (MEG5136-0000)	[RC] 315W
Merten   Schneider	MEG5300-0001 (CCT99100)	[LED, RL, RC] 4 - 20VA RL LED / 4 - 100VA RC LED
MK - Electric	K1535	[R] 65 – 450 W - Turn
MK - Electric	K1501 WHILV	[R] 60 – 500 W - Turn
MK - Electric	K4501 WHILV	[RLC] 180W
MK - Electric	K4500 WHILV	[RLC] 400W
NIKO	310-0280X	[LED] 2 – 100 VA
Niko	310-02901	[LED, R, L, C] 3 - 200W - Tast
Niko	310-03901	[LED, R, L, C] 3 - 200W - Turn
PEHA	431HAN	[RL] 6-120W [LED] 6-60W
Philips	UID8670	[LED] 2 – 100 VA-LED - Push (3wire)
RELCO	RP0977	[LED] 4-100W
RELCO	RM0545	[LED] 4-100W
Schneider	SBD315RC (SBD 315, SDD 315, ATD315, CCT011533)	[RC] 315W
Schneider	SBD200 (WDE 002299)	[ ] 4-400VA - Turn Universal (2wire)
Schneider	SAE dimmer puck CCT99100	[LED, RL, RC] 4 - 20VA RL LED / 4 - 100VA RC LED
VADSBO	ED 350	[RC] 50 – 350W
VADSBO	DU 250	[RC] 20 – 250W
VADSBO	VD300	[LED] 0 - 300VA - Turn
Varilight	HQ3W	[R] 60-400W
Varilight	ICT401 M	[RC] 20-400W
Vimar	20148	[RL] 500W
Vimar	20162	[RL] 40-300W
Vimar	Universal dimmer 20135.1	[LED] 3 - 200W - Tast
Vimar	Universal dimmer 20136.1	[LED] 3 - 200W - Turn- Leading
Vimar	Universal dimmer 20136.1	[LED] 3 - 200W - Turn- Trailing
Philips Dynalite	DDLE801	(100W per channel)
Philips Dynalite	DDMC802 (913703243509)	(x W per channel)-leading
Philips Dynalite	DDMC802 (913703243509)	(x W per channel)-Trailing

LED Bulb			LED Candle			LED Bulb		
MAS LEDBulbDT10.5-100W B22 927A60CLG 9290030116 MAS VLE LEDBulbD10.5-100W B22 A60 927FRG 9290030118 MAS VLE LEDBulbD10.5-100W B22 A60 927FRG UK 9290030118			LED classic 60W B35 E14 CL WGD90 9290030139 LED classic 60W B35 B22 CL WGD90 9290030140 LED classic 60W P45 E14 WGD90 CL 9290030141 LED classic 60W P45 B22 WGD90 CL 9290030142 LED classic 60W P45 E27 WGD90 CL 9290030143			MAS VLE LEDBulbD7.2-50W E27 A60 927 CM G 9290024128 LED classic CM 50W A60 E27 WW CL D SRT4 9290024128 LED classic 50W G120 E27 WW CM D RF 9290024129		
Dimming Performance	Dimming Range	Glowing	Dimming Performance	Dimming Range	Glowing	Dimming Performance	Dimming Range	Glowing
1-7	98% - 19%		1-5	72% - 0%		1-10	100% - 0%	
1-6	99% - 12%		1-10	0% - 0%		1-10	100% - 0%	
1-7	98% - 6%		1	96% - 0%		1-10	100% - 0%	
1-11	99% - 0%		1-20	93% - 0%		2-10	100% - 0%	
	N.A.	N.A.	1-10	66% - 0%		1-10	100% - 0%	
1-10	97% - 0%		1-17	95% - 0%		1-10	100% - 0%	
1-10	96% - 0%			N.A.	N.A.	1-10	100% - 0%	
1-10	99% - 0%		1-20	87% - 0%		1-10	100% - 0%	
1-10	97% - 3%			N.A.	N.A.	1-10	100% - 0%	
1-10	100% - 0%		1-20	76% - 0%		1-10	100% - 0%	
1-20	97% - 0%		1	93% - 0%		1-10	100% - 0%	
	N.A.	N.A.	1-3	95% - 0%		1-10	100% - 0%	
1-6	97% - 8%		1-4	97% - 0%		1-10	100% - 0%	
1-11	100% - 15%		1	97% - 0%		1-10	100% - 0%	
1-11	100% - 15%		1-20	0% - 0%		1-10	100% - 0%	
1-8	100% - 0%		1	0% - 0%		1-10	100% - 0%	
1-10	100% - 0%		1-15	70% - 0%		1-10	100% - 0%	
1-19	100% - 1%		1-20	98% - 0%		1-10	100% - 0%	
	N.A.	N.A.	1-3	95% - 0%		1-10	100% - 0%	
1-6	97% - 8%		1-4	97% - 0%		1-10	100% - 0%	
1-2	99% - 12%		1-3	96% - 0%		1-3	100% - 0%	
1-8	100% - 30%			N.A.	N.A.	1-10	100% - 0%	
1-10	98% - 13%		1-17	97% - 0%		1-10	100% - 0%	
1-6	99% - 12%		1-10	80% - 0%		1-10	100% - 0%	
1-6	99% - 7%		1-3	70% - 0%		1-10	100% - 0%	
1-10	100% - 25%		1-5	70% - 2%		1-10	100% - 0%	
1-10	100% - 9%		1-17	69% - 0%		1-10	100% - 0%	
1-8	100% - 0%		1-17	96% - 0%		1-10	100% - 0%	
1-10	98% - 13%		1-17	97% - 0%		1-10	100% - 0%	
1-6	99% - 12%		1-10	80% - 0%		1-10	100% - 0%	
1-2	98% - 22%		1-4	99% - 2%		1-4	100% - 0%	
1	96% - 0%		1-3	99% - 0%		1-3	100% - 0%	
1-8	99% - 6%		1-5	97% - 0%		1-10	100% - 0%	
1-6	99% - 0%		1-10	96% - 0%		1-10	100% - 0%	
						1-10	100% - 0%	
1-10	96% - 16%		1-2	98% - 0%		1-10	100% - 0%	
	N.A.	N.A.	1-3	95% - 0%		1-10	100% - 0%	
1-6	97% - 8%		1-3	97% - 0%		1-10	100% - 0%	
1-2	99% - 12%		1-3	96% - 0%		1-3	100% - 0%	
1-9	98% - 3%		1-15	96% - 0%		2-10	100% - 0%	
1-10	97% - 5%		1-17	97% - 0%		1-10	100% - 0%	
1-3	96% - 6%		1-6	96% - 0%		1-6	100% - 0%	
1-8	97% - 5%		1-14	99% - 0%		1-10	100% - 0%	
1-10	97% - 1%			N.A.	N.A.	1-10	100% - 0%	
1-19	97% - 0%			N.A.	N.A.	1-10	100% - 0%	
1-19	97% - 0%			N.A.	N.A.	1-10	100% - 0%	
1-6	96% - 0%		1-10	99% - 10%		1-10	100% - 0%	
1-10	97% - 0%		1-17	95% - 0%		1-10	100% - 0%	
1-10	99% - 24%			N.A.	N.A.	1-10	100% - 2%	
1-10	98% - 8%			N.A.	N.A.	1-10	100% - 0%	
1-6	97% - 8%		1-3	97% - 0%		1-10	100% - 0%	
	N.A.	N.A.	1-3	95% - 0%		1-10	100% - 0%	
1-2	99% - 12%		1-3	96% - 0%		1-3	100% - 0%	
1	99% - 36%		1-3	100% - 0%		1-3	100% - 0%	
1	99% - 19%		1-3	100% - 0%		1-3	100% - 0%	
1-6	87% - 0%		1-3	95% - 0%		1-10	100% - 0%	
1-8	100% - 3%		1-3	97% - 0%		1-10	100% - 0%	
1	98% - 3%		1-3	0% - 0%		1-3	100% - 0%	
1-10	100% - 5%		1-17	99% - 0%		1-10	100% - 0%	
1-19	100% - 22%		1-20	72% - 3%		1-10	100% - 0%	
1-19	100% - 1%		1-20	72% - 0%		1-10	100% - 0%	
1-19	98% - 2%			N.A.	N.A.	1-10	100% - 0%	
1-4	98% - 0%		1-8	96% - 0%		1-8	96% - 0%	
1-9	99% - 0%		5-10	97% - 0%		3-10	97% - 0%	
1-9	99% - 0%		3-10	97% - 0%		2-10	98% - 0%	



# Professional LED Mains Voltage range

## Recommended dimmer compatibility list for Mains Voltage Lamps



### KEY

X - Y	Excellent dimming with X-Y lamps, however external factors can negatively influence the deep dimming performance
X - Y	See note below.
	Unexpected performance behavior, not in line with good dimming perception
N.A.	Dimmer lamp combination not applicable
T.B.D.	Dimmer lamp combination not tested

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab conditions and might contain faults

Brand	Type	Load
Berker   INSTA	286710	[RC] 20 – 360 W - Turn
Berker   INSTA	2973	[LED, R, L, C] 3 - 60W - Turn
Bticino   Legrand	BTN4411N (BTNT4411N, BTL4411N)	[LED] 3 - 75W - Tast
Busch Jaeger   ABB	2250 U	[R ] 60 – 600 W - Turn
Busch Jaeger   ABB	6513 U - 102	[RC] 40 – 420 W - Turn
Busch Jaeger   ABB	6523 U	[LED] 2 – 100 VA-LED - Turn
Busch Jaeger   ABB	6526 U	[LED] 2 – 100 VA-LED - Push (2wire)
Busch Jaeger   ABB	6523 U-102	[LED, R, L, C] 2 - 100W - Turn- Leading
Busch Jaeger   ABB	6523 U-102	[LED, R, L, C] 2 - 100W - Turn- Trailing
Busch Jaeger   ABB	6523 UR-103	[LED, R, L, C] 2 - 400W - Turn- Leading
Busch Jaeger   ABB	6523 UR-103	[LED, R, L, C] 2 - 400W - Turn- Trailing
ELKO   Schneider	SBD200LED (CCTEL10501)	[LED/RC] 4 - 200W(RC) 4-400W(RL)
ELKO   Schneider	SBD315RC (315 GLE )	[RC] 315W
SE LK   Schneider	LK FUGA LED-S 120VA (506Dx219)	[LED, RL] 4 - 120W - Slider
SE LK   Schneider	LK OPUS 66 LED-S 120VA (506Nx219)	[LED, RL] 4 - 120W - Slider
Eitako	EVD61NPN-UC	400W 3-wire Push Module
Eitako	EUD61NPL-230V	[LED, R, C] 4 - 200W - Module-Leading
Eitako	EUD61NPL-230V	[LED, R, C] 4 - 200W - Module-Trailing
Feller   Schneider	40200 (SBD200LED CCTCH10601)	[LED/RC] 4 - 200W(RC) 4-400W(RL)
Feller   Schneider	40300 (SBD315)	[RLC] 300W
Feller   Schneider	40200.LED.EB (CCT99100)	[LED, RL, RC] 4 - 20VA RL LED / 4 - 100VA RC LED
Gira	1176-00/01	[RLC] 50 – 420W
Gira	2390 00/ 100	[LED] 7 – 100W - Push (3wire)
Gira   INSTA	5401 00	[LED, R, L, C] 3 - 100W/200W- Tast
Gira   INSTA	2450 00	[LED, R, L, C] 3 - 60W - Turn
Hager	EVN 011	[RC] 300VA
Hager	EVN 012	[RC] 300W
Hager	EVN 004	[RL] 500VA
Jung	1271LEDDE	[LED] 3 – 100W - Push (3wire)
Jung   INSTA	1711DE	[LED, R, L, C] 3 - 100W/200W- Tast
Jung   INSTA	1730DD	[LED, R, L, C] 3 - 60W - Turn
Klik aan Klik uit	AWMD-250	[LED] 3- 24W
Klik aan Klik uit	ACM 300	300W - 3-wire Push LED Dimmer
Legrand	78401	[RLC] 40 – 500W
Legrand	67083	[RLC] 3 – 400W
Legrand	67084	[RLC] 8 - 300 VA - Push LED (3wire)
Legrand	67085 (078406)	[RLC] 8 - 300 VA - Push LED (3wire)
Legrand	L4402N	[R ] 60-500W
Merten   Schneider	SBD200LED (MEG5134-0000)	[LED/RC] 4 - 200W(RC) 4-400W(RL)
Merten   Schneider	SBD315RC (MEG5136-0000)	[RC] 315W
Merten   Schneider	MEG5300-0001 (CCT99100)	[LED, RL, RC] 4 - 20VA RL LED / 4 - 100VA RC LED
MK - Electric	K1535	[R] 65 – 450 W - Turn
MK - Electric	K1501 WHILV	[R] 60 – 500 W - Turn
MK - Electric	K4501 WHILV	[RLC] 180W
MK - Electric	K4500 WHILV	[RLC] 400W
NIKO	310-0280X	[LED] 2 -100 VA
Niko	310-02901	[LED, R, L, C] 3 - 200W - Tast
Niko	310-03901	[LED, R, L, C] 3 - 200W - Turn
PEHA	431HAN	[RL] 6-120W [LED] 6-60W
Philips	UID8670	[LED] 2 – 100 VA-LED - Push (3wire)
RELCO	RP0977	[LED] 4-100W
RELCO	RM0545	[LED] 4-100W
Schneider	SBD315RC (SBD 315, SDD 315, ATD315, CCT011533)	[RC] 315W
Schneider	SBD200 (WDE 002299)	[ ] 4-400VA - Turn Universal (2wire)
Schneider	SAE dimmer puck CCT99100	[LED, RL, RC] 4 - 20VA RL LED / 4 - 100VA RC LED
VADSBO	ED 350	[RC] 50 – 350W
VADSBO	DU 250	[RC] 20 – 250W
VADSBO	VD300	[LED] 0 - 300VA - Turn
Varilight	HQ3W	[R] 60-400W
Varilight	ICT401 M	[RC] 20-400W
Vimar	20148	[RL] 500W
Vimar	20162	[RL] 40-300W
Vimar	Universal dimmer 20135.1	[LED] 3 - 200W - Tast
Vimar	Universal dimmer 20136.1	[LED] 3 - 200W - Turn- Leading
Vimar	Universal dimmer 20136.1	[LED] 3 - 200W - Turn- Trailing
Philips Dynalite	DDLE801	(100W per channel)
Philips Dynalite	DDMC802 (913703243509)	(x W per channel)-leading
Philips Dynalite	DDMC802 (913703243509)	(x W per channel)-Trailing

LED Bulb			LED Candle			LED Bulb		
MAS VLE LEDBulbD4-25W E27 A60 GOLD SP G 9290029828 MAS VLE LEDBulbD4-25W E27 ST64 GOLD SP G 9290029829 MAS VLE LEDBulbD4-25W E27 T32 GOLD SP G 9290029831 MAS VLE LEDBulbD4-15WE27 G93GOLD SP G 9290029830			MAS VLE LEDCandleD2.5-15WE14 B35GOLDSP G 9290029832 MAS VLE LEDLusterD 2.6-15W E14 P45 SP G 9290029833 MAS VLE LEDBulbD 2.6-15W E27 GOLDP45SP G 9290029834			LED classic 25W ST64 E27 pink D SRT4 9290024537 LED classic 25W G93 E27 pink D 1PF/4 9290024538 LED CLA giant 25W E27 G200 pink DIM 9290024539 LED classic 25W ST64 E27 gradient D SRT 9290024540 LED classic 25W G120 E27 gradient D 1PF 9290024541 LED CLA giant 28W E27 G200 gradient D 9290024542		
Dimming Performance	Dimming Range	Glowing	Dimming Performance	Dimming Range	Glowing	Dimming Performance	Dimming Range	Glowing
1-10	98% - 0%		1-10	97% - 0%		1-10	98% - 0%	
1-10	96% - 0%		1-10	96% - 0%		1-10	96% - 0%	
1-10	98% - 0%		1-10	99% - 0%		1-10	98% - 0%	
2-10	98% - 0%		2-10	96% - 0%		2-10	98% - 0%	
1-10	98% - 0%		1-10	97% - 0%		1-10	98% - 0%	
1-10	98% - 0%		1-10	100% - 0%		1-10	98% - 0%	
1-10	96% - 0%		1-10	98% - 0%		1-10	96% - 0%	
1-10	98% - 0%		1-10	96% - 0%		1-10	98% - 0%	
2-10	67% - 0%		1-10	96% - 0%		2-10	67% - 0%	
1-10	98% - 0%		1-10	97% - 0%		1-10	98% - 0%	
2-10	97% - 0%		1-10	97% - 0%		2-10	97% - 0%	
1-10	98% - 0%		1-10	96% - 0%		1-10	98% - 0%	
1-10	98% - 0%		1-10	98% - 0%		1-10	98% - 0%	
1-10	99% - 0%		1-10	97% - 0%		1-10	99% - 0%	
1-10	97% - 0%		1-10	97% - 0%		1-10	97% - 0%	
1-10	94% - 0%		1-10	97% - 0%		1-10	94% - 0%	
1-10	94% - 0%		1-10	97% - 0%		1-10	94% - 0%	
1-10	98% - 0%		1-10	96% - 0%		1-10	98% - 0%	
1-10	98% - 0%		1-10	98% - 0%		1-10	98% - 0%	
1-4	99% - 0%		1-8	99% - 0%		1-4	99% - 0%	
2-10	97% - 1%		1-10	96% - 0%		2-10	97% - 1%	
1-10	96% - 0%		1-10	95% - 0%		1-10	96% - 0%	
1-10	96% - 0%		1-10	96% - 0%		1-10	96% - 0%	
1-10	97% - 0%		1-10	99% - 0%		1-10	97% - 0%	
1-10	99% - 0%		1-10	96% - 0%		1-10	99% - 0%	
1-10	96% - 0%		1-10	90% - 0%		1-10	96% - 0%	
1-10	96% - 0%		1-10	95% - 0%		1-10	96% - 0%	
1-10	96% - 0%		1-10	96% - 0%		1-10	96% - 0%	
1-5	99% - 0%		1-9	100% - 0%		1-5	99% - 0%	
1-3	99% - 0%		1-3	95% - 1%		1-3	99% - 0%	
1-10	98% - 0%		1-10	97% - 0%		1-10	98% - 0%	
	N.A.	N.A.		N.A.	N.A.		N.A.	N.A.
1-10	97% - 0%		1-10	97% - 0%		1-10	97% - 0%	
1-10	98% - 0%		1-10	98% - 0%		1-10	98% - 0%	
1-10	98% - 0%		1-10	96% - 0%		1-10	98% - 0%	
1-4	99% - 0%		1-8	99% - 0%		1-4	99% - 0%	
2-10	98% - 0%		2-10	97% - 0%		2-10	98% - 0%	
2-10	97% - 0%		1-10	97% - 0%		2-10	97% - 0%	
1-7	99% - 0%		1-10	99% - 0%		1-7	99% - 0%	
1-10	97% - 0%		1-10	99% - 0%		1-10	97% - 0%	
1-10	97% - 0%		1-10	98% - 0%		1-10	97% - 0%	
1-10	98% - 0%		1-10	99% - 0%		1-10	98% - 0%	
1-10	98% - 0%		1-10	99% - 0%		1-10	98% - 0%	
1-10	97% - 0%		1-10	97% - 0%		1-10	97% - 0%	
1-10	98% - 0%		1-10	99% - 0%		1-10	98% - 0%	
1-10	98% - 0%		1-10	99% - 0%		1-10	98% - 0%	
1-10	97% - 2%		1-10	98% - 0%		1-10	97% - 2%	
1-10	99% - 0%		1-10	99% - 0%		1-10	99% - 0%	
1-10	98% - 0%		1-10	98% - 0%		1-10	98% - 0%	
1-10	98% - 0%		1-10	96% - 0%		1-10	98% - 0%	
1-3	98% - 0%		1-3	97% - 1%		1-3	98% - 0%	
1-3	99% - 0%		2-3	87% - 1%		1-3	99% - 0%	
1-10	97% - 0%		1-10	99% - 0%		1-10	97% - 0%	
1-10	98% - 0%		2-10	97% - 0%		1-10	98% - 0%	
1-3	98% - 0%		1-3	89% - 1%		1-3	98% - 0%	
1-10	98% - 0%		1-10	98% - 0%		1-10	98% - 0%	
1-10	97% - 0%		1-10	96% - 0%		1-10	97% - 0%	
1-10	97% - 5%		1-10	97% - 0%		1-10	97% - 5%	
1-10	97% - 0%		1-10	98% - 0%		1-10	97% - 0%	
1-3	98% - 0%		2-3	90% - 1%		1-3	98% - 0%	
	N.A.	N.A.	3	97% - 1%			N.A.	N.A.
	N.A.	N.A.	2-3	97% - 1%			N.A.	N.A.

# Professional LED Mains Voltage range

## Recommended dimmer compatibility list for Mains Voltage Lamps



### KEY

X - Y	Excellent dimming with X-Y lamps, however external factors can negatively influence the deep dimming performance
X - Y	See note below.
	Unexpected performance behavior, not in line with good dimming perception
N.A.	Dimmer lamp combination not applicable
T.B.D.	Dimmer lamp combination not tested

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab conditions and might contain faults

Brand	Type	Load
Berker   INSTA	286710	[RC] 20 – 360 W - Turn
Berker   INSTA	2973	[LED, R, L, C] 3 - 60W - Turn
Bticino   Legrand	BTN4411N (BTNT4411N, BTL4411N)	[LED] 3 - 75W - Tast
Busch Jaeger   ABB	2250 U	[R ] 60 – 600 W - Turn
Busch Jaeger   ABB	6513 U - 102	[RC] 40 – 420 W - Turn
Busch Jaeger   ABB	6523 U	[LED] 2 – 100 VA-LED - Turn
Busch Jaeger   ABB	6526 U	[LED] 2 – 100 VA-LED - Push (2wire)
Busch Jaeger   ABB	6523 U-102	[LED, R, L, C] 2 - 100W - Turn- Leading
Busch Jaeger   ABB	6523 U-102	[LED, R, L, C] 2 - 100W - Turn- Trailing
Busch Jaeger   ABB	6523 UR-103	[LED, R, L, C] 2 - 400W - Turn- Leading
Busch Jaeger   ABB	6523 UR-103	[LED, R, L, C] 2 - 400W - Turn- Trailing
ELKO   Schneider	SBD200LED (CCTEL10501)	[LED/RC] 4 - 200W(RC) 4-400W(RL)
ELKO   Schneider	SBD315RC (315 GLE )	[RC] 315W
SE LK   Schneider	LK FUGA LED-S 120VA (506Dx219)	[LED, RL] 4 - 120W - Slider
SE LK   Schneider	LK OPUS 66 LED-S 120VA (506Nx219)	[LED, RL] 4 - 120W - Slider
Eitako	EVD61NPN-UC	400W 3-wire Push Module
Eitako	EUD61NPL-230V	[LED, R, C] 4 - 200W - Module-Leading
Eitako	EUD61NPL-230V	[LED, R, C] 4 - 200W - Module-Trailing
Feller   Schneider	40200 (SBD200LED CCTCH10601)	[LED/RC] 4 - 200W(RC) 4-400W(RL)
Feller   Schneider	40300 (SBD315)	[RLC] 300W
Feller   Schneider	40200.LED.EB (CCT99100)	[LED, RL, RC] 4 - 20VA RL LED / 4 - 100VA RC LED
Gira	1176-00/01	[RLC] 50 – 420W
Gira	2390 00/ 100	[LED] 7 – 100W - Push (3wire)
Gira   INSTA	5401 00	[LED, R, L, C] 3 - 100W/200W- Tast
Gira   INSTA	2450 00	[LED, R, L, C] 3 - 60W - Turn
Hager	EVN 011	[RC] 300VA
Hager	EVN 012	[RC] 300W
Hager	EVN 004	[RL] 500VA
Jung	1271LEDDE	[LED] 3 – 100W - Push (3wire)
Jung   INSTA	1711DE	[LED, R, L, C] 3 - 100W/200W- Tast
Jung   INSTA	1730DD	[LED, R, L, C] 3 - 60W - Turn
Klik aan Klik uit	AWMD-250	[LED] 3- 24W
Klik aan Klik uit	ACM 300	300W - 3-wire Push LED Dimmer
Legrand	78401	[RLC] 40 – 500W
Legrand	67083	[RLC] 3 – 400W
Legrand	67084	[RLC] 8 - 300 VA - Push LED (3wire)
Legrand	67085 (078406)	[RLC] 8 - 300 VA - Push LED (3wire)
Legrand	L4402N	[R ] 60-500W
Merten   Schneider	SBD200LED (MEG5134-0000)	[LED/RC] 4 - 200W(RC) 4-400W(RL)
Merten   Schneider	SBD315RC (MEG5136-0000)	[RC] 315W
Merten   Schneider	MEG5300-0001 (CCT99100)	[LED, RL, RC] 4 - 20VA RL LED / 4 - 100VA RC LED
MK - Electric	K1535	[R] 65 - 450 W - Turn
MK - Electric	K1501 WHILV	[R] 60 - 500 W - Turn
MK - Electric	K4501 WHILV	[RLC] 180W
MK - Electric	K4500 WHILV	[RLC] 400W
NIKO	310-0280X	[LED] 2 -100 VA
Niko	310-02901	[LED, R, L, C] 3 - 200W - Tast
Niko	310-03901	[LED, R, L, C] 3 - 200W - Turn
PEHA	431HAN	[RL] 6-120W [LED] 6-60W
Philips	UID8670	[LED] 2 – 100 VA-LED - Push (3wire)
RELCO	RP0977	[LED] 4-100W
RELCO	RM0545	[LED] 4-100W
Schneider	SBD315RC (SBD 315, SDD 315, ATD315, CCT011533)	[RC] 315W
Schneider	SBD200 (WDE 002299)	[ ] 4-400VA - Turn Universal (2wire)
Schneider	SAE dimmer puck CCT99100	[LED, RL, RC] 4 - 20VA RL LED / 4 - 100VA RC LED
VADSBO	ED 350	[RC] 50 – 350W
VADSBO	DU 250	[RC] 20 – 250W
VADSBO	VD300	[LED] 0 - 300VA - Turn
Varilight	HQ3W	[R] 60-400W
Varilight	ICT401 M	[RC] 20-400W
Vimar	20148	[RL] 500W
Vimar	20162	[RL] 40-300W
Vimar	Universal dimmer 20135.1	[LED] 3 - 200W - Tast
Vimar	Universal dimmer 20136.1	[LED] 3 - 200W - Turn- Leading
Vimar	Universal dimmer 20136.1	[LED] 3 - 200W - Turn- Trailing
Philips Dynalite	DDLE801	(100W per channel)
Philips Dynalite	DDMC802 (913703243509)	(x W per channel)-leading
Philips Dynalite	DDMC802 (913703243509)	(x W per channel)-Trailing

LED Bulb								
LEDClassic 40W Diamond E27 2700K CL D 9290019357 LED diamond_giant 35W E27 CL DIM 9290020946 LEDClassic 40W Mushroom E27 1800K GOLD D 9290029840			LED giant 20W E27 A160 1800K smoky D 9290029825 LED giant 20W E27 G200 1800K smoky D 9290029826 LED giant 20W E27 T65 1800K smoky D 9290029827 LED double layers 20W E27 smoky DIM 9290029823			LED classic-giant 40W E27 A160 GOLD DIM 9290029835 LED classic-giant 40W E27 G200 GOLD DIM 9290029836 LED classic-giant 40W E27 T65 GOLD DIM 9290029837 LED giant crystal 26W E27 smoky DIM 9290029824		
Dimming Performance	Dimming Range	Glowing	Dimming Performance	Dimming Range	Glowing	Dimming Performance	Dimming Range	Glowing
1-10	98% - 0%		1-10	100% - 0%		1-10	100% - 0%	
1-10	96% - 0%		1-9	100% - 0%		1-9	100% - 0%	
1-10	98% - 0%		1-10	99% - 0%		1-10	99% - 0%	
2-10	98% - 0%		2-10	100% - 0%		2-10	100% - 0%	
1-10	98% - 0%		2-10	98% - 0%		2-10	98% - 0%	
1-10	98% - 0%		1-10	99% - 0%		1-10	99% - 0%	
1-10	96% - 0%		1-10	98% - 0%		1-10	98% - 0%	
1-10	98% - 0%			N.A.	N.A.		N.A.	N.A.
2-10	67% - 0%		1-10	98% - 0%		1-10	98% - 0%	
1-10	98% - 0%		1-10	99% - 0%		1-10	99% - 0%	
2-10	97% - 0%		1-10	98% - 0%		1-10	98% - 0%	
1-10	98% - 0%		1-10	99% - 0%		1-10	99% - 0%	
1-10	98% - 0%		1-9	98% - 0%		1-9	98% - 0%	
1-10	99% - 0%		1-10	99% - 0%		1-10	99% - 0%	
1-10	97% - 0%		1-10	99% - 0%		1-10	99% - 0%	
1-10	94% - 0%		1-10	97% - 0%		1-10	97% - 0%	
1-10	94% - 0%		1-10	97% - 0%		1-10	97% - 0%	
1-10	98% - 0%		1-10	99% - 0%		1-10	99% - 0%	
1-10	98% - 0%		1-9	98% - 0%		1-9	98% - 0%	
1-4	99% - 0%		1-3	100% - 0%		1-3	100% - 0%	
2-10	97% - 1%			N.A.	N.A.		N.A.	N.A.
1-10	96% - 0%		1-10	99% - 0%		1-10	99% - 0%	
1-10	96% - 0%		1-9	100% - 0%		1-9	100% - 0%	
1-10	97% - 0%		1-9	79% - 0%		1-9	79% - 0%	
1-10	97% - 0%			N.A.	N.A.		N.A.	N.A.
1-10	99% - 0%		1-10	98% - 0%		1-10	98% - 0%	
1-10	96% - 0%		1-10	98% - 0%		1-10	98% - 0%	
1-10	96% - 0%		1-10	99% - 0%		1-10	99% - 0%	
1-10	96% - 0%		1-9	100% - 0%		1-9	100% - 0%	
1-5	99% - 0%		1-3	99% - 0%		1-3	99% - 0%	
1-3	99% - 0%		1-3	97% - 0%		1-3	97% - 0%	
1-10	98% - 0%		1-10	99% - 0%		1-10	99% - 0%	
	N.A.	N.A.		N.A.	N.A.		N.A.	N.A.
1-10	97% - 0%		1-9	75% - 0%		1-9	75% - 0%	
1-10	98% - 0%			N.A.	N.A.		N.A.	N.A.
1-10	98% - 0%		1-10	99% - 0%		1-10	99% - 0%	
1-10	98% - 0%		1-9	98% - 0%		1-9	98% - 0%	
1-4	99% - 0%		1-3	100% - 0%		1-3	100% - 0%	
2-10	98% - 0%		2-10	99% - 0%		2-10	99% - 0%	
2-10	97% - 0%		1-10	99% - 0%		1-10	99% - 0%	
1-7	99% - 0%		1-5	99% - 0%		1-5	99% - 0%	
1-10	97% - 0%		1-10	99% - 0%		1-10	99% - 0%	
1-10	97% - 0%		1-10	79% - 0%		1-10	79% - 0%	
1-10	98% - 0%		1-10	99% - 0%		1-10	99% - 0%	
1-10	98% - 0%		1-10	99% - 0%		1-10	99% - 0%	
1-10	97% - 0%		1-10	98% - 0%		1-10	98% - 0%	
1-10	98% - 0%		1-10	99% - 0%		1-10	99% - 0%	
1-10	97% - 2%		1-10	71% - 0%		1-10	71% - 0%	
1-10	99% - 0%		1-10	100% - 0%		1-10	100% - 0%	
1-10	98% - 0%		1-9	98% - 0%		1-9	98% - 0%	
1-10	98% - 0%		1-10	99% - 0%		1-10	99% - 0%	
1-3	98% - 0%		1-3	100% - 0%		1-3	100% - 0%	
1-3	99% - 0%		1-3	99% - 0%		1-3	99% - 0%	
1-10	97% - 0%		2-9	82% - 0%		2-9	82% - 0%	
1-10	98% - 0%		2-10	99% - 0%		2-10	99% - 0%	
1-3	98% - 0%		1-3	99% - 0%		1-3	99% - 0%	
1-10	98% - 0%		1-10	97% - 0%		1-10	97% - 0%	
1-10	97% - 0%		1-10	98% - 0%		1-10	98% - 0%	
1-10	97% - 5%		1-10	98% - 0%		1-10	98% - 0%	
1-10	97% - 0%		1-10	98% - 0%		1-10	98% - 0%	
1-3	98% - 0%		1-3	96% - 0%		1-3	96% - 0%	
	N.A.	N.A.	1-3	96% - 0%		1-3	96% - 0%	
	N.A.	N.A.	3	99% - 0%		3	99% - 0%	



# Professional LED Mains Voltage range

## Recommended dimmer compatibility list for Mains Voltage Lamps



### KEY

X - Y	Excellent dimming with X-Y lamps, however external factors can negatively influence the deep dimming performance
X - Y	See note below.
	Unexpected performance behavior, not in line with good dimming perception
N.A.	Dimmer lamp combination not applicable
T.B.D.	Dimmer lamp combination not tested

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab conditions and might contain faults

Brand	Type	Load
Berker   INSTA	286710	[RC] 20 – 360 W - Turn
Berker   INSTA	2973	[LED, R, L, C] 3 - 60W - Turn
Bticino   Legrand	BTN4411N (BTNT4411N, BTL4411N)	[LED] 3 - 75W - Tast
Busch Jaeger   ABB	2250 U	[R ] 60 – 600 W - Turn
Busch Jaeger   ABB	6513 U - 102	[RC] 40 – 420 W - Turn
Busch Jaeger   ABB	6523 U	[LED] 2 – 100 VA-LED - Turn
Busch Jaeger   ABB	6526 U	[LED] 2 – 100 VA-LED - Push (2wire)
Busch Jaeger   ABB	6523 U-102	[LED, R, L, C] 2 - 100W - Turn- Leading
Busch Jaeger   ABB	6523 U-102	[LED, R, L, C] 2 - 100W - Turn- Trailing
Busch Jaeger   ABB	6523 UR-103	[LED, R, L, C] 2 - 400W - Turn- Leading
Busch Jaeger   ABB	6523 UR-103	[LED, R, L, C] 2 - 400W - Turn- Trailing
ELKO   Schneider	SBD200LED (CCTEL10501)	[LED/RC] 4 - 200W(RC) 4-400W(RL)
ELKO   Schneider	SBD315RC (315 GLE )	[RC] 315W
SE LK   Schneider	LK FUGA LED-S 120VA (506Dx219)	[LED, RL] 4 - 120W - Slider
SE LK   Schneider	LK OPUS 66 LED-S 120VA (506Nx219)	[LED, RL] 4 - 120W - Slider
Eitako	EVD61NPN-UC	400W 3-wire Push Module
Eitako	EUD61NPL-230V	[LED, R, C] 4 - 200W - Module-Leading
Eitako	EUD61NPL-230V	[LED, R, C] 4 - 200W - Module-Trailing
Feller   Schneider	40200 (SBD200LED CCTCH10601)	[LED/RC] 4 - 200W(RC) 4-400W(RL)
Feller   Schneider	40300 (SBD315)	[RLC] 300W
Feller   Schneider	40200.LED.EB (CCT99100)	[LED, RL, RC] 4 - 20VA RL LED / 4 - 100VA RC LED
Gira	1176-00/01	[RLC] 50 – 420W
Gira	2390 00/ 100	[LED] 7 – 100W - Push (3wire)
Gira   INSTA	5401 00	[LED, R, L, C] 3 - 100W/200W- Tast
Gira   INSTA	2450 00	[LED, R, L, C] 3 - 60W - Turn
Hager	EVN 011	[RC] 300VA
Hager	EVN 012	[RC] 300W
Hager	EVN 004	[RL] 500VA
Jung	1271LEDDE	[LED] 3 – 100W - Push (3wire)
Jung   INSTA	1711DE	[LED, R, L, C] 3 - 100W/200W- Tast
Jung   INSTA	1730DD	[LED, R, L, C] 3 - 60W - Turn
Klik aan Klik uit	AWMD-250	[LED] 3- 24W
Klik aan Klik uit	ACM 300	300W - 3-wire Push LED Dimmer
Legrand	78401	[RLC] 40 – 500W
Legrand	67083	[RLC] 3 – 400W
Legrand	67084	[RLC] 8 - 300 VA - Push LED (3wire)
Legrand	67085 (078406)	[RLC] 8 - 300 VA - Push LED (3wire)
Legrand	L4402N	[R ] 60-500W
Merten   Schneider	SBD200LED (MEG5134-0000)	[LED/RC] 4 - 200W(RC) 4-400W(RL)
Merten   Schneider	SBD315RC (MEG5136-0000)	[RC] 315W
Merten   Schneider	MEG5300-0001 (CCT99100)	[LED, RL, RC] 4 - 20VA RL LED / 4 - 100VA RC LED
MK - Electric	K1535	[R] 65 – 450 W - Turn
MK - Electric	K1501 WHILV	[R] 60 – 500 W - Turn
MK - Electric	K4501 WHILV	[RC] 180W
MK - Electric	K4500 WHILV	[RLC] 400W
NIKO	310-0280X	[LED] 2 -100 VA
Niko	310-02901	[LED, R, L, C] 3 - 200W - Tast
Niko	310-03901	[LED, R, L, C] 3 - 200W - Turn
PEHA	431HAN	[RL] 6-120W [LED] 6-60W
Philips	UID8670	[LED] 2 – 100 VA-LED - Push (3wire)
RELCO	RP0977	[LED] 4-100W
RELCO	RM0545	[LED] 4-100W
Schneider	SBD315RC (SBD 315, SDD 315, ATD315, CCT011533)	[RC] 315W
Schneider	SBD200 (WDE 002299)	[ ] 4-400VA - Turn Universal (2wire)
Schneider	SAE dimmer puck CCT99100	[LED, RL, RC] 4 - 20VA RL LED / 4 - 100VA RC LED
VADSBO	ED 350	[RC] 50 – 350W
VADSBO	DU 250	[RC] 20 – 250W
VADSBO	VD300	[LED] 0 - 300VA - Turn
Varilight	HQ3W	[R] 60-400W
Varilight	ICT401 M	[RC] 20-400W
Vimar	20148	[RL] 500W
Vimar	20162	[RL] 40-300W
Vimar	Universal dimmer 20135.1	[LED] 3 - 200W - Tast
Vimar	Universal dimmer 20136.1	[LED] 3 - 200W - Turn- Leading
Vimar	Universal dimmer 20136.1	[LED] 3 - 200W - Turn- Trailing
Philips Dynalite	DDLE801	(100W per channel)
Philips Dynalite	DDMC802 (913703243509)	(x W per channel)-leading
Philips Dynalite	DDMC802 (913703243509)	(x W per channel)-Trailing

LED Spot								
MAS LEDspot PAR20 D 50W 927 25D 9290034857 MAS LEDspot PAR20 D 50W 930 25D 9290034858 MAS LEDspot PAR20 D 50W 940 25D 9290034859 MAS LEDspot PAR20 D 50W 927 40D 9290034860 MAS LEDspot PAR20 D 50W 930 40D 9290034861 MAS LEDspot PAR20 D 50W 940 40D 9290034862			MAS LEDspot PAR30S D 75W 927 25D 9290034854 MAS LEDspot PAR30S D 75W 930 25D 9290034855 MAS LEDspot PAR30S D 75W 940 25D 9290034856			MAS LEDspot PAR38 D 100W 927 25D 9290034852		
Dimming Performance	Dimming Range	Glowing	Dimming Performance	Dimming Range	Glowing	Dimming Performance	Dimming Range	Glowing
1-10	98% - 0%		1-8	94% - 0%		1-5	98% - 0%	
	N.A.	N.A.		N.A.	N.A.	1-5	99% - 0%	
1-10	98% - 0%		1-8	94% - 0%		1-5	98% - 0%	
1-20	98% - 0%		1-10	94% - 0%		1-10	98% - 0%	
1-20	98% - 0%		1-10	93% - 0%		1-10	98% - 0%	
1-15	98% - 0%		1-10	96% - 0%		1-8	98% - 0%	
1-20	99% - 0%		1-11	99% - 0%		1-8	100% - 0%	
1-15	99% - 0%		1-10	97% - 0%		1-8	99% - 0%	
1-15	98% - 0%		1-10	97% - 0%		1-8	99% - 0%	
1-20	98% - 0%		1-20	95% - 0%		1-10	99% - 0%	
1-20	98% - 0%		1-20	95% - 0%		1-10	99% - 0%	
1-15	100% - 0%		1-8	99% - 0%		1-6	100% - 0%	
1-10	98% - 0%		1-5	94% - 0%		1-5	98% - 0%	
1-20	98% - 0%		1-10	94% - 0%		1-10	99% - 0%	
1-10	98% - 0%		1-8	95% - 0%		1-5	98% - 0%	
2-20	98% - 14%		1-20	93% - 0%		1-10	97% - 0%	
1-20	98% - 0%		1-20	93% - 0%		1-10	97% - 0%	
1-15	100% - 0%		1-8	99% - 0%		1-6	100% - 0%	
1-10	98% - 0%		1-5	94% - 0%		1-5	98% - 0%	
1-3	99% - 0%		1-2	94% - 0%		1-2	98% - 0%	
1-10	98% - 6%		2-8	91% - 0%		1-5	99% - 7%	
1-15	99% - 0%		1-10	95% - 0%		1-8	99% - 0%	
	N.A.	N.A.		N.A.	N.A.	1-5	99% - 0%	
1-10	99% - 0%		1-5	94% - 0%		1-5	98% - 0%	
1-15	99% - 0%		1-10	95% - 0%		1-8	99% - 0%	
1-15	98% - 0%		1-10	94% - 0%		2-8	98% - 14%	
1-15	98% - 0%		1-10	94% - 0%		1-8	97% - 0%	
1-15	99% - 0%		1-10	95% - 0%		1-8	99% - 0%	
	N.A.	N.A.		N.A.	N.A.	1-5	99% - 0%	
1-3	99% - 0%		1-3	94% - 0%		1-2	83% - 3%	
1-10	98% - 0%		1-8	95% - 0%		1-5	98% - 0%	
1-10	100% - 0%		1-6	99% - 0%		1-5	100% - 0%	
1	98% - 1%		1	93% - 1%		1-8	97% - 0%	
1-15	100% - 0%		1-8	99% - 0%		1-6	100% - 0%	
1-10	98% - 0%		1-5	94% - 0%		1-5	98% - 0%	
1-3	99% - 0%		1-2	94% - 0%		1-2	98% - 0%	
1-15	99% - 0%		1-8	93% - 1%		1-5	98% - 0%	
	N.A.	N.A.		N.A.	N.A.	1-8	97% - 0%	
						1-3	98% - 2%	
2-12	97% - 0%	N.A.	1-8	99% - 0%		1-6	100% - 0%	
2-5	98% - 23%		1-10	96% - 5%		1-8	97% - 0%	
1-15	98% - 0%		1-20	95% - 0%		1-8	100% - 0%	
1-15	98% - 0%		1-20	95% - 0%		1-8	100% - 0%	
2-15	98% - 11%		1-5	94% - 0%		1-5	98% - 0%	
1-15	98% - 0%			N.A.	N.A.	1-8	98% - 0%	
1-20	98% - 0%		1-15	98% - 0%		1-8	100% - 0%	
1-15	99% - 0%		1-10	93% - 0%		1-8	97% - 2%	
1-10	98% - 0%		1-5	94% - 0%		1-5	98% - 0%	
1-13	100% - 0%		1-8	99% - 0%		1-6	100% - 0%	
1-3	99% - 0%		1-2	94% - 0%		1-2	98% - 0%	
1-10	99% - 0%		1-6	95% - 0%		1-5	97% - 0%	
1-10	99% - 0%		1-8	92% - 0%		1-5	98% - 0%	
1-15	98% - 0%		1-8	94% - 0%		1-5	98% - 0%	
1-20	98% - 3%		1-20	95% - 2%		1-5	97% - 6%	
1-20	98% - 0%		1-20	93% - 0%		1-10	98% - 4%	
1-20	98% - 0%		1-20	93% - 0%		1-10	97% - 5%	
1-8	99% - 0%		1-5	99% - 0%		1-4	99% - 0%	
	N.A.	N.A.	5-10	100% - 0%			N.A.	N.A.
5-15	99% - 0%		5-10	100% - 0%		3-7	100% - 0%	

# Professional LED Mains Voltage range

Recommended dimmer compatibility list for Mains Voltage Lamps



## KEY

X - Y	Excellent dimming with X-Y lamps, however external factors can negatively influence the deep dimming performance
X - Y	See note below.
	Unexpected performance behavior, not in line with good dimming perception
N.A.	Dimmer lamp combination not applicable
T.B.D.	Dimmer lamp combination not tested

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab conditions and might contain faults

Brand	Type	Load
Berker   INSTA	286710	[RC] 20 – 360 W - Turn
Berker   INSTA	2973	[LED, R, L, C] 3 – 60W - Turn
Bticino   Legrand	BTN4411N (BTNT4411N, BTL4411N)	[LED] 3 – 75W - Tast
Busch Jaeger   ABB	2250 U	[R ] 60 – 600 W - Turn
Busch Jaeger   ABB	6513 U - 102	[RC] 40 – 420 W - Turn
Busch Jaeger   ABB	6523 U	[LED] 2 – 100 VA-LED - Turn
Busch Jaeger   ABB	6526 U	[LED] 2 – 100 VA-LED - Push (2wire)
Busch Jaeger   ABB	6523 U-102	[LED, R, L, C] 2 – 100W - Turn- Leading
Busch Jaeger   ABB	6523 U-102	[LED, R, L, C] 2 – 100W - Turn- Trailing
Busch Jaeger   ABB	6523 UR-103	[LED, R, L, C] 2 – 400W - Turn- Leading
Busch Jaeger   ABB	6523 UR-103	[LED, R, L, C] 2 – 400W - Turn- Trailing
ELKO   Schneider	SBD200LED (CCTEL10501)	[LED/RC] 4 – 200W(RC) 4-400W(RL)
ELKO   Schneider	SBD315RC (315 GLE )	[RC] 315W
SE LK   Schneider	LK FUGA LED-S 120VA (506Dx219)	[LED, RL] 4 – 120W - Slider
SE LK   Schneider	LK OPUS 66 LED-S 120VA (506Nx219)	[LED, RL] 4 – 120W - Slider
Eitako	EVD61NPN-UC	400W 3-wire Push Module
Eitako	EUD61NPL-230V	[LED, R, C] 4 – 200W - Module-Leading
Eitako	EUD61NPL-230V	[LED, R, C] 4 – 200W - Module-Trailing
Feller   Schneider	40200 (SBD200LED CCTCH10601)	[LED/RC] 4 – 200W(RC) 4-400W(RL)
Feller   Schneider	40300 (SBD315)	[RLC] 300W
Feller   Schneider	40200.LED.EB (CCT99100)	[LED, RL, RC] 4 – 20VA RL LED / 4 – 100VA RC LED
Gira	1176-00/01	[RLC] 50 – 420W
Gira	2390 00/ 100	[LED] 7 – 100W - Push (3wire)
Gira   INSTA	5401 00	[LED, R, L, C] 3 – 100W/200W- Tast
Gira   INSTA	2450 00	[LED, R, L, C] 3 – 60W - Turn
Hager	EVN 011	[RC] 300VA
Hager	EVN 012	[RC] 300W
Hager	EVN 004	[RL] 500VA
Jung	1271LEDDE	[LED] 3 – 100W - Push (3wire)
Jung   INSTA	1711DE	[LED, R, L, C] 3 – 100W/200W- Tast
Jung   INSTA	1730DD	[LED, R, L, C] 3 – 60W - Turn
Klik aan Klik uit	AWMD-250	[LED] 3– 24W
Klik aan Klik uit	ACM 300	300W - 3-wire Push LED Dimmer
Legrand	78401	[RLC] 40 – 500W
Legrand	67083	[RLC] 3 – 400W
Legrand	67084	[RLC] 8 – 300 VA - Push LED (3wire)
Legrand	67085 (078406)	[RLC] 8 – 300 VA - Push LED (3wire)
Legrand	L4402N	[R ] 60-500W
Merten   Schneider	SBD200LED (MEG5134-0000)	[LED/RC] 4 – 200W(RC) 4-400W(RL)
Merten   Schneider	SBD315RC (MEG5136-0000)	[RC] 315W
Merten   Schneider	MEG5300-0001 (CCT99100)	[LED, RL, RC] 4 – 20VA RL LED / 4 – 100VA RC LED
MK - Electric	K1535	[R] 65 – 450 W - Turn
MK - Electric	K1501 WHILV	[R] 60 – 500 W - Turn
MK - Electric	K4501 WHILV	[RLC] 180W
MK - Electric	K4500 WHILV	[RLC] 400W
NIKO	310-0280X	[LED] 2 – 100 VA
Niko	310-02901	[LED, R, L, C] 3 – 200W - Tast
Niko	310-03901	[LED, R, L, C] 3 – 200W - Turn
PEHA	431HAN	[RL] 6-120W [LED] 6-60W
Philips	UID8670	[LED] 2 – 100 VA-LED - Push (3wire)
RELCO	RP0977	[LED] 4-100W
RELCO	RM0545	[LED] 4-100W
Schneider	SBD315RC (SBD 315, SDD 315, ATD315, CCT011533)	[RC] 315W
Schneider	SBD200 (WDE 002299)	[ ] 4-400VA - Turn Universal (2wire)
Schneider	SAE dimmer puck CCT99100	[LED, RL, RC] 4 – 20VA RL LED / 4 – 100VA RC LED
VADSBO	ED 350	[RC] 50 – 350W
VADSBO	DU 250	[RC] 20 – 250W
VADSBO	V0300	[LED] 0 – 300VA - Turn
Varilight	HQ3W	[R] 60-400W
Varilight	ICT401 M	[RC] 20-400W
Vimar	20148	[RL] 500W
Vimar	20162	[RL] 40-300W
Vimar	Universal dimmer 20135.1	[LED] 3 – 200W - Tast
Vimar	Universal dimmer 20136.1	[LED] 3 – 200W - Turn- Leading
Vimar	Universal dimmer 20136.1	[LED] 3 – 200W - Turn- Trailing
Philips Dynalite	DDLE801	(100W per channel)
Philips Dynalite	DDMC802 (913703243509)	(x W per channel)-leading
Philips Dynalite	DDMC802 (913703243509)	(x W per channel)-Trailing

LED Spot								
MAS LED ExpertColor 3.9-35W GU10 927 25D 9290013464 MAS LED ExpertColor 3.9-35W GU10 930 25D 9290013465 MAS LED ExpertColor 3.9-35W GU10 930 36D 9290013468 MAS LED ExpertColor 3.9-35W GU10 940 36D 9290013469 MAS LED ExpertColor 3.9-35W GU10 950 25D 9290013466 MAS LED ExpertColor 3.9-35W GU10 927 36D 9290013467			MAS LED ExpertColor 5.5-50W GU10 927 25D 9290013470 MAS LED ExpertColor 5.5-50W GU10 927 36D 9290013473 MAS LED ExpertColor 5.5-50W GU10 930 25D 9290013471 MAS LED ExpertColor 5.5-50W GU10 940 25D 9290013472 MAS LED ExpertColor 5.5-50W GU10 930 36D 9290013474 MAS LED ExpertColor 5.5-50W GU10 940 36D 9290013475 MASLED ExpertColor5.5-50W GU10 927 25DUK 9290013470 MASLED ExpertColor5.5-50W GU10 927 36DUK 9290013473 MASLEDExpertColor 5.5-50W GU10 930 36DUK 9290013474			MASTER LEDspot VALUE D 3.7-35W GU10 36D 927 CRI90 9290013482 MASTER LEDspot VALUE D 3.7-35W GU10 60D 930 CRI90 9290013483 MAS LED spot VLE D 3.7-35W GU10 940 36D 9290013484 MAS LED spot VLE D 3.7-35W GU10 927 36D 9290029794 MAS LED spot VLE DT 3.7-35W GU10 927 36D 9290029797 MAS LED spot VLE D 3.7-35W GU10 927 60D 9290029798 MAS LED spot VLE D 3.7-35W GU10 930 60D 9290029799 MAS LED spot VLE D 3.7-35W GU10 940 60D 9290013487		
Dimming Performance	Dimming Range	Glowing	Dimming Performance	Dimming Range	Glowing	Dimming Performance	Dimming Range	Glowing
1-15	98% - 15%		1-10	99% - 9%		1-15	98% - 12%	
1-15	99% - 3%		1-11	99% - 4%		1-16	99% - 7%	
1-15	95% - 3%		1-10	100% - 0%		1-15	98% - 0%	
1-20	94% - 0%	2	1-20	100% - 0%		1,3-20	99% - 0%	
1-20	94% - 16%		1-20	100% - 10%		1-20	98% - 13%	
1-20	98% - 6%		1-18	99% - 0%		1-20	98% - 3%	
1-20	94% - 19%		1-15	100% - 15%		1-20	98% - 17%	
1-20	99% - 4%		1-15	98% - 0%		1-20	98% - 0%	
1-20	99% - 4%		1-15	98% - 0%		2-20	98% - 1%	
1-20	98% - 0%		2-20	98% - 0%		1-20	98% - 0%	
1-20	99% - 0%		2-20	99% - 0%		2-20	99% - 0%	
1-20	97% - 13%		1-15	98% - 13%		1-20	97% - 9%	
1-15	97% - 2%		1-10	98% - 0%		2-15	98% - 0%	
1-20	98% - 18%		1-20	98% - 13%		1-20	98% - 15%	
1-20	98% - 18%		1-20	98% - 13%		1-20	98% - 15%	
1-20	98% - 2%		1-15	98% - 0%		1-20	98% - 0%	
1-20	98% - 0%		1-20	99% - 0%		1-20	77% - 0%	
1-20	98% - 0%		1-20	99% - 0%		1-20	98% - 0%	
1-20	97% - 13%		1-15	98% - 13%		1-20	97% - 9%	
1-15	97% - 2%		1-10	98% - 0%		2-15	98% - 0%	
1-5	96% - 18%		1-3	98% - 13%		1-5	98% - 15%	
1-20	98% - 29%		1-15	99% - 24%		1-20	98% - 28%	
1-20	98% - 8%		1-15	98% - 3%		1-20	99% - 5%	
1-15	99% - 3%		1-11	99% - 4%		1-16	99% - 7%	
1-15	98% - 8%		1-10	98% - 1%		1-15	99% - 4%	
1-20	97% - 20%		1-15	99% - 11%		1-20	99% - 17%	
1-20	99% - 13%		1-15	99% - 9%		1-20	98% - 10%	
1-20	99% - 6%		1-15	98% - 0%		1-20	98% - 3%	
1-20	98% - 8%		1-15	98% - 3%		1-20	99% - 5%	
1-15	99% - 3%		1-11	99% - 4%		1-16	99% - 7%	
1-5	97% - 0%		1-3	97% - 0%		1-5	99% - 0%	
1-20	98% - 0%		1-15	96% - 0%		1-20	98% - 0%	
1-20	98% - 3%		1-15	99% - 1%		1-20	97% - 1%	
1-15	98% - 0%		1-10	98% - 0%		1-15	97% - 0%	
2-20	97% - 38%		2-15	97% - 34%		2-20	98% - 38%	
1-20	97% - 13%		1-15	98% - 13%		1-20	97% - 9%	
1-15	97% - 2%		1-10	98% - 0%		2-15	98% - 0%	
1-5	96% - 18%		1-3	98% - 13%		1-5	98% - 15%	
1-20	97% - 23%		2-15	98% - 19%		1-20	98% - 22%	
1-20	98% - 16%		1-15	97% - 12%		1-20	97% - 9%	
1-11	96% - 7%		1-8	95% - 13%		1-12	99% - 13%	
1-20	99% - 18%		1-15	99% - 13%		1-20	97% - 10%	
1-20	98% - 6%		1-15	99% - 0%		1-20	97% - 0%	
1-20	98% - 18%		1-20	98% - 16%		1-20	97% - 15%	
1-20	98% - 18%		1-20	98% - 16%		1-20	97% - 15%	
1-15	98% - 19%		1-10	99% - 18%		1-15	98% - 19%	
1-20	98% - 6%		1-18	99% - 0%		1-20	98% - 3%	
1-20	97% - 28%		1-15	99% - 23%		1-20	98% - 27%	
1-20	97% - 8%		1-15	97% - 2%		1-20	97% - 7%	
1-15	97% - 2%		1-10	98% - 0%		2-15	98% - 0%	
1-20	97% - 13%		1-15	98% - 13%		1-20	97% - 9%	
1-5	96% - 18%		1-3	98% - 13%		1-5	98% - 15%	
1-18	97% - 15%		1-13	96% - 20%		1-19	99% - 36%	
1-13	95% - 0%		1-9	95% - 0%		1-14	98% - 0%	
1-15	97% - 30%		1-10	99% - 25%		1-15	97% - 29%	
1-20	98% - 26%		1-15	99% - 20%		2-20	97% - 26%	
1-20	95% - 6%		1-15	94% - 11%		1-20	99% - 11%	
2-20	98% - 16%		1-15	98% - 8%		2-20	98% - 13%	
1-20	99% - 35%		1-20	98% - 27%		1-20	97% - 35%	
1-20	99% - 29%		1-20	100% - 25%		1-20	97% - 33%	
1-20	99% - 29%		1-20	99% - 25%		1-20	97% - 33%	
1-12	99% - 0%		1-8	99% - 0%		1-12	98% - 0%	
2-20	98% - 0%		3-17	99% - 0%		4-20	98% - 0%	
3-20	99% - 0%		1-17	99% - 0%		4-20	98% - 0%	

# Professional LED Mains Voltage range

Recommended dimmer compatibility list for Mains Voltage Lamps






## KEY

X - Y	Excellent dimming with X-Y lamps, however external factors can negatively influence the deep dimming performance
X - Y	See note below.
	Unexpected performance behavior, not in line with good dimming perception
N.A.	Dimmer lamp combination not applicable
T.B.D.	Dimmer lamp combination not tested

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab conditions and might contain faults

Brand	Type	Load
Berker   INSTA	286710	[RC] 20 – 360 W - Turn
Berker   INSTA	2973	[LED, R, L, C] 3 – 60W - Turn
Bticino   Legrand	BTN4411N (BTNT4411N, BTL4411N)	[LED] 3 – 75W - Tast
Busch Jaeger   ABB	2250 U	[R ] 60 – 600 W - Turn
Busch Jaeger   ABB	6513 U - 102	[RC] 40 – 420 W - Turn
Busch Jaeger   ABB	6523 U	[LED] 2 – 100 VA-LED - Turn
Busch Jaeger   ABB	6526 U	[LED] 2 – 100 VA-LED - Push (2wire)
Busch Jaeger   ABB	6523 U-102	[LED, R, L, C] 2 – 100W - Turn- Leading
Busch Jaeger   ABB	6523 U-102	[LED, R, L, C] 2 – 100W - Turn- Trailing
Busch Jaeger   ABB	6523 UR-103	[LED, R, L, C] 2 – 400W - Turn- Leading
Busch Jaeger   ABB	6523 UR-103	[LED, R, L, C] 2 – 400W - Turn- Trailing
ELKO   Schneider	SBD200LED (CCTEL10501)	[LED/RC] 4 – 200W(RC) 4–400W(RL)
ELKO   Schneider	SBD315RC (315 GLE )	[RC] 315W
SE LK   Schneider	LK FUGA LED-S 120VA (506Dx219)	[LED, RL] 4 – 120W - Slider
SE LK   Schneider	LK OPUS 66 LED-S 120VA (506Nx219)	[LED, RL] 4 – 120W - Slider
Eitako	EVD61NPN-UC	400W 3-wire Push Module
Eitako	EUD61NPL-230V	[LED, R, C] 4 – 200W - Module-Leading
Eitako	EUD61NPL-230V	[LED, R, C] 4 – 200W - Module-Trailing
Feller   Schneider	40200 (SBD200LED CCTCH10601)	[LED/RC] 4 – 200W(RC) 4–400W(RL)
Feller   Schneider	40300 (SBD315)	[RLC] 300W
Feller   Schneider	40200.LED.EB (CCT99100)	[LED, RL, RC] 4 – 20VA RL LED / 4 – 100VA RC LED
Gira	1176-00/01	[RLC] 50 – 420W
Gira	2390 00/ 100	[LED] 7 – 100W - Push (3wire)
Gira   INSTA	5401 00	[LED, R, L, C] 3 – 100W/200W- Tast
Gira   INSTA	2450 00	[LED, R, L, C] 3 – 60W - Turn
Hager	EVN 011	[RC] 300VA
Hager	EVN 012	[RC] 300W
Hager	EVN 004	[RL] 500VA
Jung	1271LEDDE	[LED] 3 – 100W - Push (3wire)
Jung   INSTA	1711DE	[LED, R, L, C] 3 – 100W/200W- Tast
Jung   INSTA	1730DD	[LED, R, L, C] 3 – 60W - Turn
Klik aan Klik uit	AWMD-250	[LED] 3– 24W
Klik aan Klik uit	ACM 300	300W - 3-wire Push LED Dimmer
Legrand	78401	[RLC] 40 – 500W
Legrand	67083	[RLC] 3 – 400W
Legrand	67084	[RLC] 8 – 300 VA - Push LED (3wire)
Legrand	67085 (078406)	[RLC] 8 – 300 VA - Push LED (3wire)
Legrand	L4402N	[R ] 60–500W
Merten   Schneider	SBD200LED (MEG5134-0000)	[LED/RC] 4 – 200W(RC) 4–400W(RL)
Merten   Schneider	SBD315RC (MEG5136-0000)	[RC] 315W
Merten   Schneider	MEG5300-0001 (CCT99100)	[LED, RL, RC] 4 – 20VA RL LED / 4 – 100VA RC LED
MK - Electric	K1535	[R] 65 – 450 W - Turn
MK - Electric	K1501 WHILV	[R] 60 – 500 W - Turn
MK - Electric	K4501 WHILV	[RLC] 180W
MK - Electric	K4500 WHILV	[RLC] 400W
NIKO	310-0280X	[LED] 2 – 100 VA
Niko	310-02901	[LED, R, L, C] 3 – 200W - Tast
Niko	310-03901	[LED, R, L, C] 3 – 200W - Turn
PEHA	431HAN	[RL] 6–120W [LED] 6–60W
Philips	UID8670	[LED] 2 – 100 VA-LED - Push (3wire)
RELCO	RP0977	[LED] 4-100W
RELCO	RM0545	[LED] 4-100W
Schneider	SBD315RC (SBD 315, SDD 315, ATD315, CCT011533)	[RC] 315W
Schneider	SBD200 (WDE 002299)	[ ] 4–400VA - Turn Universal (2wire)
Schneider	SAE dimmer puck CCT99100	[LED, RL, RC] 4 – 20VA RL LED / 4 – 100VA RC LED
VADSBO	ED 350	[RC] 50 – 350W
VADSBO	DU 250	[RC] 20 – 250W
VADSBO	VD300	[LED] 0 – 300VA - Turn
Varilight	HQ3W	[R] 60–400W
Varilight	ICT401 M	[RC] 20–400W
Vimar	20148	[RL] 500W
Vimar	20162	[RL] 40–300W
Vimar	Universal dimmer 20135.1	[LED] 3 – 200W - Tast
Vimar	Universal dimmer 20136.1	[LED] 3 – 200W - Turn- Leading
Vimar	Universal dimmer 20136.1	[LED] 3 – 200W - Turn- Trailing
Philips Dynalite	DDLE801	(100W per channel)
Philips Dynalite	DDMC802 (913703243509)	(x W per channel)-leading
Philips Dynalite	DDMC802 (913703243509)	(x W per channel)-Trailing

LED Spot								
MAS LED spot VLE D 4.9-50W GU10 930 36D 9290013489			MAS LED spot VLE DT 6.2-80W GU10 927 36D 9290020659			MAS LED spot VLE D 6.2-80W GU10 927 36D 9290020595		
MAS LED spot VLE D 4.9-50W GU10 940 36D 9290013490			MASLEDspot VLE D 6.2-80W GU10 940 36D UK 9290020660			MAS LED spot VLE D 6.2-80W GU10 940 36D 9290020660		
MAS LED spot VLE D 4.9-50W GU10 927 60D 9290013491			MASLEDspot VLE D 6.2-80W GU10 930 36D UK 9290020684			MAS LED spot VLE D 6.2-80W GU10 965 36D 9290022099		
MAS LED spot VLE D 4.9-50W GU10 930 60D 9290013492			MASLEDspot VLE D 6.2-80W GU10 965 36D UK 9290022099			MAS LED spot VLE D 650lm GU10 930 120D 9290022100		
MAS LED spot VLE D 4.9-50W GU10 940 60D 9290013493			MAS LEDspot VLE D 650lm GU10 930 120D UK 9290022100			MAS LED spot VLE D 680lm GU10 940 120D 9290022101		
MAS LED spot VLEDT4.9-50W GU10 927 36DUK 9290013503			MAS LED spot VLE D 6.2-80W GU10 930 36D 9290020684			MAS LED spot VLE D 680lm GU10 965 120D 9290022102		
MAS LEDspotVLE D 4.9-50W GU10 940 36D UK 9290013490						MASLEDspot VLE D 6.2-80W GU10 927 36D UK 9290020595		
MAS LEDspotVLE D 4.9-50W GU10 930 36D UK 9290013489								
MAS LED spot VLE DT 4.9-50W GU10 927 36D 9290013503								
MAS LED spot VLE D 4.8-50W GU10 927 36D 9290029801								
MAS LED spot VLE D 4.8-50W GU10 927 36D 9290029801								
								
Dimming Performance	Dimming Range	Glowing	Dimming Performance	Dimming Range	Glowing	Dimming Performance	Dimming Range	Glowing
1-15	97% - 7%		1-10	90% - 0%		1-10	90% - 0%	
1-10	96% - 5%		1-10	87% - 0%		1-10	87% - 0%	
1-15	96% - 0%			N.A.	N.A.		N.A.	N.A.
1-20	98% - 0%	2	1-10	92% - 0%		1-10	92% - 0%	
1-20	98% - 7%		1-10	92% - 0%		1-10	92% - 0%	
1-20	96% - 1%		1-10	92% - 0%		1-10	92% - 0%	
1-20	97% - 9%							
1-20	95% - 0%		1-10	93% - 0%		1-10	93% - 0%	
1-20	93% - 0%		1-10	87% - 0%		1-10	87% - 0%	
1-20	96% - 0%		1-10	91% - 1%		1-10	91% - 1%	
1-20	95% - 0%		1-10	89% - 0%		1-10	89% - 0%	
1-15	92% - 5%		1-11	87% - 0%		1-11	87% - 0%	
1-10	95% - 0%		1-10	87% - 1%		1-10	87% - 1%	
1-20	95% - 9%		1-10	90% - 0%		1-10	90% - 0%	
1-20	95% - 9%		1-10	90% - 0%		1-10	90% - 0%	
1-15	98% - 0%		1-10	90% - 0%		1-10	90% - 0%	
1-8	97% - 0%		1-10	91% - 0%		1-10	91% - 0%	
1-20	96% - 0%		1-10	92% - 0%		1-10	92% - 0%	
1-15	92% - 5%		1-11	87% - 0%		1-11	87% - 0%	
1-10	95% - 0%		1-10	87% - 1%		1-10	87% - 1%	
1-3	95% - 9%			N.A.	N.A.		N.A.	N.A.
1-15	96% - 18%		1-10	95% - 10%		1-10	95% - 10%	
1-20	97% - 2%		1-10	91% - 0%		1-10	91% - 0%	
1-10	96% - 5%		1-10	87% - 0%		1-10	87% - 0%	
1-10	98% - 2%		1-10	87% - 1%		1-10	87% - 1%	
1-20	96% - 10%		1-10	91% - 0%		1-10	91% - 0%	
1-20	95% - 6%		1-10	91% - 0%		1-10	91% - 0%	
1-20	96% - 1%		1-10	93% - 0%		1-10	93% - 0%	
1-20	97% - 2%		1-10	91% - 0%		1-10	91% - 0%	
1-10	96% - 5%		1-10	87% - 0%		1-10	87% - 0%	
1-5	95% - 0%		1-10	85% - 3%		1-10	85% - 3%	
1-17	98% - 0%		1-15	90% - 0%		1-15	90% - 0%	
1-15	98% - 0%		1-10	86% - 0%		1-10	8% - 0%	
			1-11	87% - 0%		1-11	87% - 0%	
1-10	96% - 0%							
1-20	95% - 24%		1-10	82% - 11%		1-10	82% - 11%	
1-15	92% - 5%		1-11	87% - 0%		1-11	87% - 0%	
1-10	95% - 0%		1-10	87% - 1%		1-10	87% - 1%	
1-3	95% - 9%			N.A.	N.A.		N.A.	N.A.
1-15	96% - 13%		1-10	86% - 0%		1-10	86% - 0%	
1-20	94% - 6%		1-10	87% - 1%		1-10	87% - 1%	
1-9	98% - 6%							
1-15	94% - 7%		1-9	81% - 0%		1-9	81% - 0%	
1-20	95% - 0%		1-10	88% - 2%		1-10	88% - 2%	
1-20	98% - 7%		1-10	90% - 2%		1-10	90% - 2%	
1-20	98% - 7%		1-10	90% - 2%		1-10	90% - 2%	
1-10	94% - 10%			N.A.	N.A.		N.A.	N.A.
1-20	96% - 1%		1-10	92% - 0%		1-10	92% - 0%	
1-20	96% - 17%		1-20	95% - 0%		1-20	95% - 0%	
1-20	96% - 2%		1-10	85% - 0%		1-10	85% - 0%	
1-10	95% - 0%		1-10	87% - 1%		1-10	87% - 1%	
1-15	92% - 5%		1-11	87% - 0%		1-11	87% - 0%	
1-3	95% - 9%			N.A.	N.A.		N.A.	N.A.
1-15	97% - 13%		1-10	77% - 5%		1-10	77% - 5%	
1-10	96% - 0%		1-7	73% - 0%		1-7	73% - 0%	
1-10	95% - 18%		1-10	85% - 0%		1-10	85% - 0%	
2-15	96% - 12%		1-10	89% - 0%		1-10	89% - 0%	
1-17	98% - 5%		1-11	94% - 0%		1-11	94% - 0%	
1-20	96% - 4%		1-10	95% - 0%		1-10	95% - 0%	
1-20	98% - 18%		1-10	86% - 0%		1-10	86% - 0%	
1-20	96% - 16%		1-10	87% - 1%		1-10	87% - 1%	
1-20	95% - 16%		1-10	85% - 1%		1-10	85% - 1%	
1-10	95% - 0%		1-7	87% - 0%		1-7	87% - 0%	
2-19	99% - 0%		6-13	88% - 0%		6-13	88% - 0%	
1-19	98% - 0%		4-13	90% - 0%		4-13	90% - 0%	



# Professional LED Mains Voltage range

## Recommended dimmer compatibility list for Mains Voltage Lamps



### KEY

X - Y	Excellent dimming with X-Y lamps, however external factors can negatively influence the deep dimming performance
X - Y	See note below.
	Unexpected performance behavior, not in line with good dimming perception
N.A.	Dimmer lamp combination not applicable
T.B.D.	Dimmer lamp combination not tested

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab conditions and might contain faults

Brand	Type	Load
Berker   INSTA	286710	[RC] 20 – 360 W - Turn
Berker   INSTA	2973	[LED, R, L, C] 3 - 60W - Turn
Bticino   Legrand	BTN4411N (BTNT4411N, BTL4411N)	[LED] 3 - 75W - Tast
Busch Jaeger   ABB	2250 U	[R ] 60 – 600 W - Turn
Busch Jaeger   ABB	6513 U - 102	[RC] 40 – 420 W - Turn
Busch Jaeger   ABB	6523 U	[LED] 2 – 100 VA-LED - Turn
Busch Jaeger   ABB	6526 U	[LED] 2 – 100 VA-LED - Push (2wire)
Busch Jaeger   ABB	6523 U-102	[LED, R, L, C] 2 - 100W - Turn- Leading
Busch Jaeger   ABB	6523 U-102	[LED, R, L, C] 2 - 100W - Turn- Trailing
Busch Jaeger   ABB	6523 UR-103	[LED, R, L, C] 2 - 400W - Turn- Leading
Busch Jaeger   ABB	6523 UR-103	[LED, R, L, C] 2 - 400W - Turn- Trailing
ELKO   Schneider	SBD200LED (CCTEL10501)	[LED/RC] 4 - 200W(RC) 4-400W(RL)
ELKO   Schneider	SBD315RC (315 GLE )	[RC] 315W
SE LK   Schneider	LK FUGA LED-S 120VA (506Dx219)	[LED, RL] 4 - 120W - Slider
SE LK   Schneider	LK OPUS 66 LED-S 120VA (506Nx219)	[LED, RL] 4 - 120W - Slider
Eitako	EVD61NPN-UC	400W 3-wire Push Module
Eitako	EUD61NPL-230V	[LED, R, C] 4 - 200W - Module-Leading
Eitako	EUD61NPL-230V	[LED, R, C] 4 - 200W - Module-Trailing
Feller   Schneider	40200 (SBD200LED CCTCH10601)	[LED/RC] 4 - 200W(RC) 4-400W(RL)
Feller   Schneider	40300 (SBD315)	[RLC] 300W
Feller   Schneider	40200.LED.EB (CCT99100)	[LED, RL, RC] 4 - 20VA RL LED / 4 - 100VA RC LED
Gira	1176-00/01	[RLC] 50 – 420W
Gira	2390 00/ 100	[LED] 7 – 100W - Push (3wire)
Gira   INSTA	5401 00	[LED, R, L, C] 3 - 100W/200W- Tast
Gira   INSTA	2450 00	[LED, R, L, C] 3 - 60W - Turn
Hager	EVN 011	[RC] 300VA
Hager	EVN 012	[RC] 300W
Hager	EVN 004	[RL] 500VA
Jung	1271LEDDE	[LED] 3 – 100W - Push (3wire)
Jung   INSTA	1711DE	[LED, R, L, C] 3 - 100W/200W- Tast
Jung   INSTA	1730DD	[LED, R, L, C] 3 - 60W - Turn
Klik aan Klik uit	AWMD-250	[LED] 3- 24W
Klik aan Klik uit	ACM 300	300W - 3-wire Push LED Dimmer
Legrand	78401	[RLC] 40 – 500W
Legrand	67083	[RLC] 3 – 400W
Legrand	67084	[RLC] 8 - 300 VA - Push LED (3wire)
Legrand	67085 (078406)	[RLC] 8 - 300 VA - Push LED (3wire)
Legrand	L4402N	[R ] 60-500W
Merten   Schneider	SBD200LED (MEG5134-0000)	[LED/RC] 4 - 200W(RC) 4-400W(RL)
Merten   Schneider	SBD315RC (MEG5136-0000)	[RC] 315W
Merten   Schneider	MEG5300-0001 (CCT99100)	[LED, RL, RC] 4 - 20VA RL LED / 4 - 100VA RC LED
MK - Electric	K1535	[R] 65 – 450 W - Turn
MK - Electric	K1501 WHILV	[R] 60 – 500 W - Turn
MK - Electric	K4501 WHILV	[RLC] 180W
MK - Electric	K4500 WHILV	[RLC] 400W
NIKO	310-0280X	[LED] 2 – 100 VA
Niko	310-02901	[LED, R, L, C] 3 - 200W - Tast
Niko	310-03901	[LED, R, L, C] 3 - 200W - Turn
PEHA	431HAN	[RL] 6-120W [LED] 6-60W
Philips	UID8670	[LED] 2 – 100 VA-LED - Push (3wire)
RELCO	RP0977	[LED] 4-100W
RELCO	RM0545	[LED] 4-100W
Schneider	SBD315RC (SBD 315, SDD 315, ATD315, CCT011533)	[RC] 315W
Schneider	SBD200 (WDE 002299)	[ ] 4-400VA - Turn Universal (2wire)
Schneider	SAE dimmer puck CCT99100	[LED, RL, RC] 4 - 20VA RL LED / 4 - 100VA RC LED
VADSBO	ED 350	[LED] 50 – 350W
VADSBO	DU 250	[RC] 20 – 250W
VADSBO	VD300	[LED] 0 - 300VA - Turn
Varilight	HQ3W	[R] 60-400W
Varilight	ICT401 M	[RC] 20-400W
Vimar	20148	[RL] 500W
Vimar	20162	[RL] 40-300W
Vimar	Universal dimmer 20135.1	[LED] 3 - 200W - Tast
Vimar	Universal dimmer 20136.1	[LED] 3 - 200W - Turn- Leading
Vimar	Universal dimmer 20136.1	[LED] 3 - 200W - Turn- Trailing
Philips Dynalite	DDLE801	(100W per channel)
Philips Dynalite	DDMC802 (913703243509)	(x W per channel)-leading
Philips Dynalite	DDMC802 (913703243509)	(x W per channel)-Trailing

LED Spot								
CorePro LEDspot 3-35W GU10 840 36D DIM 9290020656 CorePro LEDspot 3-35W GU10 830 36D DIM 9290020682 CorePro LEDspot 3-35W GU10 827 36D DIM 9290024958 CoreProLEDspot 3-35W GU10 830 36D DIM UK 9290020682			CorePro LEDspot 4-50W GU10 830 36D DIM 9290020683 CorePro LEDspot 4-50W GU10 840 36D DIM 9290020658 CoreProLEDspot 4-50W GU10 840 36D DIM UK 9290020658 CoreProLEDspot 4-50W GU10 830 36D DIM UK 9290020683 CoreProLEDspot 4-50W GU10 827 36D DIM UK 9290024959 CorePro LEDspot 4-50W GU10 827 36D DIM 9290024959 CoreProLEDspot 4-50W GU10 865 36D DIM UK 9290035624			MAS LEDspot VLE D 4.7-50W GU10 82736D5CT 9290029954 MAS LEDspot VLE D 4.7-50W GU10 83036D5CT 9290029955		
Dimming Performance	Dimming Range	Glowing	Dimming Performance	Dimming Range	Glowing	Dimming Performance	Dimming Range	Glowing
1-20	96% - 18%		1-15	94% - 24%		1-15	94% - 0%	
1-20	96% - 3%		1-15	94% - 69%		1-10	94% - 69%	
1-20	97% - 0%		1-15	93% - 22%		1-15	90% - 19%	
2-20	96% - 0%		2-15	99% - 1%		1-20	92% - 0%	
1-20	96% - 0%		1-15	95% - 0%		1-20	98% - 6%	
1-20	95% - 0%		1-15	97% - 0%		1-20	96% - 0%	
1-20	95% - 0%		1-15	92% - 7%		1-20	96% - 0%	
1-20	95% - 0%		1-15	94% - 11%		1-20	95% - 0%	
1-20	95% - 0%		1-15	97% - 0%		1-20	93% - 6%	
1-20	96% - 0%		1-15	99% - 3%		1-20	94% - 0%	
1-20	95% - 30%		1-15	94% - 21%		1-17	89% - 22%	
1-20	96% - 22%		1-15	97% - 13%		1-10	93% - 0%	
1-20	96% - 0%		1-15	95% - 27%		1-20	94% - 25%	
1-20	96% - 0%		1-15	95% - 27%		1-20	94% - 25%	
1-20	96% - 0%		1-15	95% - 3%		1-15	92% - 2%	
1-20	96% - 0%		1-15	96% - 0%		1-20	90% - 3%	
1-20	96% - 0%		1-15	96% - 0%		1-20	92% - 3%	
1-20	95% - 30%		1-15	94% - 21%		1-17	89% - 22%	
1-20	96% - 22%		1-15	97% - 13%		1-10	93% - 0%	
1-20	96% - 0%		1-5	94% - 25%		1-3	94% - 23%	
1-20	95% - 0%		1-15	100% - 0%		1-15	99% - 34%	
1-20	93% - 21%		1-15	94% - 22%		1-20	94% - 0%	
1-20	96% - 3%		1-15	94% - 69%		1-10	94% - 69%	
1-20	95% - 0%		1-15	97% - 14%		1-10	98% - 0%	
1-20	96% - 0%		1-15	96% - 14%		1-20	98% - 0%	
1-20	96% - 0%		1-15	96% - 13%		1-20	97% - 0%	
1-20	96% - 0%		1-15	92% - 14%		1-20	96% - 13%	
1-20	93% - 21%		1-15	94% - 22%		1-20	94% - 0%	
1-20	96% - 3%		1-15	94% - 69%		1-10	94% - 69%	
1-20	96% - 2%		1-5	92% - 33%		1-5	82% - 0%	
1-20	89% - 0%		1-15	87% - 0%	1-3	1-17	93% - 0%	
1-20	95% - 0%		1-15	96% - 15%		1-15	95% - 12%	
1-20	92% - 0%		1-15	92% - 0%		1-17	87% - 0%	
3-20	95% - 0%		3-15	86% - 30%		1-20	93% - 4%	
1-20	95% - 30%		1-15	94% - 21%		1-17	89% - 22%	
1-20	96% - 0%		1-15	97% - 13%		1-10	93% - 0%	
1-20	96% - 0%		1-5	94% - 25%		1-3	94% - 23%	
1-20	95% - 0%		1-15	85% - 17%		1-15	96% - 0%	
1-20	92% - 0%		1-15	90% - 22%		1-20	95% - 4%	
1-15	79% - 12%		1-11	83% - 14%		1-8	91% - 15%	
1-20	85% - 14%		1-15	88% - 15%		1-14	84% - 14%	
1-20	96% - 3%		1-15	98% - 5%		1-20	98% - 1%	
1-20	95% - 0%		1-15	94% - 5%		1-20	92% - 5%	
1-20	96% - 0%		1-15	94% - 5%		1-20	92% - 5%	
1-20	96% - 0%		1-15	89% - 17%		1-10	98% - 0%	
1-20	95% - 0%		1-15	97% - 0%		1-20	96% - 0%	
1-20	99% - 9%		1-15	99% - 8%		1-20	97% - 7%	
	N.A.	N.A.		N.A.	N.A.	1-20	99% - 0%	
1-20	96% - 22%		1-15	97% - 13%		1-10	93% - 0%	
1-20	95% - 30%		1-15	94% - 21%		1-17	89% - 22%	
1-20	96% - 0%		1-5	94% - 25%		1-3	94% - 23%	
1-20	88% - 33%		1-15	84% - 28%		1-15	87% - 27%	
1-17	85% - 12%		1-13	80% - 9%	1-13	1-11	82% - 7%	
1-20	96% - 0%		1-15	95% - 0%		1-10	94% - 0%	
1-20	95% - 0%		1-15	98% - 15%		1-15	96% - 0%	
1-20	93% - 0%		1-15	93% - 0%		1-17	93% - 0%	
1-20	96% - 0%		1-15	99% - 15%		1-20	97% - 0%	
1-20	94% - 0%		1-15	98% - 29%		1-20	96% - 27%	
1-20	95% - 0%		1-15	98% - 6%		1-20	94% - 6%	
1-20	94% - 0%		1-15	98% - 4%		1-20	95% - 4%	
1-15	90% - 0%		1-12	93% - 0%		1-10	88% - 0%	
	N.A.	N.A.		N.A.	N.A.		N.A.	N.A.
1-20	96% - 0%		1-15	98% - 0%		9-20	92% - 0%	

# Professional LED Mains Voltage range

Recommended dimmer compatibility list for Mains Voltage Lamps



## KEY

X - Y	Excellent dimming with X-Y lamps, however external factors can negatively influence the deep dimming performance
X - Y	See note below.
	Unexpected performance behavior, not in line with good dimming perception
N.A.	Dimmer lamp combination not applicable
T.B.D.	Dimmer lamp combination not tested

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab conditions and might contain faults

Brand	Type	Load
Berker   INSTA	286710	[RC] 20 – 360 W - Turn
Berker   INSTA	2973	[LED, R, L, C] 3 - 60W - Turn
Bticino   Legrand	BTN4411N (BTNT4411N, BTL4411N)	[LED] 3 - 75W - Tast
Busch Jaeger   ABB	2250 U	[R ] 60 – 600 W - Turn
Busch Jaeger   ABB	6513 U - 102	[RC] 40 – 420 W - Turn
Busch Jaeger   ABB	6523 U	[LED] 2 – 100 VA-LED - Turn
Busch Jaeger   ABB	6526 U	[LED] 2 – 100 VA-LED - Push (2wire)
Busch Jaeger   ABB	6523 U-102	[LED, R, L, C] 2 - 100W - Turn- Leading
Busch Jaeger   ABB	6523 U-102	[LED, R, L, C] 2 - 100W - Turn- Trailing
Busch Jaeger   ABB	6523 UR-103	[LED, R, L, C] 2 - 400W - Turn- Leading
Busch Jaeger   ABB	6523 UR-103	[LED, R, L, C] 2 - 400W - Turn- Trailing
ELKO   Schneider	SBD200LED (CCTEL10501)	[LED/RC] 4 - 200W(RC) 4-400W(RL)
ELKO   Schneider	SBD315RC (315 GLE )	[RC] 315W
SE LK   Schneider	LK FUGA LED-S 120VA (506Dx219)	[LED, RL] 4 - 120W - Slider
SE LK   Schneider	LK OPUS 66 LED-S 120VA (506Nx219)	[LED, RL] 4 - 120W - Slider
Eitako	EVD61NPN-UC	400W 3-wire Push Module
Eitako	EUD61NPL-230V	[LED, R, C] 4 - 200W - Module-Leading
Eitako	EUD61NPL-230V	[LED, R, C] 4 - 200W - Module-Trailing
Feller   Schneider	40200 (SBD200LED CCTCH10601)	[LED/RC] 4 - 200W(RC) 4-400W(RL)
Feller   Schneider	40300 (SBD315)	[RLC] 300W
Feller   Schneider	40200.LED.EB (CCT99100)	[LED, RL, RC] 4 - 20VA RL LED / 4 - 100VA RC LED
Gira	1176-00/01	[RLC] 50 – 420W
Gira	2390 00/ 100	[LED] 7 – 100W - Push (3wire)
Gira   INSTA	5401 00	[LED, R, L, C] 3 - 100W/200W- Tast
Gira   INSTA	2450 00	[LED, R, L, C] 3 - 60W - Turn
Hager	EVN 011	[RC] 300VA
Hager	EVN 012	[RC] 300W
Hager	EVN 004	[RL] 500VA
Jung	1271LEDDE	[LED] 3 – 100W - Push (3wire)
Jung   INSTA	1711DE	[LED, R, L, C] 3 - 100W/200W- Tast
Jung   INSTA	1730DD	[LED, R, L, C] 3 - 60W - Turn
Klik aan Klik uit	AWMD-250	[LED] 3- 24W
Klik aan Klik uit	ACM 300	300W - 3-wire Push LED Dimmer
Legrand	78401	[RLC] 40 – 500W
Legrand	67083	[RLC] 3 – 400W
Legrand	67084	[RLC] 8 - 300 VA - Push LED (3wire)
Legrand	67085 (078406)	[RLC] 8 - 300 VA - Push LED (3wire)
Legrand	L4402N	[R ] 60-500W
Merten   Schneider	SBD200LED (MEG5134-0000)	[LED/RC] 4 - 200W(RC) 4-400W(RL)
Merten   Schneider	SBD315RC (MEG5136-0000)	[RC] 315W
Merten   Schneider	MEG5300-0001 (CCT99100)	[LED, RL, RC] 4 - 20VA RL LED / 4 - 100VA RC LED
MK - Electric	K1535	[R] 65 – 450 W - Turn
MK - Electric	K1501 WHILV	[R] 60 – 500 W - Turn
MK - Electric	K4501 WHILV	[RLC] 180W
MK - Electric	K4500 WHILV	[RLC] 400W
NIKO	310-0280X	[LED] 2 – 100 VA
Niko	310-02901	[LED, R, L, C] 3 - 200W - Tast
Niko	310-03901	[LED, R, L, C] 3 - 200W - Turn
PEHA	431HAN	[RL] 6-120W [LED] 6-60W
Philips	UID8670	[LED] 2 – 100 VA-LED - Push (3wire)
RELCO	RP0977	[LED] 4-100W
RELCO	RM0545	[LED] 4-100W
Schneider	SBD315RC (SBD 315, SDD 315, ATD315, CCT011533)	[RC] 315W
Schneider	SBD200 (WDE 002299)	[ ] 4-400VA - Turn Universal (2wire)
Schneider	SAE dimmer puck CCT99100	[LED, RL, RC] 4 - 20VA RL LED / 4 - 100VA RC LED
VADSBO	ED 350	[RC] 50 – 350W
VADSBO	DU 250	[RC] 20 – 250W
VADSBO	VD300	[LED] 0 - 300VA - Turn
Varilight	HQ3W	[R] 60-400W
Varilight	ICT401 M	[RC] 20-400W
Vimar	20148	[RL] 500W
Vimar	20162	[RL] 40-300W
Vimar	Universal dimmer 20135.1	[LED] 3 - 200W - Tast
Vimar	Universal dimmer 20136.1	[LED] 3 - 200W - Turn- Leading
Vimar	Universal dimmer 20136.1	[LED] 3 - 200W - Turn- Trailing
Philips Dynalite	DDLE801	(100W per channel)
Philips Dynalite	DDMC802 (913703243509)	(x W per channel)-leading
Philips Dynalite	DDMC802 (913703243509)	(x W per channel)-Trailing

LED Spot					
CoreProLEDspot D 4.3-60W R50 E14 827 36D 9290018912 CoreProLEDspot D 4.5-60W R63 E27 827 36D 9290018914			CoreProLEDspot D8.5-100W R80 E27 827 36D 9290029969		
Dimming Performance	Dimming Range	Glowing	Dimming Performance	Dimming Range	Glowing
1-15	97% - 0%		1-8	99% - 11%	
	N.A.	N.A.		N.A.	N.A.
1-15	97% - 0%		1-8	95% - 0%	
1-15	97% - 0%		1-10	95% - 0%	
1-15	98% - 0%		1-10	95% - 11%	
1-15	98% - 0%		1-11	98% - 0%	
			1-10	96% - 11%	
1-15	97% - 0%		1-10	93% - 0%	
1-15	97% - 0%		1-10	95% - 0%	
1-15	96% - 0%		1-10	95% - 0%	
1-15	97% - 0%		1-10	96% - 0%	
1-15	99% - 0%		1-8	95% - 16%	
1-15	96% - 0%		1-5	95% - 0%	
1-15	97% - 0%		1-10	95% - 14%	
1-15	97% - 0%		1-10	95% - 14%	
1-15	96% - 0%		1-8	96% - 11%	
1-15	96% - 0%		1-10	95% - 0%	
1-15	95% - 0%		1-10	95% - 0%	
1-15	99% - 0%		1-8	95% - 16%	
1-15	96% - 0%		1-5	95% - 0%	
1-5	96% - 0%		1-2	96% - 16%	
1-15	96% - 0%		1-8	94% - 26%	
1-15	98% - 0%		1-10	96% - 3%	
	N.A.	N.A.		N.A.	N.A.
1-15	97% - 0%		1-5	96% - 1%	
1-15	95% - 0%		1-10	96% - 12%	
1-15	95% - 0%		1-10	96% - 8%	
1-15	97% - 0%		1-10	95% - 0%	
1-15	98% - 0%		1-10	95% - 16%	
	N.A.	N.A.	1-5	95% - 0%	
1-5	95% - 0%		1-3	87% - 0%	
1-19	92% - 0%		1-9	97% - 0%	
1-15	97% - 0%		1-8	96% - 0%	
1-15	99% - 0%				
			1-5	97% - 0%	
	N.A.	N.A.	1-10	95% - 30%	
1-15	99% - 0%		1-8	95% - 16%	
1-15	96% - 0%		1-5	95% - 0%	
1-5	96% - 0%		1-2	96% - 16%	
1-15	89% - 0%		1-10	95% - 13%	
2-15	97% - 0%		1-10	95% - 4%	
1-10	96% - 0%		1-5	96% - 6%	
1-15	99% - 0%		1-8	94% - 5%	
1-15	96% - 0%		1-10	96% - 0%	
1-15	97% - 0%		1-10	96% - 14%	
1-15	97% - 0%		1-10	96% - 14%	
1-10	96% - 0%		1-5	95% - 10%	
1-15	98% - 0%		1-11	98% - 0%	
1-15	99% - 0%		1-10	96% - 30%	
1-15	97% - 0%		1-10	96% - 5%	
1-15	96% - 0%		1-5	95% - 0%	
1-15	99% - 0%		1-8	95% - 16%	
1-16	97% - 0%		1-8	97% - 22%	
1-12	96% - 0%		1-6	95% - 0%	
1-10	96% - 0%		1-5	96% - 27%	
2-15	96% - 0%		1-8	94% - 16%	
1-19	96% - 0%		1-9	94% - 4%	
1-15	96% - 0%		1-10	96% - 7%	
1-15	96% - 0%		1-10	95% - 30%	
1-15	96% - 0%		1-10	94% - 28%	
1-15	96% - 0%		1-10	94% - 27%	
1-11	98% - 0%		1-5	98% - 0%	
3-15	97% - 0%		2-10	100% - 0%	
1-15	99% - 0%		1-10	99% - 0%	

# Professional LED Mains Voltage range

Recommended dimmer compatibility list for Mains Voltage Lamps



## KEY

X - Y	Excellent dimming with X-Y lamps, however external factors can negatively influence the deep dimming performance
X - Y	See note below.
	Unexpected performance behavior, not in line with good dimming perception
N.A.	Dimmer lamp combination not applicable
T.B.D.	Dimmer lamp combination not tested

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab conditions and might contain faults

Brand	Type	Load
Berker   INSTA	286710	[RC] 20 – 360 W - Turn
Berker   INSTA	2973	[LED, R, L, C] 3 - 60W - Turn
Bticino   Legrand	BTN4411N (BTNT4411N, BTL4411N)	[LED] 3 - 75W - Tast
Busch Jaeger   ABB	2250 U	[R ] 60 – 600 W - Turn
Busch Jaeger   ABB	6513 U - 102	[RC] 40 – 420 W - Turn
Busch Jaeger   ABB	6523 U	[LED] 2 – 100 VA-LED - Turn
Busch Jaeger   ABB	6526 U	[LED] 2 – 100 VA-LED - Push (2wire)
Busch Jaeger   ABB	6523 U-102	[LED, R, L, C] 2 - 100W - Turn- Leading
Busch Jaeger   ABB	6523 U-102	[LED, R, L, C] 2 - 100W - Turn- Trailing
Busch Jaeger   ABB	6523 UR-103	[LED, R, L, C] 2 - 400W - Turn- Leading
Busch Jaeger   ABB	6523 UR-103	[LED, R, L, C] 2 - 400W - Turn- Trailing
ELKO   Schneider	SBD200LED (CCTEL10501)	[LED/RC] 4 – 200W(RC) 4-400W(RL)
ELKO   Schneider	SBD315RC (315 GLE )	[RC] 315W
SE LK   Schneider	LK FUGA LED-S 120VA (506Dx219)	[LED, RL] 4 - 120W - Slider
SE LK   Schneider	LK OPUS 66 LED-S 120VA (506Nx219)	[LED, RL] 4 - 120W - Slider
Eitako	EVD61NPN-UC	400W 3-wire Push Module
Eitako	EUD61NPL-230V	[LED, R, C] 4 - 200W - Module-Leading
Eitako	EUD61NPL-230V	[LED, R, C] 4 - 200W - Module-Trailing
Feller   Schneider	40200 (SBD200LED CCTCH10601)	[LED/RC] 4 – 200W(RC) 4-400W(RL)
Feller   Schneider	40300 (SBD315)	[RLC] 300W
Feller   Schneider	40200.LED.EB (CCT99100)	[LED, RL, RC] 4 - 20VA RL LED / 4 - 100VA RC LED
Gira	1176-00/01	[RLC] 50 – 420W
Gira	2390 00/ 100	[LED] 7 – 100W - Push (3wire)
Gira   INSTA	5401 00	[LED, R, L, C] 3 - 100W/200W- Tast
Gira   INSTA	2450 00	[LED, R, L, C] 3 - 60W - Turn
Hager	EVN 011	[RC] 300VA
Hager	EVN 012	[RC] 300W
Hager	EVN 004	[RL] 500VA
Jung	1271LEDDE	[LED] 3 – 100W - Push (3wire)
Jung   INSTA	1711DE	[LED, R, L, C] 3 - 100W/200W- Tast
Jung   INSTA	1730DD	[LED, R, L, C] 3 - 60W - Turn
Klik aan Klik uit	AWMD-250	[LED] 3- 24W
Klik aan Klik uit	ACM 300	300W - 3-wire Push LED Dimmer
Legrand	78401	[RLC] 40 – 500W
Legrand	67083	[RLC] 3 – 400W
Legrand	67084	[RLC] 8 - 300 VA - Push LED (3wire)
Legrand	67085 (078406)	[RLC] 8 - 300 VA - Push LED (3wire)
Legrand	L4402N	[R ] 60-500W
Merten   Schneider	SBD200LED (MEG5134-0000)	[LED/RC] 4 – 200W(RC) 4-400W(RL)
Merten   Schneider	SBD315RC (MEG5136-0000)	[RC] 315W
Merten   Schneider	MEG5300-0001 (CCT99100)	[LED, RL, RC] 4 - 20VA RL LED / 4 - 100VA RC LED
MK - Electric	K1535	[R] 65 – 450 W - Turn
MK - Electric	K1501 WHILV	[R] 60 – 500 W - Turn
MK - Electric	K4501 WHILV	[RLC] 180W
MK - Electric	K4500 WHILV	[RLC] 400W
NIKO	310-0280X	[LED] 2 – 100 VA
Niko	310-02901	[LED, R, L, C] 3 - 200W - Tast
Niko	310-03901	[LED, R, L, C] 3 - 200W - Turn
PEHA	431HAN	[RL] 6-120W [LED] 6-60W
Philips	UID8670	[LED] 2 – 100 VA-LED - Push (3wire)
RELCO	RP0977	[LED] 4-100W
RELCO	RM0545	[LED] 4-100W
Schneider	SBD315RC (SBD 315, SDD 315, ATD315, CCT011533)	[RC] 315W
Schneider	SBD200 (WDE 002299)	[ ] 4-400VA - Turn Universal (2wire)
Schneider	SAE dimmer puck CCT99100	[LED, RL, RC] 4 - 20VA RL LED / 4 - 100VA RC LED
VADSBO	ED 350	[RC] 50 – 350W
VADSBO	DU 250	[RC] 20 – 250W
VADSBO	VD300	[LED] 0 - 300VA - Turn
Varilight	HQ3W	[R] 60-400W
Varilight	ICT401 M	[RC] 20-400W
Vimar	20148	[RL] 500W
Vimar	20162	[RL] 40-300W
Vimar	Universal dimmer 20135.1	[LED] 3 - 200W - Tast
Vimar	Universal dimmer 20136.1	[LED] 3 - 200W - Turn- Leading
Vimar	Universal dimmer 20136.1	[LED] 3 - 200W - Turn- Trailing
Philips Dynalite	DDLE801	(100W per channel)
Philips Dynalite	DDMC802 (913703243509)	(x W per channel)-leading
Philips Dynalite	DDMC802 (913703243509)	(x W per channel)-Trailing

LED Capsule					
CorePro LEDcapsuleMV 2.6-25W G9 827 D 9290023899 CorePro LEDcapsuleMV 2.6-25W G9 827 D UK 9290023899			CorePro LEDcapsuleMV 4-40W G9 827 D 9290023900		
Dimming Performance	Dimming Range	Glowing	Dimming Performance	Dimming Range	Glowing
1-20	95% - 0%		1-15	93% - 0%	
1-20	95% - 0%		1-15	93% - 68%	
1-20	94% - 0%		1-15	92% - 0%	
2-20	94% - 0%		1-15	93% - 0%	
1-20	96% - 0%		1-15	94% - 0%	
1-20	93% - 0%		1-15	92% - 0%	
1-20	79% - 0%		1-15	81% - 0%	
1-20	90% - 0%		1-15	90% - 0%	
1-20	93% - 0%		1-15	92% - 0%	
1-20	93% - 0%		1-15	92% - 0%	
1-16	99% - 0%		1-20	99% - 0%	
1-20	89% - 0%		1-15	89% - 0%	
1-20	87% - 0%		1-15	87% - 0%	
1-20	87% - 0%		1-15	87% - 0%	
1-20	86% - 0%		1-15	87% - 0%	
1-20	84% - 0%		1-15	85% - 0%	
1-20	91% - 0%		1-15	90% - 0%	
1-16	99% - 0%		1-20	99% - 0%	
1-20	89% - 0%		1-15	89% - 0%	
1-8	83% - 0%		1-5	84% - 0%	
1-20	89% - 0%		1-15	89% - 0%	
1-20	79% - 0%		1-15	91% - 0%	
1-20	95% - 0%		1-15	93% - 68%	
1-9	79% - 0%		1-5	91% - 31%	
1-20	96% - 0%		1-20	99% - 0%	
1-20	85% - 0%		1-15	97% - 0%	
1-20	100% - 0%		1-20	99% - 0%	
1-20	90% - 0%		1-15	85% - 0%	
1-16	99% - 0%		1-20	99% - 0%	
1-20	89% - 0%		1-15	89% - 0%	
1-8	83% - 0%		1-5	87% - 0%	
1-20	96% - 0%		1-15	85% - 0%	
1-20	85% - 0%		1-15	90% - 0%	
1-14	96% - 0%		1-11	95% - 0%	
2-20	92% - 0%		2-16	99% - 0%	
1-20	82% - 0%		1-15	90% - 0%	
1-20	94% - 10%		1-15	88% - 8%	
1-20	94% - 10%		1-15	88% - 8%	
1-20	88% - 0%		1-15	89% - 0%	
1-20	93% - 0%		1-15	92% - 0%	
1-20	100% - 0%		1-20	99% - 0%	
1-20	85% - 0%			N.A.	N.A.
1-20	89% - 0%		1-15	89% - 0%	
1-16	99% - 0%		1-20	99% - 0%	
1-8	83% - 0%		1-5	86% - 0%	
1-20	94% - 0%		1-18	98% - 0%	
1-19	93% - 0%		1-13	98% - 0%	
1-20	94% - 0%		1-15	88% - 0%	
1-20	94% - 0%		1-15	88% - 0%	
1-20	93% - 0%		1-20	97% - 0%	
1-20	81% - 0%		1-15	90% - 0%	
1-20	83% - 0%		1-15	89% - 0%	
1-20	96% - 0%		1-15	93% - 0%	
1-20	85% - 0%		1-15	93% - 0%	
	N.A.	N.A.	1-12	95% - 0%	
1,4-11	98% - 0%		3-20	90% - 0%	4-5
10-11	99% - 0%		3-20	99% - 0%	



# Professional LED Mains Voltage range

Recommended dimmer compatibility list for Mains Voltage Lamps



## KEY

X - Y	Excellent dimming with X-Y lamps, however external factors can negatively influence the deep dimming performance
X - Y	See note below.
	Unexpected performance behavior, not in line with good dimming perception
N.A.	Dimmer lamp combination not applicable
T.B.D.	Dimmer lamp combination not tested

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab conditions and might contain faults

Brand	Type	Load
Berker   INSTA	286710	[RC] 20 – 360 W - Turn
Berker   INSTA	2973	[LED, R, L, C] 3 - 60W - Turn
Bticino   Legrand	BTN4411N (BTNT4411N, BTL4411N)	[LED] 3 - 75W - Tast
Busch Jaeger   ABB	2250 U	[R ] 60 – 600 W - Turn
Busch Jaeger   ABB	6513 U - 102	[RC] 40 – 420 W - Turn
Busch Jaeger   ABB	6523 U	[LED] 2 – 100 VA-LED - Turn
Busch Jaeger   ABB	6526 U	[LED] 2 – 100 VA-LED - Push (2wire)
Busch Jaeger   ABB	6523 U-102	[LED, R, L, C] 2 - 100W - Turn- Leading
Busch Jaeger   ABB	6523 U-102	[LED, R, L, C] 2 - 100W - Turn- Trailing
Busch Jaeger   ABB	6523 UR-103	[LED, R, L, C] 2 - 400W - Turn- Leading
Busch Jaeger   ABB	6523 UR-103	[LED, R, L, C] 2 - 400W - Turn- Trailing
ELKO   Schneider	SBD200LED (CCTEL10501)	[LED/RC] 4 – 200W(RC) 4-400W(RL)
ELKO   Schneider	SBD315RC (315 GLE )	[RC] 315W
SE LK   Schneider	LK FUGA LED-S 120VA (506Dx219)	[LED, RL] 4 - 120W - Slider
SE LK   Schneider	LK OPUS 66 LED-S 120VA (506Nx219)	[LED, RL] 4 - 120W - Slider
Eitako	EVD61NPN-UC	400W 3-wire Push Module
Eitako	EUD61NPL-230V	[LED, R, C] 4 - 200W - Module-Leading
Eitako	EUD61NPL-230V	[LED, R, C] 4 - 200W - Module-Trailing
Feller   Schneider	40200 (SBD200LED CCTCH10601)	[LED/RC] 4 – 200W(RC) 4-400W(RL)
Feller   Schneider	40300 (SBD315)	[RLC] 300W
Feller   Schneider	40200.LED.EB (CCT99100)	[LED, RL, RC] 4 - 20VA RL LED / 4 - 100VA RC LED
Gira	1176-00/01	[RLC] 50 – 420W
Gira	2390 00/ 100	[LED] 7 – 100W - Push (3wire)
Gira   INSTA	5401 00	[LED, R, L, C] 3 - 100W/200W- Tast
Gira   INSTA	2450 00	[LED, R, L, C] 3 - 60W - Turn
Hager	EVN 011	[RC] 300VA
Hager	EVN 012	[RC] 300W
Hager	EVN 004	[RL] 500VA
Jung	1271LEDDE	[LED] 3 – 100W - Push (3wire)
Jung   INSTA	1711DE	[LED, R, L, C] 3 - 100W/200W- Tast
Jung   INSTA	1730DD	[LED, R, L, C] 3 - 60W - Turn
Klik aan Klik uit	AWMD-250	[LED] 3- 24W
Klik aan Klik uit	ACM 300	300W - 3-wire Push LED Dimmer
Legrand	78401	[RLC] 40 – 500W
Legrand	67083	[RLC] 3 – 400W
Legrand	67084	[RLC] 8 - 300 VA - Push LED (3wire)
Legrand	67085 (078406)	[RLC] 8 - 300 VA - Push LED (3wire)
Legrand	L4402N	[R ] 60-500W
Merten   Schneider	SBD200LED (MEG5134-0000)	[LED/RC] 4 – 200W(RC) 4-400W(RL)
Merten   Schneider	SBD315RC (MEG5136-0000)	[RC] 315W
Merten   Schneider	MEG5300-0001 (CCT99100)	[LED, RL, RC] 4 - 20VA RL LED / 4 - 100VA RC LED
MK - Electric	K1535	[R] 65 – 450 W - Turn
MK - Electric	K1501 WHILV	[R] 60 – 500 W - Turn
MK - Electric	K4501 WHILV	[RLC] 180W
MK - Electric	K4500 WHILV	[RLC] 400W
NIKO	310-0280X	[LED] 2 – 100 VA
Niko	310-02901	[LED, R, L, C] 3 - 200W - Tast
Niko	310-03901	[LED, R, L, C] 3 - 200W - Turn
PEHA	431HAN	[RL] 6-120W [LED] 6-60W
Philips	UID8670	[LED] 2 – 100 VA-LED - Push (3wire)
RELCO	RP0977	[LED] 4-100W
RELCO	RM0545	[LED] 4-100W
Schneider	SBD315RC (SBD 315, SDD 315, ATD315, CCT011533)	[RC] 315W
Schneider	SBD200 (WDE 002299)	[ ] 4-400VA - Turn Universal (2wire)
Schneider	SAE dimmer puck CCT99100	[LED, RL, RC] 4 - 20VA RL LED / 4 - 100VA RC LED
VADSBO	ED 350	[RC] 50 – 350W
VADSBO	DU 250	[RC] 20 – 250W
VADSBO	VD300	[LED] 0 - 300VA - Turn
Varilight	HQ3W	[R] 60-400W
Varilight	ICT401 M	[RC] 20-400W
Vimar	20148	[RL] 500W
Vimar	20162	[RL] 40-300W
Vimar	Universal dimmer 20135.1	[LED] 3 - 200W - Tast
Vimar	Universal dimmer 20136.1	[LED] 3 - 200W - Turn- Leading
Vimar	Universal dimmer 20136.1	[LED] 3 - 200W - Turn- Trailing
Philips Dynalite	DDLE801	(100W per channel)
Philips Dynalite	DDMC802 (913703243509)	(x W per channel)-leading
Philips Dynalite	DDMC802 (913703243509)	(x W per channel)-Trailing

LED Spot					
CorePro R75 118mm 14-100W 830 D 9290012437 CorePro R75 118mm 14-100W 840 D 9290012438 CorePro LED linear D 14-120W R75 118 830 9290013536 CorePro LED linear D 14-120W R75 118 840 9290013537			CoreProLED linearD 17.5-150W R75 118 830 9290020166 CoreProLED linearD 17.5-150W R75 118 840 9290020167		
Dimming Performance	Dimming Range	Glowing	Dimming Performance	Dimming Range	Glowing
1-5	95% - 2%		1	99% - 15%	
1-3	94% - 0%		1-3	98% - 10%	
1-5	93% - 0%			N.A.	N.A.
1-8	94% - 0%		1-7	97% - 0%	
1-8	98% - 6%		1-7	96% - 17%	
1-5	93% - 7%		1-2	96% - 25%	
			1-6	98% - 0%	
1-5	94% - 0%		1-6	97% - 10%	
1-5	93% - 0%		1-6	97% - 3%	
1-8	92% - 0%		1-20	95% - 1%	
1-8	93% - 0%		1-20	95% - 1%	
1-6	98% - 3%		1-5	99% - 16%	
1-5	97% - 0%		1-4	95% - 3%	
1-8	93% - 0%		1-7	98% - 16%	
1-8	93% - 0%		1-7	98% - 16%	
1-5	93% - 0%		1-5	96% - 1%	
1-8	95% - 0%		1-11	98% - 0%	
1-8	93% - 0%		1-11	98% - 5%	
1-6	98% - 3%		1-5	99% - 16%	
1-5	97% - 0%		1-4	95% - 3%	
1-1	94% - 0%		1	98% - 15%	
1-6	93% - 0%		1-5	97% - 24%	
1-5	93% - 0%		1-6	96% - 7%	
1-3	94% - 0%		1-3	98% - 10%	
1-3	97% - 0%		1-3	95% - 3%	
1-5	93% - 0%		1-6	96% - 1%	
1-5	93% - 0%		1-6	98% - 5%	
1-5	93% - 0%		1-6	98% - 10%	
1-5	93% - 0%		1-6	96% - 7%	
1-3	94% - 0%		1-3	98% - 10%	
1-2	93% - 0%		1	97% - 29%	
1-5	100% - 0%		1-3	97% - 0%	
1-5	93% - 0%		1-5	97% - 4%	
1-4	99% - 0%		1-3	99% - 0%	
1-5	93% - 0%		1-6	98% - 44%	
1-5	98% - 3%		1-5	99% - 16%	
1-5	97% - 0%		1-4	95% - 3%	
1	94% - 0%		1	98% - 15%	
1-5	94% - 4%		2-5	98% - 18%	
1-5	95% - 11%		1-6	98% - 17%	
1-3	100% - 1%		1-2	98% - 12%	
1-5	99% - 8%		1-4	99% - 18%	
1-5	97% - 0%		1-6	98% - 1%	
1-8	93% - 0%		1-11	98% - 0%	
1-8	93% - 0%		1-11	98% - 0%	
1-3	93% - 0%		1-3	98% - 12%	
1-5	93% - 0%		1-2	96% - 25%	
	N.A.	N.A.		N.A.	N.A.
				N.A.	N.A.
1-5	97% - 0%		1-4	95% - 3%	
1-6	98% - 3%		1-5	99% - 16%	
1	94% - 0%		1	98% - 15%	
2-5	100% - 14%		1-3	98% - 27%	
1-4	99% - 2%		1-3	97% - 5%	
1-4	93% - 0%		1-3	98% - 0%	
1-5	94% - 20%		1-5	98% - 18%	
1-6	100% - 0%		1-3	99% - 19%	
1-5	93% - 0%		1-6	98% - 20%	
1-8	93% - 0%		1-11	98% - 29%	
1-8	93% - 0%		1-11	99% - 1%	
1-5	95% - 0%		1-11	98% - 0%	
1-3	100% - 0%		1-3	98% - 0%	
2	99% - 0%		4-5	99% - 0%	
1-7	99% - 0%		2-5	99% - 0%	

## Notes:

---

- #1) Dimmers are tested with the number of LED light sources mentioned in the column "Dimming performance". A number of LED light sources outside the listed range may result in less optimal behavior. Although not specifically tested, some dimmers can be loaded with more light sources than specified in this document.
- #1a) Most (non-LED dedicated) dimmers can be loaded with LED light sources up to 20% of dimmer specified maximum power. Example: Dimmer 400W -> 20% = 80W, which means that e.g. up to 16 pcs 5W LED light sources can be connected.
- #1b) LED dimmers can be loaded up to the specified maximum dimmer power (Wattage).
- #2) Always study the packaging of LED light sources if these can be used in combination with occupancy/motion sensors.
- #3) "Glowing" means: when connected to a dimmer in its off-state, a LED light source may still emit a small, yet visible amount of light. This may e.g. occur if a low quantity of LED light sources is connected.
- #4) "Dimming Range" color indications and criteria (all percentages relate to the LED light source full power):
  - Green cell: minimum dimming level is below 10% and maximum level at least 80%.
  - Yellow cell: minimum dimming level is between 10% and 20% (inclusive) AND maximum level is above or equal to 80%.
  - Red cell: not compatible.
  - Grey cell: the dimmer - LED light source combination is not applicable.
  - White cell: no data available.
- #5) Various dimmer suppliers offer "active loads" to optimize dimming performance in case of light source-dimmer system issues. (e.g. Busch Jaeger Compensator 6596).
- #6) This list is based on measurements performed in a lab environment at nominal mains voltage, different mains voltages may result in a different dimming range.
- #7) Dimmer manufacturers may change the technical design of their dimmer without informing Philips / Signify. Such changes may affect the performance when used in combination with LED light sources.
- #8) In general Philips dimmable LED light sources can be dimmed with any type of dimmer (type R, RL, RC or RLC).
- #9) Mixed loads may give unexpected dimming behavior or even result in defects, for which Philips / Signify cannot be held responsible.
- #10) LED light source are dimmable across the indicated dimming range, but may exhibit minor flickering at distinct dim settings:
  - "Dimming Performance" color indications and criteria:
  - Green cell: No / or single point flicker, flicker range < 5% and below 80%.
  - Yellow cell: Flicker range < 5%, single point flicker > 80%, 5%-20% flicker range below 80%
  - Red cell: Flicker failed.
  - White cell: No data available.
- #11) The information contained here is believed to be accurate at the time it was published, but is provided "AS IS".



© 2022 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Specifically mentioned products, materials and/or tools from third parties are only indicative and reference to these products, materials and/or tools does not necessarily mean they are endorsed by Signify.

2022  
Data subject to change.