

# PHILIPS

Horticulture LED

GreenPower  
LED toplighting



## Full flexibility for optimal uniformity

Whether you want to increase yields, move to predictable year-round production, improve quality or shorten growth cycles, you can achieve it with the Philips GreenPower LED toplighting linear.

GreenPower LED toplighting linear is the product you'll need when light uniformity is key. It offers full flexibility in mounting the lights by using a separate c-profile. The result is optimal vertical light distribution and horizontal uniformity in cases where crop heights are limited or lower light levels are required. The linear range's efficacy boosts up to 3.5  $\mu\text{mol/J}$  and has an option to dim the lights to let you set and adjust the light levels when you need to.

Successful projects were installed in:

- High wire vegetables: tomatoes, cucumbers and peppers
- Leafy greens and herbs: lettuce and basil
- Soft fruits: strawberries
- Floriculture: cut flowers, potted plants, bedding plants, annuals and perennials
- Propagation for floriculture and vegetables
- Medicinal cannabis

### Key benefits

- Can be installed in any greenhouse situation, including in cases of lower light levels or limited height
- Maximal horizontal light uniformity and vertical light distribution to ensure uniform growth
- Efficacy up to 3.5  $\mu\text{mol/J}$
- Dimmability lets you set the proper light level at any given time and increase efficacy
- Uses 50% less energy than HPS lights

# Power up when flexibility is key

## Uniform crops and convenient installation

The advanced LED technology in our GreenPower LED toplighting linear delivers maximal horizontal light uniformity and vertical light distribution. This ensures uniform growth for every plant in your greenhouse to help you realize a higher return on each crop. The grow light can be easily mounted on a trellis or C-profile which allows you to position the lighting exactly where you need it. Simply click the modules into each other with or without spaces between them, to get the right set-up for your crops.

## GrowWise Control System enables dimming

277-400V GreenPower LED toplighting linear can be dimmed to 10% of its maximal photosynthetic photonflux in combination with the GrowWise Control System to improve the efficacy. This allows growers to dim the lighting for reasons of additional energy saving during peak hours or to mimic the dusk to dawn interval and enhance results for specific crop.

Dimming will work reliable without the need of specific control cables. The GrowWise Control System can be used standalone or can be connected and controlled via your climate computer.

## Efficient output

Our GreenPower LED toplighting linear offers light output levels that typically range between 500 to 800  $\mu\text{mol/s}$  per module at a very high efficacy of up to 3.5  $\mu\text{mol/J}$ . That makes it a highly efficient replacement and energy-efficient supplement for traditional lighting systems.

## Specifications 200-400V

Spectral version		Deep Red/Blue types			Deep Red/White types			
Spectral code		LB	MB	HB	LB	MB	W (VSN2)	MB + Far red
Typical photon flux	$\mu\text{mol/s}$	550	550	520	520	520	500	500
Power consumption (max)	W	155	160	160	155	160	200	175
Efficacy	$\mu\text{mol/J}$	3.5	3.4	3.3	3.4	3.3	2.5	2.9

## Specifications 277-400V

Spectral version		Deep Red/Blue types		Deep Red/White types	
Spectral code		LB*	MB*	LB*	W (VSN2)*
Typical photon flux	$\mu\text{mol/s}$	800	800	800	630
Power consumption (max)	W	230	250	250	250
Efficacy	$\mu\text{mol/J}$	3.5	3.2	3.2	2.5

\* Note: dimmable product between 10% and 100% Photosynthetic Photon Flux when combined with a GrowWise Control system.

Dimensions (LxWxH)	cm/inch	126.4 x 5.5 x 8 / 49.8 x 2.2 x 3.2
Weight	kg/lbs	3.2 / 7.1
Power factor	VAC	> 0.95 @ 400 VAC
Lifetime <sup>#</sup>	hrs	L90: 36.000; L70: 50.000
Ingress protection rating		IP66, UL/CSA rating: Suitable for dry, damp and wet locations
Cooling		Passively air-cooled
Approval marks		CE, UL/CSA, RoHS, ISO, RCM
Accessories		Full range of accessories available for easy and quick installation

### Legend

W = White (VSN2 broad spectrum)  
LB = Low Blue  
MB = Medium blue  
HB = High blue

<sup>#</sup> Lifetime and maintenance values are given at an ambient temperature of 25 °C / 77 °F. All measured lifetimes are industry standard measurements indicating average length of operation and not a performance claim specific to any individual product.

Philips GreenPower horticulture LED products meet photobiological safety standard EN 62471. Signify advises not to look into a direct light source as indicated in the application guide (doc# 4422 944 05672). Please protect eyes for the 300-700 nm range by wearing approved protection glasses.



© 2021 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify.


Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V. All other trademarks are owned by Signify Holding or their respective owners.

Document order number: 4422 944 04727 E  
07/2021 | Data subject to change

For more information about Philips Horticulture LED Solutions visit: [www.philips.com/horti](http://www.philips.com/horti)

Write us an e-mail: [horti.info@signify.com](mailto:horti.info@signify.com)

Or tweet us: @PhilipsHorti



## Reliable, low-maintenance design

The GreenPower LED toplighting linear uses passive cooling without moving parts, so it performs robustly and reliably and is easy to install. The module is designed to dissipate heat efficiently, which greatly extends its lifetime.