



3 hours compliant bulkhead emergency light

Emergency Light LED Bulkhead

Safety is important for building owners, and therefore having proper emergency lighting in place is a major concern for them. The Emergency bulkhead EM121C offers an easy solution for stand-alone emergency lighting, with maintained/non-maintained mode which leave the choices by customers. The lithium battery (LiFePO4) has many advantages over nickel-based products, as it has a longer lifetime, better discharge behaviors, is produced in a more welfare friendly way and can be recycled.

Benefits

- Welfare friendly solution versus nickel-based products as the battery can be recycled
- $\boldsymbol{\cdot}$ Lithium based battery type provides longer lifetime
- · low self-discharge and high temperature tolerance

Features

- · 3 hours battery duration when full charged
- · Self-test function
- · LFP is designed environmental friendly
- · Maintained or non-maintained mode selection

Application

- Airports
- Offices
- · Retail

Specifications

Emergency Light LED Bulkhead

Mounting type	Recessed/Surface/Ceiling
Operating Temperature	0 to +45°C
range	
Light Source	LED
Mains Voltage	220-240V/50-60Hz
Emergency lighting	Emergency lighting Pro 3hrs
Material	Housing: ABS/Cover: PC
Main color of the	RAL 9003
luminaire	

Ingress protection	IP40
Light source	No
replaceable	
Overall height	63mm
Overall length	355mm
Overall width	111m
Installation	surface/ceiling/recessed

Versions



Emergency Light Bulkhead

Product details





Emergency Light Bulkhead

Emergency Light LED Bulkhead



© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.