

Philips BN016 offers exceptional value. It is Perfect for your everyday lighting installations. It provides quality light and substantial energy and maintenance savings.

Essential Smartbright T8 Batten

BN016 Batten provide flexibility to customer to choose from 3 CCT and 2 different size and lumen packages, based on their specific need.

Benefits

- · Slim and integrated design
- · Polycarbonate housing with one pc extrusion process
- · Standalone Batten: both Surface and suspended mounting

Essential Smartbright T8 Batten

Features

- 15,000 hrs life, L70/B50
- 1 Year warranty
- \cdot 2 lengths, 3 colors Increased number of options for easy application
- CRI 70, SDCM < 7, 100 lm/W
- · Mounting accessories included

Application

- Hospitality
- · Offices
- · Residential

| Light Technical | | |
|-------------------------------------|-----------------|--|
| Color rendering index (CRI) | >70 | |
| Luminous Efficacy (rated) (Nom) | 100 lm/W | |
| | | |
| Operating and Electrical | | |
| Protection class IEC | Safety class II | |
| Input Voltage | 220 to 240 V | |
| Line Frequency | 50 or 60 Hz | |
| | | |
| Controls and Dimming | | |
| Dimmable | No | |
| | | |
| Mechanical and Housing | | |
| Optical cover type | Polycarbonate | |
| Housing Color | White | |
| Mech. impact protection code | IKO2 | |
| Ingress protection code | IP20 | |
| | | |
| Approval and Application | | |
| Ambient temperature range | -20 to +40 °C | |
| CE mark | No | |
| | | |
| Initial Performance (IEC Compliant) | | |
| Luminous flux tolerance | +/-10% | |
| | | |

Light Technical

| Order Code | Full Product Name | Correlated Color Temperature (Nom) | Luminous Flux | |
|--------------|-----------------------------|------------------------------------|---------------|--|
| 911401892781 | BN016C LED16/NW L1200 G2 | 4000 K | 1,600 lm | |
| 911401892881 | BN016C LED16/CW L1200 G2 | 6500 K | 1,600 lm | |
| 911401893281 | BN016C LED16/WW L1200 GM G2 | 3000 K | 1,600 lm | |
| 911401893381 | BN016C LED16/NW L1200 GM G2 | 4000 K | 1,600 lm | |
| 911401893481 | BN016C LED16/CW L1200 GM G2 | 6500 K | 1,600 lm | |
| 911401892481 | BN016C LED8/NW L600 G2 | 4000 K | 800 lm | |
| 911401892581 | BN016C LED8/CW L600 G2 | 6500 K | 800 lm | |
| 911401892981 | BN016C LED8/WW L600 GM G2 | 3000 K | 800 lm | |
| 911401893081 | BN016C LED8/NW L600 GM G2 | 4000 K | 800 lm | |
| 911401893181 | BN016C LED8/CW L600 GM G2 | 6500 K | 800 lm | |
| | | | | |

Operating and Electrical

| Order Code | Full Product Name | Power Consumption |
|--------------|-----------------------------|-------------------|
| Order Code | Tull Floduct Name | rower consumption |
| 911401892781 | BN016C LED16/NW L1200 G2 | 16 W |
| 911401892881 | BN016C LED16/CW L1200 G2 | 16 W |
| 911401893281 | BN016C LED16/WW L1200 GM G2 | 16 W |
| 911401893381 | BN016C LED16/NW L1200 GM G2 | 16 W |
| 911401893481 | BN016C LED16/CW L1200 GM G2 | 16 W |

| Order Code | Full Product Name | Power Consumption |
|--------------|---------------------------|-------------------|
| 911401892481 | BN016C LED8/NW L600 G2 | 8 W |
| 911401892581 | BN016C LED8/CW L600 G2 | 8 W |
| 911401892981 | BN016C LED8/WW L600 GM G2 | 8 W |
| 911401893081 | BN016C LED8/NW L600 GM G2 | 8 W |
| 911401893181 | BN016C LED8/CW L600 GM G2 | 8 W |

Essential Smartbright T8 Batten



© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.