



Reliable, high performance technology for extreme LED applications

Xitanium LED drivers - programmable

Our Xitanium programmable Xtreme LED drivers with global input voltage (UL, ENEC) are designed to deliver high performance, protection and configurability. The Xtreme technology ensures maximum robustness and protection with a very long lifetime. Configuration of programmable drivers can be done via DALI and the MultiOne software.

Benefits

- Ultimate robustness, energy savings through high efficiency and via multiple dimming and lower maintenance costs
- $\cdot \ \mathsf{Fully} \ \mathsf{programmable} \ \mathsf{LED}\text{-}\mathsf{drivers} \ \mathsf{designed} \ \mathsf{for} \ \mathsf{connected} \ \mathsf{lighting} \ \mathsf{systems}$
- Easy to design-in, configure and install with extended diagnostics via MultiOne

Features

- High surge protection (CM/DM)
- · Multiple control interfaces: DALI, 1-10V (Prog+: also AmpDim)
- · Autonomous dimming via integrated DynaDimmer
- · Constant Light Output (CLO)
- Input voltage range 120-277Vac
- \cdot Long lifetime and robust protection against moisture, vibration and temperature

Xitanium LED drivers - programmable

Application

- Outdoor
- Industry



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.