



The original!

MASTER PL-S 2 Pin

MASTER PL-S is an efficient low-wattage compact fluorescent lamp, typically used for decorative and orientation purposes. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 2-pin version is designed for operation on electromagnetic gear and is provided with a plug-in/pull-out lamp base

Benefits

- Optimal light performance for short or long operation per switch-on
- · Multiple light color choice
- · Good color rendering (CRI >80)

Features

- \cdot 2-pin base with a housing incorporating the special instant starter and capacitor
- Fluorescent tri-phosphor technology
- · Low light depreciation over lamp life

Application


- Application
- Designed for use in hotels, restaurants, theatres and homes
- · Suitable for use in signs, corridors, security and orientation lighting

Warnings and Safety

- \cdot Use only with electromagnetic control gear
- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position
- · Dimming is not possible
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

MASTER PL-S 2 Pin

Dimensional drawing



Product	D (max)	D1 (max)	C (max)
MASTER PL-S 13W/840/2P 1CT/10	27.1 mm	13 mm	178.2 mm
MASTER PL-S 13W/865/2P 1CT/10	27.1 mm	13 mm	178.2 mm

General Information	
Cap-Base	GX23
Light Technical	
Color rendering index (CRI)	82
Operating and Electrical	
Lamp Current (Nom)	0.290 A
Voltage (Nom)	56 V
Power Consumption	13.0 W
Controls and Dimming	
Dimmable	No
Approval and Application	
Mercury (Hg) Content (Nom)	1.4 mg

Light Technical

			Correlated	Luminous	
			Color	Efficacy	
	Full Product	Color	Temperature	(rated)	Luminous
Order Code	Name	Designation	(Nom)	(Nom)	Flux
Order Code 927902884066		Designation Cool White	(Nom) 4000 K	(Nom) 66 lm/W	Flux 860 lm

			Correlated	Luminous	
			Color	Efficacy	
	Full Product	Color	Temperature	(rated)	Luminous
Order Code	Name	Designation	(Nom)	(Nom)	Flux
Order Code	Name 840/2P	Designation	(Nom)	(Nom)	Flux



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.