



Product Description

MASTER PL-C 4 Pin

Energy-saving compact fluorescent lamps. Compact long-arc low-pressure mercury discharge lamp. Envelope consists of 4 parallel narrow fluorescent tubes

Benefits

- · Optimal light performance for short or long operation per switch on
- $\boldsymbol{\cdot}$ Long life and sustainable light output

Features

- · 4-pin base without starter and capacitor
- · Lamp characteristics are influenced by operating conditions and control gear used
- · Dimming is possible

Application

- Designed for general or supplementary lighting in professional or home environments
- Recessed or surface-mounted downlighters, wall units, table lamps and pendant lamps

Warnings and Safety

- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position as well as applied HF control gear
- Shorter lamp life when often switching and not well pre-heated electrodes
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

MASTER PL-C 4 Pin

Versions






LPPR PLC4P 13W

LPPR PLC4P 18W

Dimensional drawing



Product	D (max)	D1 (max)	A (max)	B (max)	C (max)
MASTER PL-C 13W/830/4P 1CT/	27.1 mm	27.1 mm	97.5 mm	117.0 mm	131.9 mm
5X10BOX					
MASTER PL-C 18W/827/4P 1CT/	27.1 mm	27.1 mm	109.5 mm	128.0 mm	142.9 mm
5X10BOX					

Light Technical	
Color rendering index (CRI)	82
Controls and Dimming	
Controts and Dimining	
Dimmable	Yes
Approval and Application	
Mercury (Hg) Content (Nom)	1.4 mg

General Information

Order Code	Full Product Name	Cap-Base
927907183001	MASTER PL-C 13W/830/4P 1CT/5X10BOX	G24q-1

Order Code	Full Product Name	Cap-Base
927907282701	MASTER PL-C 18W/827/4P 1CT/5X10BOX	G24q-2

Light Technical

			Correlated	Luminous	
			Color	Efficacy	
	Full Product	Color	Temperature	(rated)	Luminous
Order Code		.	(3.1)		
Order Code	Name	Designation	(Nom)	(Nom)	Flux
927907183001			3000 K	(Nom) 72 lm/W	900 lm

			Correlated	Luminous	
			Color	Efficacy	
	Full Product	Color	Temperature	(rated)	Luminous
Order Code	Name	Designation	(Nom)	(Nom)	Flux
Order Code	Name 830/4P 1CT/	Designation	(Nom)	(Nom)	Flux

MASTER PL-C 4 Pin

			Correlated	Luminous	
	Full Product	Color	Color Temperature	Efficacy (rated)	Luminous
Order Code			·	` ′	
	Name		(Nom)	(Nom)	Flux
927907282701	MASTER PL-	Designation Incandescent	(Nom) 2700 K	(Nom) 67 lm/W	Flux 1,200 lm

			Correlated	Luminous	
			Color	Efficacy	
	Full Product	Color	Temperature	(rated)	Luminous
Order Code	Name	Designation	(Nom)	(Nom)	Flux
	827/4P 1CT/				

Operating and Electrical

		Lamp Current	
Order Code	Full Product Name	(Nom)	Power Consumption
927907183001	MASTER PL-C 13W/830/4P	0.170 A	13.0 W
	1CT/5X10BOX		

		Lamp Current	
Order Code	Full Product Name	(Nom)	Power Consumption
927907282701	MASTER PL-C 18W/827/4P	0.230 A	16.5 W
	1CT/5X10BOX		

Approval and Application

		Energy Consumption kWh/
Order Code	Full Product Name	1000 h
927907183001	MASTER PL-C 13W/830/4P 1CT/	15 kWh
	5X10BOX	

		Energy Consumption kWh/
Order Code	Full Product Name	1000 h
927907282701	MASTER PL-C 18W/827/4P 1CT/	20 kWh
	5X10BOX	

