PHILIPS Lighting



Product Description

EB-Certalume for TL5 lamps

Affordable, reliable, high frequency electronic ballast for TL5 fluorescent lamps, ideal alternative for electromagnetic (EM) ballasts

Benefits

- Energy efficient, CELMA A3, saving 25% energy compared to electromagnetic "Ctype" ballasts
- Energy efficient, CELMA A3, saving 25% energy compared to electromagnetic "Ctype" ballasts
- The EB-C TL5 range has a robust design and meets safety, EMC and Immunity tests including safety approbation via an external test-house covering IEC/EN 61347.
- The EB-C TL5 range has a robust design and meets safety, EMC and Immunity tests including safety approbation via an external test-house covering IEC/EN 61347.
- $\boldsymbol{\cdot}$ Ideal alternative for electromagnetic ballast, no ignitor needed
- $\boldsymbol{\cdot}$ Ideal alternative for electromagnetic ballast, no ignitor needed

Features

- Energy efficient CELMA A3
- Energy efficient CELMA A3
- Complying to CCC certificate including safety acc IEC 61347
- Complying to CCC certificate including safety acc IEC 61347
- 25.000 hour lifetime at Tc max. and 3.000 on/off switches on one lamp.
- 25.000 hour lifetime at Tc max. and 3.000 on/off switches on one lamp.
- Rapid, flicker-free or warm lamp start (< 2.0 s)
- Rapid, flicker-free or warm lamp start (< 2.0 s)
- High power factor 0.95 with THD <25%
- High power factor 0.95 with THD <25%
- EMC compliant to EN 55015 2006 + A1 2007
- EMC compliant to EN 55015 2006 + A1 2007
- \cdot 45 degree connector for easy connection with push button release.
- \cdot 45 degree connector for easy connection with push button release.

EB-Certalume for TL5 lamps

Application


- Designed for applications where lamps burn for a long period of time and switching cycle (on/off) is infrequent. Typical areas of application include:
- Designed for applications where lamps burn for a long period of time and switching cycle (on/off) is infrequent. Typical areas of application include:
- Professional indoor applications (e.g. offices and hotels)
- \cdot Professional indoor applications (e.g. offices and hotels)
- $\boldsymbol{\cdot}$ Department stores, shops, supermarkets and public area's
- $\boldsymbol{\cdot}$ Department stores, shops, supermarkets and public area's
- \cdot Indoor lighting boxes
- Indoor lighting boxes
- Homes
- Homes

Versions



EB-Ci 1-2 Lamp 14-28W TL5 220-240V

Dimensional drawing



Product	A1	A2	B1	C1	D1
EB-Ci 1-2 14-28W 220-240V 50/60 Hz	210 mm	200 mm	30 mm	26 mm	4.3 mm

EB-Certalume for TL5 lamps



© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.

www.lighting.philips.com 2024, August 29 - data subject to change