



# MASTER LEDspot LV AR111 – Ideal solution for spot lighting in shops

## MASTER LEDspot LV AR111

Delivering a warm, halogen-like accent beam, MASTER LEDspot LV AR111 is an ideal retrofit solution for spot and general lighting applications in the hospitality and retail industry. It is particularly suitable for general lighting where the light is on all the time, such as creative accent lighting applications in shops, restaurants, hotels, and especially for galleries, exhibitions and museums. The robustly designed MASTER LEDspot LV AR111 offers various beam angles for a clearly defined beam spread. There is no UV or IR in the beam, making it suitable for illuminating heat-sensitive objects (food, organic materials, paintings, etc.). The patented intelligent driver enables broad compatibility with existing electromagnetic and electronic halogen transformers. MASTER LEDspot LV AR111 delivers huge energy savings and minimises maintenance cost without any reduction in brightness.

### Benefits

- Up to 80% energy saving compared with halogen lamps
- Up to 80% energy saving compared with halogen lamps
- Broad compatibility with transformers
- Broad compatibility with transformers
- Retrofittable
- Retrofittable

# MASTER LEDspot LV AR111


## Features

- Patented intelligent driver
- Patented intelligent driver
- Lifetime of 45,000 hours
- Lifetime of 45,000 hours
- Low energy consumption
- Low energy consumption
- Clearly defined beam spread
- Clearly defined beam spread
- UV- and IR-free light for less heat and protection for heat-sensitive objects
- UV- and IR-free light for less heat and protection for heat-sensitive objects

## Application

- Shops, hotels, restaurants, bars, cafés
- Shops, hotels, restaurants, bars, cafés
- Galleries, museums, exhibitions, lobbies, corridors, stairwells, washrooms, reception areas
- Galleries, museums, exhibitions, lobbies, corridors, stairwells, washrooms, reception areas

## Dimensional drawing



Product	D	C
MAS LED ExpertColor 15-75W 927 AR111 24D	111 mm	62 mm
MAS LED ExpertColor 15-75W 930 AR111 24D	111 mm	62 mm
MAS LED ExpertColor 15-75W 930 AR111 40D	111 mm	62 mm

MASTER LEDspot LV AR111



General Information	
Cap-Base	G53
Switching Cycle	50,000
Nominal lifetime	40,000 hour(s)
Light Technical	
Color rendering index (CRI)	97
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Input Frequency	- Hz
Line Frequency	- Hz
Power Consumption	15 W
Starting Time (Nom)	0.5 s
Wattage Equivalent	75 W
Temperature	
T-Case Maximum (Nom)	74 °C
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Shape	AR111
Approval and Application	
Energy Consumption kWh/1000 h	17 kWh

Light Technical (1/2)

Order Code	Full Product Name	Beam Angle (Nom)	Correlated Color Temperature (Nom)	Color Code	Luminous Flux
929002239008	MAS LED ExpertColor 15-75W 927 AR111 24D	24 degree(s)	2700 K	927	950 lm
929002239108	MAS LED ExpertColor 15-75W 930 AR111 24D	24 degree(s)	3000 K	930	1,000 lm
929002239408	MAS LED ExpertColor 15-75W 930 AR111 40D	40 degree(s)	3000 K	930	1,000 lm


Light Technical (2/2)

Order Code	Full Product Name	Luminous Intensity (Nom)
929002239008	MAS LED ExpertColor 15-75W 927 AR111 24D	3,500 cd
929002239108	MAS LED ExpertColor 15-75W 930 AR111 24D	3,500 cd
929002239408	MAS LED ExpertColor 15-75W 930 AR111 40D	1,400 cd




MASTER LEDspot LV AR111


Accent Diagrams



Accent Diagram - MAS LED ExpertColor 15-75W 927 AR111 24D




Accent Diagram - MAS LED ExpertColor 15-75W 930 AR111 24D




Accent Diagram - MAS LED ExpertColor 15-75W 930 AR111 40D


Beam Diagrams



Beam diagram - MAS LED ExpertColor 15-75W 927 AR111 24D



Beam diagram - MAS LED ExpertColor 15-75W 930 AR111 40D



Beam diagram - MAS LED ExpertColor 15-75W 930 AR111 24D

