





interact

Philips Group Cabinet Control enables customers to manage their lighting installation and energy usage. A retrofittable modular solution enabling decision-making with insights

Group Cabinet Control

Philips Group Cabinet Control enables remote grouping, monitoring, and controlling of diverse outdoor luminaires. Customers can control their lighting installations, through a retrofitted modular cabinet solution at the electrical cabinet. Supports optimized energy consumption and manages KPIs better. The solution autonomously executes complex tasks based on the configurations. The Controller can automatically switch between different available communications carriers to provide stable and reliable communications to Interact application(s).

Benefits

- · A modular solution which can be retrofitted at the existing electrical cabinet
- \cdot Customer controlled connected cabinet and lighting installation
- \cdot Can be hosted on-premise or in cloud

Features

- · Central switching (on/off) of a whole group of lighting points
- \cdot Under/over voltage supply detection
- \cdot Cabinet door 'open' detection
- Mains power failure alarm
- Includes centralized switching from either a central schedule astro-clock, a photocell or an external trigger signal.
- Flexible to connect with any compatible RS485 energy meter
- Scalable across 2G (GPRS)/3G/4G and Ethernet connectivity
- Built in GPS for accurate positioning (Gen. 3 onwards)
- Future-proof, upgradeable system
- Wide operating voltage range from 120-277V makes the controller to be used in wide geographical locations.

Application

- $\boldsymbol{\cdot}$ Road and Street
- $\boldsymbol{\cdot}$ Arena and Sports
- \cdot Tunnel

Warnings and Safety

- Refer to Documentation portal for all technical documents (https://www.partner.portal.signify.com/)
- \cdot Check the local LTE band applicable before placing an order for the controller
- \cdot No UL certification in Gen3 controller and modules
- Update forecast for Gen3 in Koolog tool to ensure on-time delivery for projects

Versions



Coded Mains Receiver Adaptor



Coded Mains Receiver LN



Coded Mains Transmitter



Coded Mains Transformer LL

Versions



Coded Mains Transformer LN



LFC7590 Surge Guard



LCU7591 Leak Coil



LFC7510 Current








LFC7530 Battery


LFC7520 Switch

LFC7550 RS485


LCU7590 3 Phase Coil


Dimensional drawing






an in a row we want to be a row we want to be














Dimensional drawing




















Product details

Coded Mains Receiver LN

Coded Mains Transmitter

PHILIPS

•••



LFC7590/00 Surge Guard front





© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.

www.lighting.philips.com 2024, August 30 - data subject to change