

ENVIRONMENTAL PRODUCT DECLARATION

IN ACCORDANCE WITH EN 15804+A2 & ISO 14025 / ISO 21930

Philips Metronomis LED Fluid

BDS670

Signify N.V.



GENERAL INFORMATION

MANUFACTURER

Manufacturer	Signify N.V.
Address	High Tech Campus 48, 5656 AE Eindhoven, The Netherlands
Contact details	sustainability@signify.com
Website	https://www.signify.com/global

EPD STANDARDS, SCOPE AND VERIFICATION

Program operator	EPD Hub, hub@epdhub.com
Reference standard	EN 15804+A2:2019 and ISO 14025
PCR	EPD Hub Core PCR version 1.0, 1 Feb 2022
Sector	Electrical product
Category of EPD	Pre-verified EPD
Scope of the EPD	Cradle to gate with options, A4-B7, and modules C1-C4, D
EPD author	Sustainability Signify
EPD verification	Independent verification of this EPD and data, according to ISO 14025: ☒ Internal certification ☐ External verification

The manufacturer has the sole ownership, liability, and responsibility for the EPD. EPDs within the same product category but from different programs may not be comparable. EPDs of lighting products may not be comparable if they do not comply with EN 15804 and if they are not compared in a lighting context.

PRODUCT

Product name	Philips Metronomis LED
Additional labels	BDS670 LED80/722 I MDM SRT 60
Product reference	910925868198
Place of production	Poland
Period for data	2022
Averaging in EPD	No averaging
Variation in GWP-fossil for A1-A3	%

ENVIRONMENTAL DATA SUMMARY

Declared unit	1 unit of 6720 lumens over 100000 hours
Declared unit mass	14.7 kg
GWP-fossil, A1-A3 (kgCO ₂ e)	3.26E+02
GWP-total, A1-A3 (kgCO ₂ e)	3.20E+02
Secondary material, inputs (%)	14.0
Secondary material, outputs (%)	40.3
Total energy use, A1-A3 (kWh)	1220.0
Total water use, A1-A3 (m ³ e)	1.82E+00

PRODUCT AND MANUFACTURER

ABOUT THE MANUFACTURER

Signify is the world leader in lighting for professionals, consumers and lighting for the Internet of Things. Our energy efficient lighting products, systems and services enable our customers to enjoy a superior quality of light, and make people’s lives safer and more comfortable, businesses more productive and cities more liveable.

For more information, please visit: <https://www.signify.com/global>

PRODUCT DESCRIPTION

Philips Metronomis LED is the first post-top luminaire range in the world to offer a palette of lighting effects to give projects a unique contextual or aesthetic touch. An innovative play of reflection, light and shadow that casts a pattern on the ground, or in the bowl, to create additional ambience. Four iconic designs are available: Metronomis LED Torch (BDS650), Metronomis LED Torch with hat (BDS651), Metronomis LED Sharp (BDS660), and Metronomis LED Fluid (BDS670). Each luminaire design has a visual and modular link to Metronomis I, reduced to its essential elements. During the day, the discreet, transparent design blends into its urban context, whether that be contemporary or classical architecture and surroundings, while its night-time appearance is both functional and decorative. Flexible and modular, the Metronomis LED family comes with a range of columns and a wide variety of effects. This enables architects and lighting designers to create a unified, consistent lighting design across any cityscape, while still reflecting the differences in urban culture and history. Metronomis LED also offers all the benefits of LEDGINE. Energy saving, serviceable and upgradable, this luminaire range is designed to maintain excellent light quality over its lifetime.

For more information, please visit <https://www.lighting.philips.com/link/BDS670/fam/aa/en>

Footer_input

PRODUCT RAW MATERIAL MAIN COMPOSITION

Raw material category	Amount, mass- %	Material origin
Metals	58.7	EU , APAC
Minerals	2.38	EU , APAC
Fossil materials	38.93	EU , APAC
Bio-based materials	0	Not applicable

BIOGENIC CARBON CONTENT

Product’s biogenic carbon content at the factory gate

Biogenic carbon content in product, kg C	0
Biogenic carbon content in packaging, kg C	1.136

FUNCTIONAL UNIT AND SERVICE LIFE

Declared unit	1 Product
Mass per declared unit	14.7 kg
Functional unit	1 unit of 6720 lumens over 100000 hours
Reference service life	100000 hours

SUBSTANCES, REACH - VERY HIGH CONCERN

The product does not contain any REACH SVHC substances in amounts greater than 0,1 % (1000 ppm).

PRODUCT LIFE-CYCLE

SYSTEM BOUNDARY

This EPD covers the life-cycle modules listed in the following table.

Product stage			Assembly stage		Use stage								End of life stage				Beyond the system boundaries	
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D		
x	x	x	x	x	MNR	MNR	MNR	MNR	MNR	x	MNR	MNR	x	x	x		x	
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	Deconstr./demol.	Transport	Waste processing	Disposal	Reuse	Recovery	Recycling

Modules not declared = MND. Modules not relevant = MNR.

MANUFACTURING AND PACKAGING (A1-A3)

The environmental impacts considered for the product stage cover the manufacturing of raw materials used in the production as well as packaging materials and other ancillary materials. Also, electricity, and waste formed in the production processes at Signify's manufacturing facilities are included in this stage.

The product is made of metals, plastics, and electronic components. All components are transported to Signify's production facility, where the main manufacturing processes primarily are associated with assembly. The finished product is packaged with polyethylene, cardboard, and/or paper as packaging material before being sent to customers. Manufacturing loss, ancillaries and wastes are calculated according to the data that each manufacturing site is sharing with Signify. The total annual amount of waste in kg is allocated to the total annual production in kg at the specific manufacturing site responsible for the production of the studied luminaire.

Footer_input

Thus, it is possible to allocate it according to the weight of the product analysed in this study. Some of the waste are due to ancillary materials used during manufacturing while the rest is due to material losses.

TRANSPORT AND INSTALLATION (A4-A5)

Transport distances were calculated on the base of the supplier location and manufacturing location and then made a cumulative group choosing the conservative scenario. Environmental impacts from installation include waste packaging materials (A5). The impacts of energy consumption and the used ancillary materials during installation are considered negligible.

PRODUCT USE AND MAINTENANCE (B1-B7)


During the use phase, the product consumes electricity from Europe's electricity grid mix (B6). The total power consumption of the reference product is calculated as follows: Wattage x Reference lifetime = kWh consumed throughout the entire use phase B6.

PRODUCT END OF LIFE (C1-C4, D)

Consumption of energy and natural resources in demolition process is assumed to be negligible. It is assumed that the waste is collected separately and transported to the waste treatment centre. Transportation distance to treatment is assumed as 150 km and the transportation method is assumed to be lorry (C2). According to EN 50693:2019, the sequence of treatment operations occurring to the product shall include de-pollution, fractions separation and preparation (dismantling, crushing, shredding, sorting), recycling, other material recovery, energy recovery and disposal. In this study, the default values from table G.4 of EN 50693 is used for treating materials in different waste treatment methods. Due to the material and energy recovery potential of parts in the lighting system, the end-of-life product is converted into recycled raw materials, while the energy recovered from incineration displaces electricity and heat

production (D). The benefits and loads of incineration and recycling are included in Module D.

SYSTEM BOUNDARY



LIFE-CYCLE ASSESSMENT

CUT-OFF CRITERIA

The study does not exclude any modules or processes which are stated mandatory in the reference standard and the applied PCR. The study does not exclude any hazardous materials or substances. The study includes all major raw material and energy consumption. All inputs and outputs of the unit processes, for which data is available for, are included in the calculation. There is no neglected unit process more than 1% of total mass or energy flows. The module specific total neglected input and output flows also do not exceed 5% of energy usage or mass.

ALLOCATION, ESTIMATES AND ASSUMPTIONS

Allocation is required if some material, energy, and waste data cannot be measured separately for the product under investigation. All allocations are done as per the reference standards and the applied PCR. In this study, ancillary materials, energy & water consumption, material loss and waste generation at the manufacturing site are attributed to the bill of materials of the products, therefore, they are allocated by partitioning the quantities on the base of the total production in kg throughout the year. Thus, allocation has been done in the following ways:

Data type	Allocation
Raw materials	No allocation
Packaging materials	No allocation
Ancillary materials	Allocated by mass or volume
Manufacturing energy and waste	Allocated by mass or volume

This EPD is created with a most conservative scenario in A1-A3 in terms of material composition.

AVERAGES AND VARIABILITY

Type of average	No averaging
Averaging method	Not applicable
Variation in GWP-fossil for A1-A3	Not applicable

This EPD is product and factory specific and does not contain average calculations. It is created with a most conservative scenario in A1-A3 in terms of material composition.

LCA SOFTWARE AND BIBLIOGRAPHY

This EPD has been created using One Click LCA EPD Generator. The LCA and EPD have been prepared according to the reference standards and ISO 14040/14044. Ecoinvent 3.8 database was used as the source of environmental data.

ENVIRONMENTAL IMPACT DATA

CORE ENVIRONMENTAL IMPACT INDICATORS – EN 15804+A2, PEF

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
GWP – total ¹⁾	kg CO ₂ e	2.93E+02	3.33E+00	2.42E+01	3.20E+02	3.33E+00	4.62E+00	MNR	MNR	MNR	MNR	MNR	2.54E+03	MNR	MNR	2.09E-01	6.24E+00	3.73E+00	-1.13E+02
GWP – fossil	kg CO ₂ e	2.94E+02	3.33E+00	2.83E+01	3.26E+02	3.32E+00	5.22E-01	MNR	MNR	MNR	MNR	MNR	2.53E+03	MNR	MNR	2.09E-01	6.23E+00	3.73E+00	-1.13E+02
GWP – biogenic	kg CO ₂ e	-1.81E+00	0.00E+00	-4.10E+00	-5.90E+00	1.29E-03	4.10E+00	MNR	MNR	MNR	MNR	MNR	0.00E+00	MNR	MNR	0.00E+00	0.00E+00	0.00E+00	-1.53E-02
GWP – LULUC	kg CO ₂ e	4.34E-01	1.30E-03	2.10E-02	4.56E-01	1.23E-03	3.86E-05	MNR	MNR	MNR	MNR	MNR	5.91E+00	MNR	MNR	7.72E-05	2.80E-04	1.97E-04	-1.05E-02
Ozone depletion pot.	kg CFC ₁₁ e	1.33E-05	7.59E-07	1.89E-06	1.60E-05	7.65E-07	1.14E-08	MNR	MNR	MNR	MNR	MNR	1.28E-04	MNR	MNR	4.81E-08	3.04E-08	2.59E-08	-3.01E-06
Acidification potential	mol H ⁺ e	1.94E+00	1.94E-02	4.22E-02	2.00E+00	1.41E-02	9.25E-04	MNR	MNR	MNR	MNR	MNR	1.44E+01	MNR	MNR	8.86E-04	3.23E-03	1.58E-03	-1.13E+00
EP-freshwater ²⁾	kg Pe	1.99E-02	2.63E-05	2.83E-04	2.02E-02	2.72E-05	1.19E-06	MNR	MNR	MNR	MNR	MNR	2.68E-01	MNR	MNR	1.71E-06	8.93E-06	7.90E-06	-6.97E-03
EP-marine	kg Ne	2.95E-01	5.46E-03	1.61E-02	3.17E-01	4.18E-03	3.98E-04	MNR	MNR	MNR	MNR	MNR	1.92E+00	MNR	MNR	2.63E-04	1.04E-03	1.59E-03	-1.25E-01
EP-terrestrial	mol Ne	3.29E+00	6.04E-02	1.37E-01	3.49E+00	4.62E-02	4.12E-03	MNR	MNR	MNR	MNR	MNR	2.18E+01	MNR	MNR	2.90E-03	1.12E-02	6.10E-03	-1.44E+00
POCP (“smog”) ³⁾	kg NMVOCe	9.89E-01	1.83E-02	4.12E-02	1.05E+00	1.48E-02	1.03E-03	MNR	MNR	MNR	MNR	MNR	5.97E+00	MNR	MNR	9.29E-04	2.87E-03	1.78E-03	-4.16E-01
ADP-minerals & metals ⁴⁾	kg Sbe	8.91E-03	7.61E-06	1.12E-04	9.03E-03	7.79E-06	3.73E-07	MNR	MNR	MNR	MNR	MNR	2.36E-02	MNR	MNR	4.90E-07	1.83E-05	8.20E-07	-1.08E-03
ADP-fossil resources	MJ	3.22E+03	4.95E+01	4.89E+02	3.76E+03	4.99E+01	9.04E-01	MNR	MNR	MNR	MNR	MNR	5.38E+04	MNR	MNR	3.14E+00	3.12E+00	2.46E+00	-1.10E+03
Water use ⁵⁾	m ³ e depr.	7.39E+01	2.18E-01	4.44E+00	7.86E+01	2.23E-01	2.11E-01	MNR	MNR	MNR	MNR	MNR	1.47E+03	MNR	MNR	1.41E-02	2.75E-01	1.94E-01	-7.72E+00

1) GWP = Global Warming Potential; 2) EP = Eutrophication potential. Required characterisation method and data are in kg P-eq. Multiply by 3,07 to get PO₄e; 3) POCP = Photochemical ozone formation; 4) ADP = Abiotic depletion potential; 5) EN 15804+A2 disclaimer for Abiotic depletion and Water use and optional indicators except Particulate matter and Ionizing radiation, human health. The results of these environmental impact indicators shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator.

ADDITIONAL (OPTIONAL) ENVIRONMENTAL IMPACT INDICATORS – EN 15804+A2, PEF

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Particulate matter	Incidence	2.12E-05	3.67E-07	5.38E-07	2.21E-05	3.83E-07	8.38E-09	MNR	MNR	MNR	MNR	MNR	4.75E-05	MNR	MNR	2.41E-08	3.66E-08	1.78E-08	-6.35E-06
Ionizing radiation ⁶⁾	kBq U235e	1.19E+01	2.35E-01	3.43E-01	1.24E+01	2.38E-01	3.19E-03	MNR	MNR	MNR	MNR	MNR	1.46E+03	MNR	MNR	1.50E-02	1.59E-02	1.18E-02	-6.52E+00

Ecotoxicity (freshwater)	CTUe	1.09E+04	4.39E+01	3.04E+02	1.13E+04	4.49E+01	5.93E+00	MNR	MNR	MNR	MNR	MNR	3.66E+04	MNR	MNR	2.83E+00	2.21E+01	7.60E+02	-2.22E+03
Human toxicity, cancer	CTUh	4.15E-07	1.15E-09	1.33E-08	4.30E-07	1.10E-09	2.77E-10	MNR	MNR	MNR	MNR	MNR	1.20E-06	MNR	MNR	6.94E-11	8.56E-10	3.56E-09	-1.19E-09
Human tox. non-cancer	CTUh	1.00E-05	4.29E-08	1.47E-07	1.02E-05	4.45E-08	1.20E-08	MNR	MNR	MNR	MNR	MNR	3.94E-05	MNR	MNR	2.80E-09	3.23E-08	5.45E-08	-2.40E-06
SQP ⁷⁾	-	1.02E+03	5.46E+01	1.53E+02	1.23E+03	5.75E+01	4.84E-01	MNR	MNR	MNR	MNR	MNR	9.73E+03	MNR	MNR	3.62E+00	4.18E+00	3.21E+00	-2.23E+02

6) EN 15804+A2 disclaimer for Ionizing radiation, human health. This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator; 7) SQP = Land use related impacts/soil quality.

USE OF NATURAL RESOURCES

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Renew. PER as energy ⁸⁾	MJ	2.41E+02	5.47E-01	5.55E+02	7.96E+02	5.63E-01	2.89E-02	MNR	MNR	MNR	MNR	MNR	1.10E+04	MNR	MNR	3.54E-02	3.45E-01	1.04E-01	-1.88E+01
Renew. PER as material	MJ	1.68E+01	0.00E+00	3.59E+01	5.27E+01	0.00E+00	-3.59E+01	MNR	MNR	MNR	MNR	MNR	0.00E+00	MNR	MNR	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Total use of renew. PER	MJ	2.58E+02	5.47E-01	5.90E+02	8.49E+02	5.63E-01	-3.59E+01	MNR	MNR	MNR	MNR	MNR	1.10E+04	MNR	MNR	3.54E-02	3.45E-01	1.04E-01	-1.88E+01
Non-re. PER as energy	MJ	3.05E+03	4.95E+01	4.76E+02	3.58E+03	4.99E+01	9.04E-01	MNR	MNR	MNR	MNR	MNR	5.37E+04	MNR	MNR	3.14E+00	3.12E+00	2.46E+00	-1.10E+03
Non-re. PER as material	MJ	1.65E+02	0.00E+00	8.80E+00	1.73E+02	0.00E+00	-8.80E+00	MNR	MNR	MNR	MNR	MNR	0.00E+00	MNR	MNR	0.00E+00	-7.99E+01	-7.52E+01	7.12E+00
Total use of non-re. PER	MJ	3.22E+03	4.95E+01	4.84E+02	3.75E+03	4.99E+01	-7.90E+00	MNR	MNR	MNR	MNR	MNR	5.37E+04	MNR	MNR	3.14E+00	-7.68E+01	-7.27E+01	-1.09E+03
Secondary materials	kg	2.06E+00	1.42E-02	2.95E+00	5.03E+00	1.39E-02	1.08E-03	MNR	MNR	MNR	MNR	MNR	5.54E+00	MNR	MNR	8.72E-04	3.40E-03	4.48E-03	4.58E+00
Renew. secondary fuels	MJ	1.53E-01	1.35E-04	2.05E-01	3.59E-01	1.40E-04	1.69E-05	MNR	MNR	MNR	MNR	MNR	4.49E-02	MNR	MNR	8.80E-06	1.43E-04	4.66E-05	-4.02E-03
Non-ren. secondary fuels	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	MNR	MNR	MNR	MNR	MNR	0.00E+00	MNR	MNR	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Use of net fresh water	m ³	1.71E+00	6.25E-03	1.05E-01	1.82E+00	6.47E-03	3.51E-03	MNR	MNR	MNR	MNR	MNR	4.63E+01	MNR	MNR	4.07E-04	9.95E-03	5.52E-03	-3.47E-01

8) PER = Primary energy resources.

END OF LIFE – WASTE

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
-----------------	------	----	----	----	-------	----	----	----	----	----	----	----	----	----	----	----	----	----	---

Hazardous waste	kg	5.03E+01	6.57E-02	7.84E-01	5.12E+01	6.62E-02	7.40E-04	MNR	MNR	MNR	MNR	MNR	1.93E+02	MNR	MNR	4.17E-03	1.60E-02	1.79E-01	-1.74E+01
Non-hazardous waste	kg	4.33E+02	1.05E+00	7.53E+00	4.42E+02	1.09E+00	3.01E+00	MNR	MNR	MNR	MNR	MNR	1.22E+04	MNR	MNR	6.84E-02	2.93E+00	5.92E+00	-3.20E+02
Radioactive waste	kg	5.00E-03	3.32E-04	2.21E-04	5.56E-03	3.34E-04	1.43E-06	MNR	MNR	MNR	MNR	MNR	3.92E-01	MNR	MNR	2.10E-05	8.56E-06	0.00E+00	-2.40E-03

END OF LIFE – OUTPUT FLOWS

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Components for re-use	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	MNR	MNR	MNR	MNR	MNR	0.00E+00	MNR	MNR	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Materials for recycling	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	MNR	MNR	MNR	MNR	MNR	0.00E+00	MNR	MNR	0.00E+00	5.92E+00	0.00E+00	0.00E+00
Materials for energy rec	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	MNR	MNR	MNR	MNR	MNR	0.00E+00	MNR	MNR	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Exported energy	MJ	0.00E+00	0.00E+00	2.56E+00	2.56E+00	0.00E+00	0.00E+00	MNR	MNR	MNR	MNR	MNR	0.00E+00	MNR	MNR	0.00E+00	5.68E+01	0.00E+00	0.00E+00

ENVIRONMENTAL IMPACTS – EN 15804+A1, CML / ISO 21930

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Global Warming Pot.	kg CO ₂ e	2.85E+02	3.29E+00	2.83E+01	3.16E+02	3.29E+00	5.17E-01	MNR	MNR	MNR	MNR	MNR	2.50E+03	MNR	MNR	2.07E-01	6.22E+00	4.10E+00	-1.10E+02
Ozone depletion Pot.	kg CFC ₁₁ e	1.21E-05	6.01E-07	1.64E-06	1.43E-05	6.06E-07	9.96E-09	MNR	MNR	MNR	MNR	MNR	1.11E-04	MNR	MNR	3.81E-08	2.58E-08	2.14E-08	-2.55E-06
Acidification	kg SO ₂ e	1.63E+00	1.52E-02	3.17E-02	1.68E+00	1.09E-02	6.72E-04	MNR	MNR	MNR	MNR	MNR	1.23E+01	MNR	MNR	6.88E-04	2.48E-03	1.18E-03	-9.76E-01
Eutrophication	kg PO ₄ ³ e	5.66E-01	2.90E-03	1.68E-02	5.86E-01	2.49E-03	5.05E-04	MNR	MNR	MNR	MNR	MNR	9.43E+00	MNR	MNR	1.57E-04	1.33E-03	1.22E-02	-2.72E-01

POCP ("smog")	kg C ₂ H ₄ e	1.02E-01	5.29E-04	2.75E-03	1.06E-01	4.27E-04	2.03E-05	MNR	MNR	MNR	MNR	MNR	5.01E-01	MNR	MNR	2.69E-05	8.11E-05	1.59E-04	-4.82E-02
ADP-elements	kg Sbe	8.79E-03	7.38E-06	1.09E-04	8.91E-03	7.55E-06	2.95E-07	MNR	MNR	MNR	MNR	MNR	2.36E-02	MNR	MNR	4.75E-07	1.81E-05	6.45E-07	-1.07E-03
ADP-fossil	MJ	3.20E+03	4.95E+01	4.89E+02	3.73E+03	4.99E+01	9.04E-01	MNR	MNR	MNR	MNR	MNR	5.37E+04	MNR	MNR	3.14E+00	3.12E+00	2.46E+00	-1.10E+03

APPENDIX (PEP ECOPASSPORT ALIGNED)

This section represents the scaling method for the **B6 module**, following the PEP EcoPassport PSR for luminaries (PSR-0014-ed2.0-EN-2023 07 13). The GWP results were scaled from a reference variant of a product family, based on various light management scenarios and power inputs of the luminaires within the same product family

To calculate the Scaled Impact (*SI*), we have followed the below methods:

1. Calculate the power scaling factor (PSF), which is the ratio of the power input of the variant in questions P_{in} and the power input of the base variant P_{base} .

$$PSF = \frac{P_{in}}{P_{base}}$$

2. Calculate the Total Scaling factor by multiplying the PSF by the control scaling factor (CSF), where the CSF is determined according the relevant control factor scenario (e.g. if the luminaire has a presence detection system). The presented controls factors values in Table A1 are based on BS EN 15193-1:2017. Please refer to this publication or contact Signify directly for more information.

$$TSF = PSF * CSF$$

Table A1: Light management function (PEP EcoPassport aligned)

Scenario	Abbrev.	CSF
No control	NC	1
Daylight dependency factor	DD	0.75
Presence sensing	PS	0.75
Daylight dependency and presence sensing	DD+PS	0.55

3. Lastly, the GWP of the base variant is then scaled by the TSF.

$$\text{Scaled Impact} = \text{GWP}_{\text{case}} * \text{TSF}$$

Table A2 Scaled GWP per scaling factor (EPD Hub aligned)

Configuration	Flux [lm]	Power [W]	Efficacy [lm/W]	PSF	Total Scaling Factor (TSF)				Scaled Impacts (GWP100 B6 - kg CO2eq.)			
					NC	DD	PS	DD+PS	NC	DD	PS	DD+PS
BDS670 LED20/740	1680.0	12.8	131.2	0.203	0.203	0.152	0.152	0.112	2233.0	1672.0	1672.0	1232.0
BDS670 LED25/740	2100.0	15.8	132.9	0.251	0.251	0.188	0.188	0.138	2761.0	2068.0	2068.0	1518.0
BDS670 LED30/740	2490.0	18.6	133.9	0.295	0.295	0.221	0.221	0.162	3245.0	2431.0	2431.0	1782.0
BDS670 LED40/740	3320.0	25.0	132.8	0.397	0.397	0.298	0.298	0.218	4367.0	3278.0	3278.0	2398.0
BDS670 LED50/740	4200.0	29.5	142.4	0.468	0.468	0.351	0.351	0.257	5148.0	3861.0	3861.0	2827.0
BDS670 LED60/740	5040.0	35.5	142.0	0.563	0.563	0.422	0.422	0.31	6193.0	4642.0	4642.0	3410.0
BDS670 LED70/740	5880.0	41.0	143.4	0.651	0.651	0.488	0.488	0.358	7161.0	5368.0	5368.0	3938.0
BDS670 LED80/740	6720.0	46.0	146.1	0.73	0.73	0.547	0.547	0.402	8030.0	6017.0	6017.0	4422.0
BDS670 LED90/740	7560.0	52.0	145.4	0.825	0.825	0.619	0.619	0.454	9075.0	6809.0	6809.0	4994.0
BDS670 LED100/740	8300.0	58.0	143.1	0.921	0.921	0.691	0.691	0.507	10131.0	7601.0	7601.0	5577.0
BDS670 LED110/740	9130.0	63.0	144.9	1.0	1.0	0.75	0.75	0.55	11000.0	8250.0	8250.0	6050.0
BDS670 LED120/740	9960.0	69.0	144.3	1.095	1.095	0.821	0.821	0.602	12045.0	9031.0	9031.0	6622.0

BDS670 LED15/840	1260.0	11.8	106.8	0.187	0.187	0.14	0.14	0.103	2057.0	1540.0	1540.0	1133.0
BDS670 LED20/840	1680.0	15.6	107.7	0.248	0.248	0.186	0.186	0.136	2728.0	2046.0	2046.0	1496.0
BDS670 LED25/840	2075.0	19.2	108.1	0.305	0.305	0.229	0.229	0.168	3355.0	2519.0	2519.0	1848.0
BDS670 LED30/840	2490.0	23.0	108.3	0.365	0.365	0.274	0.274	0.201	4015.0	3014.0	3014.0	2211.0
BDS670 LED40/840	3280.0	31.5	104.1	0.5	0.5	0.375	0.375	0.275	5500.0	4125.0	4125.0	3025.0
BDS670 LED50/840	4200.0	36.5	115.1	0.579	0.579	0.434	0.434	0.318	6369.0	4774.0	4774.0	3498.0
BDS670 LED60/840	5040.0	43.5	115.9	0.69	0.69	0.517	0.517	0.38	7590.0	5687.0	5687.0	4180.0
BDS670 LED70/840	5810.0	51.0	113.9	0.81	0.81	0.608	0.608	0.446	8910.0	6688.0	6688.0	4906.0
BDS670 LED80/840	6640.0	57.0	116.5	0.905	0.905	0.679	0.679	0.498	9955.0	7469.0	7469.0	5478.0
BDS670 LED90/840	7470.0	64.0	116.7	1.016	1.016	0.762	0.762	0.559	11176.0	8382.0	8382.0	6149.0
BDS670 LED100/840	8300.0	71.0	116.9	1.127	1.127	0.845	0.845	0.62	12397.0	9295.0	9295.0	6820.0
BDS670 LED110/840	9130.0	79.0	115.6	1.254	1.254	0.941	0.941	0.69	13794.0	10351.0	10351.0	7590.0
BDS670 LED120/840	9840.0	87.0	113.1	1.381	1.381	1.036	1.036	0.76	15191.0	11396.0	11396.0	8360.0
BDS670 LED15/722	1260.0	13.0	96.9	0.206	0.206	0.154	0.154	0.113	2266.0	1694.0	1694.0	1243.0
BDS670 LED20/722	1680.0	17.2	97.7	0.273	0.273	0.205	0.205	0.15	3003.0	2255.0	2255.0	1650.0
BDS670 LED25/722	2075.0	21.5	96.5	0.341	0.341	0.256	0.256	0.188	3751.0	2816.0	2816.0	2068.0
BDS670 LED30/722	2490.0	26.0	95.8	0.413	0.413	0.31	0.31	0.227	4543.0	3410.0	3410.0	2497.0
BDS670 LED40/722	3360.0	32.5	103.4	0.516	0.516	0.387	0.387	0.284	5676.0	4257.0	4257.0	3124.0
BDS670 LED50/722	4200.0	40.5	103.7	0.643	0.643	0.482	0.482	0.354	7073.0	5302.0	5302.0	3894.0
BDS670 LED60/722	4980.0	48.5	102.7	0.77	0.77	0.578	0.578	0.424	8470.0	6358.0	6358.0	4664.0
BDS670 LED70/722	5810.0	57.0	101.9	0.905	0.905	0.679	0.679	0.498	9955.0	7469.0	7469.0	5478.0
BDS670 LED80/722	6640.0	63.0	105.4	1.0	1.0	0.75	0.75	0.55	11000.0	8250.0	8250.0	6050.0
BDS670 LED90/722	7470.0	71.0	105.2	1.127	1.127	0.845	0.845	0.62	12397.0	9295.0	9295.0	6820.0
BDS670 LED100/722	8300.0	80.0	103.8	1.27	1.27	0.953	0.953	0.699	13970.0	10483.0	10483.0	7689.0

BDS670 LED110/722	9020.0	88.0	102.5	1.397	1.397	1.048	1.048	0.768	15367.0	11528.0	11528.0	8448.0
BDS670 LED120/722	9840.0	97.0	101.4	1.54	1.54	1.155	1.155	0.847	16940.0	12705.0	12705.0	9317.0
BDS670 LED15/727	1260.0	11.4	110.5	0.181	0.181	0.136	0.136	0.1	1991.0	1496.0	1496.0	1100.0
BDS670 LED20/727	1680.0	14.8	113.5	0.235	0.235	0.176	0.176	0.129	2585.0	1936.0	1936.0	1419.0
BDS670 LED25/727	2075.0	18.2	114.0	0.289	0.289	0.217	0.217	0.159	3179.0	2387.0	2387.0	1749.0
BDS670 LED30/727	2490.0	22.0	113.2	0.349	0.349	0.262	0.262	0.192	3839.0	2882.0	2882.0	2112.0
BDS670 LED40/727	3280.0	30.0	109.3	0.476	0.476	0.357	0.357	0.262	5236.0	3927.0	3927.0	2882.0
BDS670 LED50/727	4200.0	34.5	121.7	0.548	0.548	0.411	0.411	0.301	6028.0	4521.0	4521.0	3311.0
BDS670 LED60/727	4980.0	41.5	120.0	0.659	0.659	0.494	0.494	0.362	7249.0	5434.0	5434.0	3982.0
BDS670 LED70/727	5810.0	48.5	119.8	0.77	0.77	0.578	0.578	0.424	8470.0	6358.0	6358.0	4664.0
BDS670 LED80/727	6640.0	54.0	123.0	0.857	0.857	0.643	0.643	0.471	9427.0	7073.0	7073.0	5181.0
BDS670 LED90/727	7470.0	61.0	122.5	0.968	0.968	0.726	0.726	0.532	10648.0	7986.0	7986.0	5852.0
BDS670 LED100/727	8300.0	68.0	122.1	1.079	1.079	0.809	0.809	0.593	11869.0	8899.0	8899.0	6523.0
BDS670 LED110/727	9020.0	75.0	120.3	1.19	1.19	0.892	0.892	0.654	13090.0	9812.0	9812.0	7194.0
BDS670 LED120/727	9840.0	82.0	120.0	1.302	1.302	0.977	0.977	0.716	14322.0	10747.0	10747.0	7876.0
BDS670 LED20/730	1680.0	13.4	125.4	0.213	0.213	0.16	0.16	0.117	2343.0	1760.0	1760.0	1287.0
BDS670 LED25/730	2100.0	16.6	126.5	0.263	0.263	0.197	0.197	0.145	2893.0	2167.0	2167.0	1595.0
BDS670 LED30/730	2490.0	19.8	125.8	0.314	0.314	0.235	0.235	0.173	3454.0	2585.0	2585.0	1903.0
BDS670 LED40/730	3320.0	26.5	125.3	0.421	0.421	0.316	0.316	0.232	4631.0	3476.0	3476.0	2552.0
BDS670 LED50/730	4200.0	31.5	133.3	0.5	0.5	0.375	0.375	0.275	5500.0	4125.0	4125.0	3025.0
BDS670 LED60/730	5040.0	37.5	134.4	0.595	0.595	0.446	0.446	0.327	6545.0	4906.0	4906.0	3597.0
BDS670 LED70/730	5880.0	43.5	135.2	0.69	0.69	0.517	0.517	0.38	7590.0	5687.0	5687.0	4180.0
BDS670 LED80/730	6720.0	48.5	138.6	0.77	0.77	0.578	0.578	0.424	8470.0	6358.0	6358.0	4664.0
BDS670 LED90/730	7470.0	55.0	135.8	0.873	0.873	0.655	0.655	0.48	9603.0	7205.0	7205.0	5280.0

BDS670 LED100/730	8300.0	61.0	136.1	0.968	0.968	0.726	0.726	0.532	10648.0	7986.0	7986.0	5852.0
BDS670 LED110/730	9130.0	67.0	136.3	1.063	1.063	0.797	0.797	0.585	11693.0	8767.0	8767.0	6435.0
BDS670 LED120/730	9960.0	74.0	134.6	1.175	1.175	0.881	0.881	0.646	12925.0	9691.0	9691.0	7106.0
BDS670 LED15/827	1260.0	13.0	96.9	0.206	0.206	0.154	0.154	0.113	2266.0	1694.0	1694.0	1243.0
BDS670 LED20/827	1680.0	17.2	97.7	0.273	0.273	0.205	0.205	0.15	3003.0	2255.0	2255.0	1650.0
BDS670 LED25/827	2075.0	21.5	96.5	0.341	0.341	0.256	0.256	0.188	3751.0	2816.0	2816.0	2068.0
BDS670 LED30/827	2490.0	26.0	95.8	0.413	0.413	0.31	0.31	0.227	4543.0	3410.0	3410.0	2497.0
BDS670 LED50/827	4200.0	40.5	103.7	0.643	0.643	0.482	0.482	0.354	7073.0	5302.0	5302.0	3894.0
BDS670 LED60/827	4980.0	48.5	102.7	0.77	0.77	0.578	0.578	0.424	8470.0	6358.0	6358.0	4664.0
BDS670 LED70/827	5810.0	57.0	101.9	0.905	0.905	0.679	0.679	0.498	9955.0	7469.0	7469.0	5478.0
BDS670 LED80/827	6640.0	63.0	105.4	1.0	1.0	0.75	0.75	0.55	11000.0	8250.0	8250.0	6050.0
BDS670 LED90/827	7470.0	71.0	105.2	1.127	1.127	0.845	0.845	0.62	12397.0	9295.0	9295.0	6820.0
BDS670 LED100/827	8300.0	80.0	103.8	1.27	1.27	0.953	0.953	0.699	13970.0	10483.0	10483.0	7689.0
BDS670 LED110/827	9020.0	88.0	102.5	1.397	1.397	1.048	1.048	0.768	15367.0	11528.0	11528.0	8448.0
BDS670 LED120/827	9840.0	97.0	101.4	1.54	1.54	1.155	1.155	0.847	16940.0	12705.0	12705.0	9317.0
BDS670 LED15/830	1260.0	12.2	103.3	0.194	0.194	0.146	0.146	0.107	2134.0	1606.0	1606.0	1177.0
BDS670 LED20/830	1680.0	16.0	105.0	0.254	0.254	0.191	0.191	0.14	2794.0	2101.0	2101.0	1540.0
BDS670 LED25/830	2075.0	19.8	104.8	0.314	0.314	0.235	0.235	0.173	3454.0	2585.0	2585.0	1903.0
BDS670 LED30/830	2490.0	24.0	103.8	0.381	0.381	0.286	0.286	0.21	4191.0	3146.0	3146.0	2310.0
BDS670 LED40/830	3280.0	32.5	100.9	0.516	0.516	0.387	0.387	0.284	5676.0	4257.0	4257.0	3124.0
BDS670 LED50/830	4200.0	37.5	112.0	0.595	0.595	0.446	0.446	0.327	6545.0	4906.0	4906.0	3597.0
BDS670 LED60/830	5040.0	45.0	112.0	0.714	0.714	0.535	0.535	0.393	7854.0	5885.0	5885.0	4323.0
BDS670 LED70/830	5810.0	53.0	109.6	0.841	0.841	0.631	0.631	0.463	9251.0	6941.0	6941.0	5093.0
BDS670 LED80/830	6640.0	59.0	112.5	0.937	0.937	0.703	0.703	0.515	10307.0	7733.0	7733.0	5665.0

BDS670 LED90/830	7470.0	66.0	113.2	1.048	1.048	0.786	0.786	0.576	11528.0	8646.0	8646.0	6336.0
BDS670 LED100/830	8300.0	74.0	112.2	1.175	1.175	0.881	0.881	0.646	12925.0	9691.0	9691.0	7106.0
BDS670 LED110/830	9130.0	82.0	111.3	1.302	1.302	0.977	0.977	0.716	14322.0	10747.0	10747.0	7876.0
BDS670 LED120/830	9840.0	90.0	109.3	1.429	1.429	1.072	1.072	0.786	15719.0	11792.0	11792.0	8646.0

APPENDIX (PEP ECOPASSPORT ALIGNED)

This section represents the scaling method for the **B6 module**, following the PEP EcoPassport PSR for luminaries (PSR-0014-ed2.0-EN-2023 07 13). The GWP results were scaled from a reference variant of a product family, based on various light management functions, the lumen output (O_{lum}) and reference service life (RSL) of each product within the same product family.

To calculate the Scaled Impact (SI_{pep}), we have followed the below methods:

1. Calculate the power scaling factor (PSF), which is the ratio of the power input of the variant in questions P_{in} and the power input of the base variant P_{base} .

$$PSF = \frac{P_{in}}{P_{base}}$$

2. Using this scaled GWP, we then can apply the PEP Ecopassport method for calculating the environmental impact of the functional unit for a luminary (1000 lumens over 35000 hours), applied to B6, where the Functional Unit application considers the lumen output (Olum) and reference service lifetime (RSL) of the product to estimate the final environmental impact. The scaled impact (SI_{pep}) is presented in Table A4.

$$GSF = \frac{FU_{pep}}{FU_p} = \frac{1,000}{O_{lum}} * \frac{35,000}{RSL}$$

3. Calculate the GWP scaling factor (PGSF), by multiplying the PSF by the GSF.

$$PGSF = PSF * GSF$$

4. Calculate the Total Scaling factor by multiplying the PSF by the control scaling factor (CSF), where the CSF is determined according the relevant control factor scenario (e.g. if the luminaire has a presence detection system), as presented in Table A1.

$$TSF = PGSF * CSF$$

Table A3: Light management functions (PEP EcoPassport aligned)

Scenario	Abbrev.	CSF
No control	NC	1
Daylight dependency factor	DD	0.75
Presence sensing	PS	0.75
Daylight dependency and presence sensing	DD+PS	0.55

5. Lastly, the GWP of the base variant is then scaled by the TSF.

$$\text{Scaled GWP} = \text{GWP}_{\text{case}} * \text{TSF}$$

As described in the EPD, calculations are made based on dataset describing electricity available on the low voltage level in Europe for year 2022 (source Ecoinvent 3.8 database). This value should be adjusted depending on specific project requirements. Presented controls factors and functional unit conversion values are based on the PEP EcoPassport PSR for luminaries (PSR-0014-ed2.0-EN-2023 07 13). Please refer to this publication or contact Signify directly for more information.

Table A4 Scale impact per scaling factor (PEP EcoPassport aligned)

Configuration	Flux [lm]	Power [W]	Efficacy [lm/W]	PSF	Total Scaling Factor (TSF)				Scaled Impacts (GWP100 B6 - kg CO2eq.)			
					NC	DD	PS	DD+PS	NC	DD	PS	DD+PS
BDS670 LED20/740	1680.0	12.8	131.2	0.042	0.042	0.032	0.032	0.023	462.0	352.0	352.0	253.0
BDS670 LED25/740	2100.0	15.8	132.9	0.042	0.042	0.032	0.032	0.023	462.0	352.0	352.0	253.0
BDS670 LED30/740	2490.0	18.6	133.9	0.042	0.042	0.032	0.032	0.023	462.0	352.0	352.0	253.0
BDS670 LED40/740	3320.0	25.0	132.8	0.042	0.042	0.032	0.032	0.023	462.0	352.0	352.0	253.0
BDS670 LED50/740	4200.0	29.5	142.4	0.039	0.039	0.029	0.029	0.021	429.0	319.0	319.0	231.0
BDS670 LED60/740	5040.0	35.5	142.0	0.039	0.039	0.029	0.029	0.021	429.0	319.0	319.0	231.0
BDS670 LED70/740	5880.0	41.0	143.4	0.039	0.039	0.029	0.029	0.021	429.0	319.0	319.0	231.0
BDS670 LED80/740	6720.0	46.0	146.1	0.038	0.038	0.028	0.028	0.021	418.0	308.0	308.0	231.0
BDS670 LED90/740	7560.0	52.0	145.4	0.038	0.038	0.028	0.028	0.021	418.0	308.0	308.0	231.0
BDS670 LED100/740	8300.0	58.0	143.1	0.039	0.039	0.029	0.029	0.021	429.0	319.0	319.0	231.0
BDS670 LED110/740	9130.0	63.0	144.9	0.038	0.038	0.028	0.028	0.021	418.0	308.0	308.0	231.0
BDS670 LED120/740	9960.0	69.0	144.3	0.038	0.038	0.028	0.028	0.021	418.0	308.0	308.0	231.0

BDS670 LED15/840	1260.0	11.8	106.8	0.052	0.052	0.039	0.039	0.029	572.0	429.0	429.0	319.0
BDS670 LED20/840	1680.0	15.6	107.7	0.052	0.052	0.039	0.039	0.029	572.0	429.0	429.0	319.0
BDS670 LED25/840	2075.0	19.2	108.1	0.052	0.052	0.039	0.039	0.029	572.0	429.0	429.0	319.0
BDS670 LED30/840	2490.0	23.0	108.3	0.051	0.051	0.038	0.038	0.028	561.0	418.0	418.0	308.0
BDS670 LED40/840	3280.0	31.5	104.1	0.053	0.053	0.04	0.04	0.029	583.0	440.0	440.0	319.0
BDS670 LED50/840	4200.0	36.5	115.1	0.048	0.048	0.036	0.036	0.026	528.0	396.0	396.0	286.0
BDS670 LED60/840	5040.0	43.5	115.9	0.048	0.048	0.036	0.036	0.026	528.0	396.0	396.0	286.0
BDS670 LED70/840	5810.0	51.0	113.9	0.049	0.049	0.037	0.037	0.027	539.0	407.0	407.0	297.0
BDS670 LED80/840	6640.0	57.0	116.5	0.048	0.048	0.036	0.036	0.026	528.0	396.0	396.0	286.0
BDS670 LED90/840	7470.0	64.0	116.7	0.048	0.048	0.036	0.036	0.026	528.0	396.0	396.0	286.0
BDS670 LED100/840	8300.0	71.0	116.9	0.047	0.047	0.035	0.035	0.026	517.0	385.0	385.0	286.0
BDS670 LED110/840	9130.0	79.0	115.6	0.048	0.048	0.036	0.036	0.026	528.0	396.0	396.0	286.0
BDS670 LED120/840	9840.0	87.0	113.1	0.05	0.05	0.038	0.038	0.028	550.0	418.0	418.0	308.0
BDS670 LED15/722	1260.0	13.0	96.9	0.057	0.057	0.043	0.043	0.031	627.0	473.0	473.0	341.0
BDS670 LED20/722	1680.0	17.2	97.7	0.057	0.057	0.043	0.043	0.031	627.0	473.0	473.0	341.0
BDS670 LED25/722	2075.0	21.5	96.5	0.058	0.058	0.044	0.044	0.032	638.0	484.0	484.0	352.0
BDS670 LED30/722	2490.0	26.0	95.8	0.058	0.058	0.044	0.044	0.032	638.0	484.0	484.0	352.0
BDS670 LED40/722	3360.0	32.5	103.4	0.054	0.054	0.041	0.041	0.03	594.0	451.0	451.0	330.0
BDS670 LED50/722	4200.0	40.5	103.7	0.053	0.053	0.04	0.04	0.029	583.0	440.0	440.0	319.0
BDS670 LED60/722	4980.0	48.5	102.7	0.054	0.054	0.041	0.041	0.03	594.0	451.0	451.0	330.0
BDS670 LED70/722	5810.0	57.0	101.9	0.054	0.054	0.041	0.041	0.03	594.0	451.0	451.0	330.0
BDS670 LED80/722	6640.0	63.0	105.4	0.053	0.053	0.04	0.04	0.029	583.0	440.0	440.0	319.0
BDS670 LED90/722	7470.0	71.0	105.2	0.053	0.053	0.04	0.04	0.029	583.0	440.0	440.0	319.0
BDS670 LED100/722	8300.0	80.0	103.8	0.053	0.053	0.04	0.04	0.029	583.0	440.0	440.0	319.0

BDS670 LED110/722	9020.0	88.0	102.5	0.054	0.054	0.041	0.041	0.03	594.0	451.0	451.0	330.0
BDS670 LED120/722	9840.0	97.0	101.4	0.055	0.055	0.041	0.041	0.03	605.0	451.0	451.0	330.0
BDS670 LED15/727	1260.0	11.4	110.5	0.05	0.05	0.038	0.038	0.028	550.0	418.0	418.0	308.0
BDS670 LED20/727	1680.0	14.8	113.5	0.049	0.049	0.037	0.037	0.027	539.0	407.0	407.0	297.0
BDS670 LED25/727	2075.0	18.2	114.0	0.049	0.049	0.037	0.037	0.027	539.0	407.0	407.0	297.0
BDS670 LED30/727	2490.0	22.0	113.2	0.049	0.049	0.037	0.037	0.027	539.0	407.0	407.0	297.0
BDS670 LED40/727	3280.0	30.0	109.3	0.051	0.051	0.038	0.038	0.028	561.0	418.0	418.0	308.0
BDS670 LED50/727	4200.0	34.5	121.7	0.045	0.045	0.034	0.034	0.025	495.0	374.0	374.0	275.0
BDS670 LED60/727	4980.0	41.5	120.0	0.046	0.046	0.035	0.035	0.025	506.0	385.0	385.0	275.0
BDS670 LED70/727	5810.0	48.5	119.8	0.046	0.046	0.035	0.035	0.025	506.0	385.0	385.0	275.0
BDS670 LED80/727	6640.0	54.0	123.0	0.045	0.045	0.034	0.034	0.025	495.0	374.0	374.0	275.0
BDS670 LED90/727	7470.0	61.0	122.5	0.045	0.045	0.034	0.034	0.025	495.0	374.0	374.0	275.0
BDS670 LED100/727	8300.0	68.0	122.1	0.045	0.045	0.034	0.034	0.025	495.0	374.0	374.0	275.0
BDS670 LED110/727	9020.0	75.0	120.3	0.046	0.046	0.035	0.035	0.025	506.0	385.0	385.0	275.0
BDS670 LED120/727	9840.0	82.0	120.0	0.047	0.047	0.035	0.035	0.026	517.0	385.0	385.0	286.0
BDS670 LED20/730	1680.0	13.4	125.4	0.044	0.044	0.033	0.033	0.024	484.0	363.0	363.0	264.0
BDS670 LED25/730	2100.0	16.6	126.5	0.044	0.044	0.033	0.033	0.024	484.0	363.0	363.0	264.0
BDS670 LED30/730	2490.0	19.8	125.8	0.044	0.044	0.033	0.033	0.024	484.0	363.0	363.0	264.0
BDS670 LED40/730	3320.0	26.5	125.3	0.044	0.044	0.033	0.033	0.024	484.0	363.0	363.0	264.0
BDS670 LED50/730	4200.0	31.5	133.3	0.042	0.042	0.032	0.032	0.023	462.0	352.0	352.0	253.0
BDS670 LED60/730	5040.0	37.5	134.4	0.041	0.041	0.031	0.031	0.023	451.0	341.0	341.0	253.0
BDS670 LED70/730	5880.0	43.5	135.2	0.041	0.041	0.031	0.031	0.023	451.0	341.0	341.0	253.0
BDS670 LED80/730	6720.0	48.5	138.6	0.04	0.04	0.03	0.03	0.022	440.0	330.0	330.0	242.0
BDS670 LED90/730	7470.0	55.0	135.8	0.041	0.041	0.031	0.031	0.023	451.0	341.0	341.0	253.0

BDS670 LED100/730	8300.0	61.0	136.1	0.041	0.041	0.031	0.031	0.023	451.0	341.0	341.0	253.0
BDS670 LED110/730	9130.0	67.0	136.3	0.04	0.04	0.03	0.03	0.022	440.0	330.0	330.0	242.0
BDS670 LED120/730	9960.0	74.0	134.6	0.041	0.041	0.031	0.031	0.023	451.0	341.0	341.0	253.0
BDS670 LED15/827	1260.0	13.0	96.9	0.057	0.057	0.043	0.043	0.031	627.0	473.0	473.0	341.0
BDS670 LED20/827	1680.0	17.2	97.7	0.057	0.057	0.043	0.043	0.031	627.0	473.0	473.0	341.0
BDS670 LED25/827	2075.0	21.5	96.5	0.058	0.058	0.044	0.044	0.032	638.0	484.0	484.0	352.0
BDS670 LED30/827	2490.0	26.0	95.8	0.058	0.058	0.044	0.044	0.032	638.0	484.0	484.0	352.0
BDS670 LED50/827	4200.0	40.5	103.7	0.053	0.053	0.04	0.04	0.029	583.0	440.0	440.0	319.0
BDS670 LED60/827	4980.0	48.5	102.7	0.054	0.054	0.041	0.041	0.03	594.0	451.0	451.0	330.0
BDS670 LED70/827	5810.0	57.0	101.9	0.054	0.054	0.041	0.041	0.03	594.0	451.0	451.0	330.0
BDS670 LED80/827	6640.0	63.0	105.4	0.053	0.053	0.04	0.04	0.029	583.0	440.0	440.0	319.0
BDS670 LED90/827	7470.0	71.0	105.2	0.053	0.053	0.04	0.04	0.029	583.0	440.0	440.0	319.0
BDS670 LED100/827	8300.0	80.0	103.8	0.053	0.053	0.04	0.04	0.029	583.0	440.0	440.0	319.0
BDS670 LED110/827	9020.0	88.0	102.5	0.054	0.054	0.041	0.041	0.03	594.0	451.0	451.0	330.0
BDS670 LED120/827	9840.0	97.0	101.4	0.055	0.055	0.041	0.041	0.03	605.0	451.0	451.0	330.0
BDS670 LED15/830	1260.0	12.2	103.3	0.054	0.054	0.041	0.041	0.03	594.0	451.0	451.0	330.0
BDS670 LED20/830	1680.0	16.0	105.0	0.053	0.053	0.04	0.04	0.029	583.0	440.0	440.0	319.0
BDS670 LED25/830	2075.0	19.8	104.8	0.053	0.053	0.04	0.04	0.029	583.0	440.0	440.0	319.0
BDS670 LED30/830	2490.0	24.0	103.8	0.054	0.054	0.041	0.041	0.03	594.0	451.0	451.0	330.0
BDS670 LED40/830	3280.0	32.5	100.9	0.055	0.055	0.041	0.041	0.03	605.0	451.0	451.0	330.0
BDS670 LED50/830	4200.0	37.5	112.0	0.049	0.049	0.037	0.037	0.027	539.0	407.0	407.0	297.0
BDS670 LED60/830	5040.0	45.0	112.0	0.049	0.049	0.037	0.037	0.027	539.0	407.0	407.0	297.0
BDS670 LED70/830	5810.0	53.0	109.6	0.05	0.05	0.038	0.038	0.028	550.0	418.0	418.0	308.0
BDS670 LED80/830	6640.0	59.0	112.5	0.05	0.05	0.038	0.038	0.028	550.0	418.0	418.0	308.0



BDS670 LED90/830	7470.0	66.0	113.2	0.049	0.049	0.037	0.037	0.027	539.0	407.0	407.0	297.0
BDS670 LED100/830	8300.0	74.0	112.2	0.049	0.049	0.037	0.037	0.027	539.0	407.0	407.0	297.0
BDS670 LED110/830	9130.0	82.0	111.3	0.049	0.049	0.037	0.037	0.027	539.0	407.0	407.0	297.0
BDS670 LED120/830	9840.0	90.0	109.3	0.051	0.051	0.038	0.038	0.028	561.0	418.0	418.0	308.0

