Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: PHILIPS

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

Model identifier: 9290013235D

Type	of I	ight	sour	ce:
IVDC	U I I	ISIIL	JUUI	···

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	E27		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters

Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
<u> </u>	nption in on- 00 h), rounded st integer	7	Energy efficiency class	E		
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone errow cone (90º)	806 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000		
On-mode pow pressed in W	ver (P _{on}), ex-	7,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00		
(P _{net}) for CLS, 6	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80		
Outer dimen-	Height	106	Spectral power dis-	See image		
sions without	Width	60	tribution in the	in last page		
separate con- trol gear, light- ing control	Depth	60	range 250 nm to 800 nm, at full-load			

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	60		
		Chromaticity coordinates (x and y)	0,380 0,380		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	1	Survival factor	0,90		
the lumen maintenance factor	0,93				
Parameters for LED and OLED r	Parameters for LED and OLED mains light sources:				
displacement factor (cos φ1)	0,50	Colour consistency in McAdam ellipses	6		
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-	If yes then replace- ment claim (W)	-		
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,9		

(a)'-': not applicable; (b)'-': not applicable;

