



CoreLine panel

RC132V G5 36S/840 PSD W60L60 OC

CoreLine panel, 28.5 W, 600x600 mm, 3600 lm, 4000 K, DALI, UGR19

Whether for a new building or renovation of an existing space, customers want lighting solutions that provide quality of light and substantial energy and maintenance savings. The new CoreLine Panel range of LED products can be used to replace functional luminaires in general lighting applications. Both Non-Office Compliant (NOC) version and Office Compliant version (OC) are now available. The process of selecting, installing and maintaining is so easy – it's a simple switch. Also available as an Interact Ready wireless CoreLine luminaire panel that works with Interact Pro lighting software and InteractReady devices to provide a connected lighting system for SMEs

Product data

General Information	
Light source replaceable	No
Number of gear units	Unit
Driver included	Yes
Lighting Technology	LED
Value ladder	Performance
CE mark	Yes
Warranty period	5 years
Flammability mark	For mounting on normally flammable surfaces
ENEC mark	ENEC mark
Glow-wire test	Temperature 650 °C, duration 30 s
EU RoHS compliant	Yes

Light Technical	
Luminous Flux	3,600 lm
Saturated Red (R9)	<50
Correlated Colour Temperature	4000 K
Luminous efficacy (rated) (nom.)	125 lm/W
Colour rendering index (CRI)	≥80
Flickering value (PstLM)	1
Stroboscopic effect	0.4
Light source colour	840 neutral white
Optic type	Beam angle 90°
Luminaire light beam spread	90°
Unified Glare Rating (CEN)	19

CoreLine panel

Operating and Electrical

Input Voltage	220–240 V
Line Frequency	50 or 60 Hz
Inrush current	18.3 A
Inrush time	0.276 ms
Power Consumption	28.5 W
Power Factor (Fraction)	0.9
Connection	Push-in connector 5-pole
Cable	–
Number of products on MCB of 16 A type B	14

Temperature

Ambient temperature range	–10 to +40 °C
---------------------------	---------------

Controls and Dimming

Dimmable	Yes
Driver/power unit/transformer	Power supply unit with DALI interface
Control interface	DALI
Constant light output	No

Mechanical and Housing

Housing material	Steel
Reflector material	Acrylate
Optic material	Polystyrene
Optical cover/lens material	Acrylate
Fixation material	–
Housing Colour	White
Optical cover/lens finish	Microprismatic lens
Overall length	595 mm
Overall width	595 mm
Overall height	67 mm
Dimensions (height x width x depth)	67 x 595 x 595 mm

Approval and Application

Ingress protection code	IP20/44 [Finger-protected; wire-protected, splash-proof]
Mech. impact protection code	IK03 [0.3 J]

Sustainability rating	–
Protection class IEC	Safety class II
Photobiological risk	Photobiological risk group 0 @200mm to EN62778
Photobiological risk specification	0.2 m

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	(0.38, 0.38) SDCM≤3
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life	5 %
50,000 h	
Lumen maintenance at median useful life*	L90
50,000 h	
Lumen maintenance at median useful life*	L80
100,000 h	



Application Conditions

Performance ambient temperature Tq	25 °C
Maximum dim level	3%
Suitable for random switching	Yes

Product Data

Order product name	RC132V G5 36S/840 PSD W60L60 OC
Full product name	RC132V G5 36S/840 PSD W60L60 OC
Full EOC	871951495009200
Order code	95009200
Material no. (12 NC)	911401841584
SAP numerator – quantity per pack	1
EAN/UPC – Product/Case	8719514950092
Numerator – packs per outer box	1
EAN/UPC – Case	8719514950092

Dimensional drawing



CoreLine panel

