PHILIPS Lighting



T8 Standard

F32T8/TL850/ALTO 30PK

Philips T8 lamps are energy-efficient lighting solutions.

Product data

Cap-Base	G13 [Medium Bi-Pin Fluorescent]
•	
Features	ALTO® (ALTO)
Flux measurement reference	Sphere
Life to 50% Failures (Nom)	24,000 hour(s)
Light Technical	
Color Code	850 [CCT of 5000K]
Beam Angle (Nom)	0 degree(s)
Luminous Flux	2,880 lm
Color Designation	TL850
Chromaticity Coordinate X (Nom)	347
Chromaticity Coordinate Y (Nom)	362
Correlated Color Temperature (Nom)	5000 K
Color rendering index (CRI)	≥80
Operating and Electrical	
Power Consumption	32 W
Lamp Current (Nom)	265 mA
Wattage Equivalent	32 W
Voltage (Nom)	137 V
Voltage (Nom)	137 V
Controls and Dimming	
Dimmable	Yes

Mechanical and Housing	
Bulb Finish	Coated glass
Bulb Shape	T-8 (T8)
Approval and Application	
Energy Saving Product	Energy Saving
Mercury (Hg) Content (Max)	1.7 mg
Mercury (Hg) Content (Nom)	1.7 mg
Energy Consumption kWh/1000 h	32.6 kWh
Product Data	
Order product name	F32T8/TL850/ALTO 30PK
Full product name	F32T8/TL850/ALTO 30PK
Order code	927803785005
Material Nr. (12NC)	927803785005
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677582074
Numerator - Packs per outer box	30
EAN/UPC - Case	50046677582079

Dimensional drawing

Product	C (max)	D (max)
F32T8/TL850/ALTO 30PK	1,213.6 mm	27.9 mm





© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, December 2 - data subject to change