



# **MASTER LEDspot LV**

### MASTER LED 6.5-50W 930 MR16 10D Dim

Delivering intense accent beam, MASTER LEDspot LV is an ideal retrofit solution for spot lighting. MASTER LEDspot LV is designed to replace halogen or incandescent spots. It realizes natural colors, enables cozy and comfortable ambience for residential, hospitality and emphasizes the beauty of merchandise in retail. New smaller housing provides perfect fitting with majority of luminaires in a market with a MR16 GU 5.3 holder. It not only employs Philips' patented solution to guarantee the broadest possible compatibility with standard 12V halogen electronic transformers, it also delivers high beam intensity which is equivalent to halogen MR16 spots. The dimming function enables to create the desired atmosphere and it works with broad selection of dimmers. Its high SDCM ensure stricter color consistency, that is maintained over product life. MASTER LEDspot LV delivers huge energy savings and minimizes maintenance cost without any compromise on light quality and lifetime, enabling residential and business owners to achieve a return on their investment within short period time.

#### **Product data**

General Information	
Cap-Base	GU5.3
Nominal lifetime	40,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
EU RoHS compliant	Yes
Light Technical	
Color Code	930 [CCT of 3000K]
Beam Angle (Nom)	10 degree(s)
Luminous Flux	500 lm
Luminous Intensity (Nom)	5,300 cd
Color Designation	White (WH)

Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	76.00 lm/W
Color Consistency	<4
Color rendering index (CRI)	90
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Line Frequency	- Hz
Input Frequency	- Hz
Power Consumption	6.5 W
Lamp Current (Nom)	650 mA
Wattage Equivalent	50 W
Starting Time (Nom)	0.5 s


Datasheet, 2024, March 12 data subject to change

## **MASTER LEDspot LV**

Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.7
Voltage (Nom)	ac electronic 12 V
Temperature	
T-Case Maximum (Nom)	90 ℃
Controls and Dimming	
Dimmable	Only with specific dimmers
Mechanical and Housing	
Bulb Shape	MR16
Approval and Application	
Suitable For Accent Lighting	Yes


Product Data	
Order product name	MASTER LED 6.5-50W 930 MR16 10D Dim
Full product name	MASTER LED 6.5-50W 930 MR16 10D Dim
Full product code	871951435771600
Order code	929003071708
Material Nr. (12NC)	929003071708
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514357716
Numerator - Packs per outer box	10
EAN/UPC - Case	8719514357723
	<u> </u>

## Dimensional drawing




Product	D	С
MASTER LED 6.5-50W 930 MR16 10D Dim	50 mm	46.5 mm

## Photometric data








Light Distribution Diagram - MASTER LED 6.5-50W 930 MR16 10D Dim

## **MASTER LEDspot LV**


#### Photometric data




Calculus Photographics 4.5 Philips Lighting B.V. Rigot IV

Accent Lighting Spots - MASTER LED 6.5-50W 930 MR16 10D Dim

#### Lifetime





Life Expectancy Diagram - MASTER LED 6.5-50W 930 MR16 10D Dim

Lumen Maintenance Diagram - MASTER LED 6.5-50W 930 MR16 10D Dim



© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.