

PHILIPS

Compatibility List Professional Q3 2026

Philips CorePro LED PLC/PLL/PLT

Table of contents

Philips CorePro LED PLC

Philips CorePro LED PLC 5.5W 4P G24q-1	2
Philips CorePro LED PLC 6.5W 4P G24q-2	3
Philips CorePro LED PLC 6.5W 4P G24q-2	4
Philips CorePro LED PLC 9.5W 4P G24q-3	5

Philips CorePro LED PLC 3CCT

Philips CorePro LED PLC 360D 5.5W 3CCT 4P G24q-1	7
Philips CorePro LED PLC 360D 6.5W 3CCT 4P G24q-2	8
Philips CorePro LED PLC 360D 9.5W 3CCT 4P G24q-3	9

Philips CorePro LED PLL

Philips CorePro LED PLL HF 8W 4P 2G11	10
Philips CorePro LED PLL HF 12W 4P 2G11	12
Philips CorePro LED PLL HF 16.5 W 4P 2G11	14
Philips CorePro LED PLL HF 24 W 4P 2G11	16
Philips CorePro LED PLL HF/Mains 8W 4P 2G11	18
Philips CorePro LED PLL HF/Mains 12W 4P 2G11	20
Philips CorePro LED PLL HF/Mains 16.5W 4P 2G11	22
Philips CorePro LED PLL HF/Mains 24W 4P 2G11	24

Philips CorePro LED PLT

Philips CorePro LED PLT HF 6.5W 4P GX24q-2	25
Philips CorePro LED PLT HF 9W 4P GX24q-2	26
Philips CorePro LED PLT HF 15W 4P GX24q-2	28
Philips CorePro LED PLT HF 18.5W 4P GX24q-2	29
Philips CorePro LED PLT HF/Mains 6.5W 4P GX24Q-2	30
Philips CorePro LED PLT HF/Mains 9W 4P GX24Q-3	31
Philips CorePro LED PLT HF/Mains 13.5W 4P GX24Q-3	33
Philips CorePro LED PLT HF/Mains 16W 4P GX24Q-4	34

Q3 2026

Philips CorePro LED PLC 5.5W 4P G24q-1

Ballast compatibility

Key

	Ballast is compatible.
*	Ballast is compatible. Light output may differ >10% compared to specifications.
**	Ballast is compatible. Light output may differ >10% compared to specifications.
	Ballast is not compatible.

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions.

	Ballast type	12nc	Lamps on ballast	Philips CorePro LED PLC 5.5W 4P G24q-1 Model number / EOC code: 9290037576A / 8720169290419 9290037577A / 8720169290433 AC (50 Hz) on HF Ballast Compatible
PHILIPS	HF-M 113 TL/PLS/PLC SH	913700413766	1	
	HF-M 113 TL/PLS/PLC LH	913700413966	1	
	BLUE 114 LH TL/PLS/PLC	913700421766	1	
	RED 114 SH TL/TL5/PL-C/S	913700423266	1	
	HF-P 1 13-17 PL-T/C/R EII	913700631166	1	
	HF-P 2 13-17 PL-T/C/R EII	913700631266	2	
	EB-C 113 PL-T/C 220	913713198466	1	
	EB-C 213 PL-T/C 220	913713198566	2	
	HF-M 114 TL/PLS/PLC LH	913700417066	1	
	BLUE 124 SH TL/TL5/PLL	913700417966	1	
	HF-P 113 PL-C 220-240	913700129866	1	
OSRAM	QT-ECO 1X4-16/220-240 L		1	
	QT-ECO 1X4-16/220-240 S		1	*
	QTP-D/E 1X10-13		1	
	QTP-D/E 2X10-13		2	
	QT-ECO 2X5-11/220-240 S		2	
VOSSLOH-SCHWABE	ELXc 213.870	188698	2	
	ELXc 213.870	188698	1	*
	ELXs 121.901	188663	1	**
	ELXs 121.904	188663	1	***
TRIDONIC ATCO	PCA 1x11/13 TC EXCEL one4all	22185134	1	
	PCA 1x11/13 TC ECO	22185126	1	
	PCA 2x11/13 TC EXCEL one4all	22185135	2	
	PCA 2x11/13 TC ECO	22185127	2	
	PC 1x5-16W BASIC	24138830	1	**
	PC 1x5-16W BASIC sl	24138833	1	**
	PC 1/2x9-13 TC PRO	22176405	1	
	PC 1/2x9-13 TC PRO	22176405	2	
BAG HUECO	BCD13.1-2Q-01/220-240/1-10V	10096393	2	*
	BCD13.1-2Q-01/220-240/1-10V	10096393	1	**
	BCS21.1-2LS-01/220-240	10095043	2	*
	BCS21.1-2LS-01/220-240	10095043	1	*
	BCS21.1-2QI-01/220-240	10095743	2	*
	BCS21.1-2QI-01/220-240	10095743	1	*
	EBS21.1C-01/220-240	10050990	1	*
	EBS21.1M-01/220-240	10050994	1	**
	EBS16.1C-01/220-240	10050989	1	*
TCI	BCC 121	137946HTC	1	*
	BCC 121/2	137969/21MM	1	**
	BCC 121/2 SL	137944/21H	1	**
	BCC 121 SL	137944B/21H	1	*
	BCC 121 IP54	137969IP21MM	1	*
	MBQ 113/2	137968/113	1	
	MB213	137988/213	2	**
	MB213/2	137988/2132	2	**
	MBQ 213/2	137968/213	2	
	BCC 116	137945HTC	1	**
Others	Direct mains 220-240 ACV			

Philips CorePro LED PLC

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.
Please note that Philips CorePro LED PLC 4P are only tested with HF ballast on AC operation. The performance of Philips CorePro LED PLC 4P on HF ballasts with DC operation is not tested and is therefore not guaranteed.
Philips CorePro LED PLC 4P range is designed to work on HF ballasts only. For EM ballasts configuration, please contact a Philips sales representative for more information on our EM compatible range.
This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips CorePro LED PLC 4P with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips CorePro LED PLC 4P. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube.

Dimming: Philips CorePro LED PLC 4P are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply.

Q3 2026

Philips CorePro LED PLC 6.5W 4P G24q-2

Ballast compatibility

Key

	Ballast is compatible.
*	Ballast is compatible. Light output may differ >10% compared to specifications.
**	Ballast is compatible. Light output may differ >10% compared to specifications.
	Ballast is not compatible.

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions.

	Ballast type	12nc	Lamps on ballast	Philips CorePro LED PLC 6.5W 4P G24q-2 Model number / EOC code: 9290037578A / 8720169290457 9290037579A / 8720169290471 AC (50 Hz) on HF Ballast Compatible
PHILIPS	HF-P 118 PL-T/C III	913700648566	1	
	HF-P 1/218 PL-T/C III	913700648666	1	
	HF-P 218 PL-T/C III 220-240V 50/60Hz	913700648666	2	
	HF-M RED 118 SH PLC/PL-T 230-240V	913700423466	1	**
	HF-S 218 PL-T/C II SR	913713035866	2	
	HF-S 1/218 PL-T/C II SR 220-240V 50/60Hz	913713035866	1	
	HF-S 118 PL-T/C II SR 220-240V 50/60Hz	913713035966	1	
	HF-P 218 PL-T/C 220-240	913700155366	2	
	HF-P 118 PL-T/C EII	913700630966	1	
	HF-P 218 PL-T/C EII	913700631066	2	
	EB-C 118 PL-T/C 220-240	913713198666	1	
	EB-C 218 PL-T/C 220	913713198766	2	
	HF-R 218 PL-T/C EII	913700680166	2	
	HF-R 118 PL-T/C EII	913700680066	1	
	HF-R TD 218 PL-T/C EII 220-240V 50/60Hz	913700625966	2	
	HF-R TD 118 PL-T/C EII 220-240V 50/60Hz	913700626066	1	
	HF-R 118 PL-T/C 220-240	913700126066	1	
	HF-P 1/218 PL-T/C III	9137 006 48666	2	
	HF-P 118 PL-T/C 220-240	913700110466	1	
	HF-R 218 PL-T/C 220-240	913700605066	2	
	EB-S 218 PLT/C 220-240	913710065366	2	
	HF-S 1/218 PL-T/C II SR 220-240V 50/60Hz	913713035866	2	
OSRAM	QTP-T/E 1X18, 2X18	A72031900DG	1	
	QTP-T/E 1X18, 2X18	A72031900DG	2	
	QT-ECO T/E 2X18/220-240	A72924F00DG	2	
	QTP-T/E 2x18	A57063200DG	2	
	QT-D/E 1x18/230-240		1	
	EZ-T/E 1x18/220-240	AA403390155	1	
	EZ-T/E 2x18/220-240	AA403450155	2	
	QT-ECO 1X18-21 /220-240s	A4896310255	1	
	Qti-T/E 2x18-42 DIM	AA3945305BS	2	
HELVAR	EL1/2x18TCs		1	
	EL1/2x18TCs		2	
	EL1/2x18-42TCs		1	
	EL1/2x18-42TCs		2	
TRIDONIC ATCO	PC 1/2x18 TC PRO sr	22176416	1	*
	PC 1/2x18 TC PRO sr	22176416	2	*
	PC 1x18 TC TOP	28000073	1	
	PC 2x18 TC TOP	28000074	2	
	PC 1/2x18 TC PRO	22176407	1	*
	PC 1/2x18 TC PRO	22176407	2	*
	PC PRO 18 FSQ b101	22082606	1	**
	PC 1X18-24W BASIC sl	22176000	1	
	PC 2X18 TC TOP sr	28000078	2	
BAG HUECO	BCS18.1-2Q-01 / 220-240	10097544	1	*
	BCS18.1-2Q-01 / 220-240	10097544	2	
	BCS18.1-2LS-01 / 220-240	10095044	1	**
	BCS18.1-2LS-01 / 220-240	10095044	2	*

Q3 2026

Philips CorePro LED PLC 6.5W 4P G24q-2

Ballast compatibility

Key

	Ballast is compatible.
*	Ballast is compatible. Light output may differ >10% compared to specifications.
**	Ballast is compatible. Light output may differ >10% compared to specifications.
	Ballast is not compatible.

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions.

	Ballast type	12nc	Lamps on ballast	Philips CorePro LED PLC 6.5W 4P G24q-2 Model number / EOC code: 9290037578A / 8720169290457 9290037579A / 8720169290471 AC (50 Hz) on HF Ballast Compatible
VOSSLOH - SCHWABE	ELXs 121.901	188663	1	
	ELXS 121.904	188664	1	
	ELXC 218.871	188699	1	**
	ELXC 218.871	188699	2	*
	ELXC 142.872	188700	1	
	ELXC 142.872	188700	2	
	ELXc 242.837	188643	1	
TCI	MBQ 118/2	137968/118	1	
	MBQ 218/2	137968/218	2	
	BCC 121	137946HTC	1	
ELT	BE 218-TC-5	NA	1	
	BE 218-TC-5	NA	2	
Others	Direct mains 220-240 ACV			

Philips CorePro LED PLC

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.
Please note that Philips CorePro LED PLC 4P are only tested with HF ballast on AC operation. The performance of Philips CorePro LED PLC 4P on HF ballasts with DC operation is not tested and is therefore not guaranteed.
Philips CorePro LED PLC 4P range is designed to work on HF ballasts only. For EM ballasts configuration, please contact a Philips sales representative for more information on our EM compatible range.
This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips CorePro LED PLC 4P with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips CorePro LED PLC 4P. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube.

Dimming: Philips CorePro LED PLC 4P are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply.

Q3 2026

Philips CorePro LED PLC 9.5W 4P G24q-3

Ballast compatibility

Key

	Ballast is compatible.
*	Ballast is compatible. Light output may differ >10% compared to specifications.
**	Ballast is compatible. Light output may differ >10% compared to specifications.
***	Compatible for version June 2012 onwards
(1)	Ballast Do not use in closed luminaires
	Ballast is not compatible.

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions.

	Ballast type	12nc	Lamps on ballast	Philips CorePro LED PLC 9.5W 4P G24q-3 Model number / EOC code: 9290037580A / 8720169290495 9290037581A / 8720169290518 AC (50 Hz) on HF Ballast Compatible
PHILIPS	HF-P 226 PL-T/C III	913700648866	2	*
	HF-P 126 PL-T/C III	913700648766	1	*
	HF-P 1 22-42 PL-T/C/L/T5C EII	913700630766	1	
	HF-P 2 22-42 PL-T/C/L/TL5C EII	913700630866	2	*** (1)
	HF-S 226 PL-T/C II SR	913713035666	2	
	HF-S 226 PL-T/C/L/TL5C II SR	913713035666	2	
	HF-S 126 PL-T/C/L/TL5C II SR	913713035766	1	
	HF-P 2 26-42 PL-T/C 220-240	913700195066	2	
	EB-C 126 PL-T/C 220-240V 50/60Hz	913713198866	1	
	EB-C 226 PL-T/C 220	913713198966	2	
	HF-P 1/226 PL-T/C III 220-240V 50/60Hz	913700648866	1	
	HF-P 1/226 PL-T/C III 220-240V 50/60Hz	913700648866	2	
	HF-S 1/2 26 PL-T/C II SR 220-240V 50/60Hz	913713035666	1	
	HF-S 1/2 26 PL-T/C II SR 220-240V 50/60Hz	913713035666	2	
	HF-R 1 26-42 PL-T/C EII	913700626666	1	
	HF-Ri TD 2 26-42 PL-T/C E+	913700684866	2	
	HF-Ri TD 1 26-42 PL-T/C E+	913700684766	1	
	HF-R TD 1 26-42 PL-T/C EII 220-240	913700625866	1	
	HF-P 126 PL-T/C 220-240	913700110066	1	
	HFP 226 (Philips Luminaires)	441134730331	2	
	EB-P 126 PLT/C ICC 220-240V 50/60Hz	913710065466	1	*
	HF-P 1 26-42 PL-T/C	913700193266	1	
OSRAM	QTP-M 1X26-42	A6979600455	1	
	QTP-M 2x26-32	A6979950455 69799501DG	2	
	QTP-M 2x26-32	A6979950455 69799501DG	1	
	QT-M 2x26-42/220-240 S	A526/5500DG	2	
	QTP-T/E 1X26-42,2X26	A72032500DG	2	
	QTP-T/E 1x26-42, 2x26	A72032500DG	1	
	QT-ECO T/E 2X26/220-240	A53702300DG	2	
	QT-ECO 1X26/220...240 S	A48946102DG	1	
	QT-T/E 2x26/230-240		2	
	QT-M 1x26-42/220-240 S	A48989E00DG	1	
	EZ-T/E 1X26/220-240	AA403410155	1	
	Qti-T/E 2x18-42 DIM	AA39453 05BS	2	
	QT DALI-T/E 2x26-42/230-240 DIM		2	
	EZ-T/E 2x26/220-240	AA403470155	2	
VOSSLOH-SCHWABE	ELXc 142.872	188700	2	(1)
	ELXc 142.872	188700	1	
	ELXc 242.837	188643	2	(1)
	ELXs 126.906	188667	1	
	CBC-226142	540426	2	
	ELXc 142.876	188888	1	*
	ELXc 142.876	188888	2	(1)
	ELXc 242.877	188889	2	(1)

Q3 2026

Philips CorePro LED PLC 9.5W 4P G24q-3

Ballast compatibility

Key

	Ballast is compatible.
*	Ballast is compatible. Light output may differ >10% compared to specifications.
**	Ballast is compatible. Light output may differ >10% compared to specifications.
(1)	Ballast Do not use in closed luminaires
	Ballast is not compatible.

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions.

				Philips CorePro LED PLC 9.5W 4P G24q-3
				Model number / EOC code: 9290037580A / 8720169290495 9290037581A / 8720169290518
	Ballast type	**12nc**	**Lamps on ballast**	**AC (50 Hz) on HF Ballast Compatible**
TRIDONIC ATCO	PC 1/2x26 TC PRO sr	22176417	1	*
	PC 1/2x26 TC PRO sr	22176417	2	**
	PC 1/2 x 26-42 TC PRO	22176408	1	*
	PC 1/2 x 26-42 TC PRO	22176408	2	*
	PC 2x26-42 TC PRO	22176410	2	*
	PC 1x26-42 TC TOP	28000075	1	
	PC 2x26 TC TOP	28000076	2	(1)
BAG HUECO	BCS42.1/26.2LS-01/220-240	10095045	1	
	BCS42.1/26.2LS-01/220-240	10095045	2	
	BCS42.1/26.2QI-01/220-240	10095745	1	
	BCS42.1/26.2QI-01/220-240	10095745	2	
	BCS70.1/42.2Q-01/220-240	10097546	1	
	BCS70.1/42.2Q-01/220-240	10097546	2	
	BCS42.1Q-01/220-240	10097535	1	
	BCD57.1/32.2Q-01/220-240/DALI	10096397	1	
	BCD57.1/32.2Q-01/220-240/DALI	10096397	2	
	BCS42.1/26.2Q-01/220-240	10097545	1	
	BCS42.1/26.2Q-01/220-240	10097545	2	
HELVAR	EL1/2x18-42TCs		1	
	EL1/2x18-42TCs		1	
	EL2X32/42TCS		2	*
TCI	MBQ 226/2	137968/226	2	
	MBQ 142/2	137968/142	1	** (1)
	MBQ 242/2	137962/242	1	** (1)
	MBQ 242/2	137962/242	2	
	BCC 126.	137949HTC	1	** (1)
	MB226/2	137989Tc	2	(1)
HUCO	EVG-HP 1x/2x 15-42W HC	97545	1	
	EVG-HP 1x/2x 15-42W HC	97545	2	
OTHER	Direct mains 220-240 ACV			

Philips CorePro LED PLC

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.
Please note that Philips CorePro LED PLC 4P are only tested with HF ballast on AC operation. The performance of Philips CorePro LED PLC 4P on HF ballasts with DC operation is not tested and is therefore not guaranteed.
Philips CorePro LED PLC 4P range is designed to work on HF ballasts only. For EM ballasts configuration, please contact a Philips sales representative for more information on our EM compatible range.
This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips CorePro LED PLC 4P with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips CorePro LED PLC 4P. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube.

Dimming: Philips CorePro LED PLC 4P are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply.

Q3 2026

Philips CorePro LED PLC 360D 5.5W 3CCT 4P G24q-1

Ballast compatibility

Key

	Ballast is compatible.
*	Ballast is compatible. Light output may differ >10% compared to specifications.
**	Ballast is compatible. Light output may differ >20% compared to specifications.
(1)	Ballast Do not use in closed luminaires
Dim	Ballast is compatible and conditional released for dimming
	Ballast is not compatible.

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions.

	Ballast type	12nc	Lamps on ballast	CorePro LED PLC 360D 5.5W 3CCT 4P G24q-1 Model number / EOC code: 9290044321 / 8721103147523 AC (50 Hz) on HF Ballast Compatible
PHILIPS	BLUE 114 LH TL/PLS/PLC	913700421766	1	
	RED 114 SH TL/TL5/PLC/S	913700423266	1	
OSRAM	QT-ECO 1X4-16/220-240 S	A48976F0355	1	
	QTP-D/E 1X10-13	A69794802OL	1	
	QTP-D/E 2X10-13	A69797D02OL	2	
VOSSLOH-SCHWABE	ELXc 213.870	188698	2	
	ELXc 213.870	188698	1	
	ELXs 121.901	188663	1	
	ELXs 121.904	188664	1	
TRIDONIC	PCA 1x11/13 TC ECO	22185126	1	
	PC 1x5-16W BASIC	24138830	1	
	PC 1x5-16W BASIC sl	24138833	1	
BAG HUECO	BCS21.1-2Q-01/220-240	10097543	2	
	BCS21.1-2Q-01/220-240	10097543	1	
	EBS21.1M-01/220-240	10050994	1	
TCI	BCC 121	137946HTC	1	
	BCC 121/2 SL	137944/21H	1	
	BCC 121 SL	137944B/21H	1	
	MBQ 113/2	137968/113	1	
	MBQ 213/2	137968/213	2	
Others	Direct mains			
	Electro Magnetic Ballast			

Philips CorePro LED PLC

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.
Please note that Philips CorePro LED PLC 4P are only tested with HF ballast on AC operation. The performance of Philips CorePro LED PLC 4P on HF ballasts with DC operation is not tested and is therefore not guaranteed.
Philips CorePro LED PLC 4P range is designed to work on HF ballasts only. For EM ballasts configuration, please contact a Philips sales representative for more information on our EM compatible range.
This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips CorePro LED PLC 4P with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips CorePro LED PLC 4P. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube.

Dimming: Philips CorePro LED PLC 4P are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply.

Q3 2026

Philips CorePro LED PLC 360D 6.5W 3CCT 4P G24q-2

Ballast compatibility

Key

	Ballast is compatible.
*	Ballast is compatible. Light output may differ >10% compared to specifications.
**	Ballast is compatible. Light output may differ >20% compared to specifications.
(1)	Ballast Do not use in closed luminaires
Dim	Ballast is compatible and conditional released for dimming
	Ballast is not compatible.

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions.

				CorePro LED PLC 360D 6.5W 3CCT 4P G24q-2
				Model number / EOC code: 9290044322 / 8721103147547
	Ballast type	**12nc**	**Lamps on ballast**	**AC (50 Hz) on HF Ballast Compatible**
PHILIPS	HF-P 1 18 PL-T/C III	913700648566	1	
	HF-P 1/2 18 PL-T/C III	913700648666	1	
	HF-P 118 PL-L 220-240	913700116966	1	
	HF-P 2 18 PL-T/C EII	913700631066	2	
	HF-P 2 18 PL-T/C III	913700648666	2	
	HF-R 118 PL-T/C EII	913700680066	1	
	HF-R 118 TLD 220-240	913700111866	1	
	HF-R 218 PL-T/C EII	913700680166	2	
	HF-S 1/2 18 PL-T/C II SR	913713035866	1	
	HF-S 1/2 18 PL-T/C II SR	913713035866	2	
	HF-S 118 PL-T/C II SR	913713035966	1	
OSRAM	EZ-T/E 1x18/220-240	AA403390155 01506	1	
	QT-ECO 1X18-21 /220-240s	A48963101DG	1	
	QTP-T/E 1x18, 2x18	A72031902OL	1	
	QTP-T/E 1x18, 2x18	A72031902OL	2	
	QTP-T/E 2X18	A69798900DG	2	
	QT-T/E 2x18/230-240V	A69798900DG	2	
VOSSLOH-SCHWABE	ELXs 121.901	188663	1	
	ELXs 121.904	188664	1	
TCI	BCC 121	137946HTC	1	
	MBQ 118/2	137968/118	1	
Others	Direct mains			
	Electro Magnetic Ballast			

Philips CorePro LED PLC

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.
Please note that Philips CorePro LED PLC 4P are only tested with HF ballast on AC operation. The performance of Philips CorePro LED PLC 4P on HF ballasts with DC operation is not tested and is therefore not guaranteed.
Philips CorePro LED PLC 4P range is designed to work on HF ballasts only. For EM ballasts configuration, please contact a Philips sales representative for more information on our EM compatible range.
This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips CorePro LED PLC 4P with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips CorePro LED PLC 4P. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube.

Dimming: Philips CorePro LED PLC 4P are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply.

Philips CorePro LED PLC 360D 9.5W 3CCT 4P G24q-3

Ballast compatibility

Key

	Ballast is compatible.
*	Ballast is compatible. Light output may differ >10% compared to specifications.
**	Ballast is compatible. Light output may differ >20% compared to specifications.
(1)	Ballast Do not use in closed luminaires
Dim	Ballast is compatible and conditional released for dimming
	Ballast is not compatible.

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions.

	Ballast type	12nc	Lamps on ballast	CorePro LED PLC 360D 9.5W 3CCT 4P G24q-3 Model number / EOC code: 9290044323 / 8721103147561 AC (50 Hz) on HF Ballast Compatible
PHILIPS	HF-P122-42PL-T/C/L/TL5CEII	913700630766	1	
	HF-P1/226PL-T/CIII	9137006488(L4011)	1	
	HF-P1/226PL-T/CIII	9137006488(L4011)	2	
	HF-P126PL-T/CIII	913700648766	1	
	HF-P222-42PL-T/C/L/TL5CEII	913700630866	2	
	HF-R126-42PL-T/CEII	913700626666	1	
	HF-R226-42PL-T/CEII	913700626566	1	
	HF-R226-42PL-T/CEII	913700626566	2	
	HF-RiTD126-42PL-T/CE+	913700684766	1	
	HF-RiTD226-42PL-T/CE+	913700684866	2	
	HF-S1/226PL-T/CIISR	913713035666	1	
	HF-S1/226PL-T/CIISR	9137130C12:C23356	2	
OSRAM	EZ-T/E1X26/220-240	AA40341015501548	1	
	QT-ECO1X26/220-240S	A48946103550101903	1	
	QT-ECO2X26/220-240	A37107601DG	2	
	QT-M2x26-32/230-240S	A45115100DG	2	
	QT-M2x26-42/220-240S	A52675503550101836	2	
	QTP-M1x26-42	A69796004550401844	1	
	QTP-M2x26-32	A69799504550101839	2	
	QTP-T/E1x26-42,2x26	A72032503550301838	2	
	QTP-T/E1x26-42,2x26	A72032503550301838	1	
VOSSLOH-SCHWABE	ELXc126.880	183135	1	
	ELXc126.906	188667	1	
	ELXc142.872	188714	1	
	ELXc142.872	188714	2	
	ELXc142.876	188888	1	
	ELXc142.876	188888	2	
	ELXc242.877	188889	2	
HELVAR	EL1/2X18-42Tcs	4219001K471114577	1	
	EL1/2X18-42Tcs	4219001K471114577	2	
	EL2X32/42TCs	4218001G37701664	2	
TCI	BCC126	137949HTC	1	
	MBQ142/2	137968/142	1	
	MBQ226/2	137968/226	1	
	MBQ226/2	137968/226	2	
	MBQ242/2	137962/242	1	
	MBQ242/2	137962/242	2	
Others	Direct mains			
	Electro Magnetic Ballast			

Philips CorePro LED PLC

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.
Please note that Philips CorePro LED PLC 4P are only tested with HF ballast on AC operation. The performance of Philips CorePro LED PLC 4P on HF ballasts with DC operation is not tested and is therefore not guaranteed.
Philips CorePro LED PLC 4P range is designed to work on HF ballasts only. For EM ballasts configuration, please contact a Philips sales representative for more information on our EM compatible range.
This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips CorePro LED PLC 4P with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips CorePro LED PLC 4P. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube.

Dimming: Philips CorePro LED PLC 4P are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply.

Q3 2026

Philips CorePro LED PLL HF 8W 4P 2G11

Ballast compatibility

Key

	Ballast is compatible.
*	Ballast is compatible. Light output may differ >10% compared to specifications.
**	Ballast is compatible. Light output may differ >10% compared to specifications.
(1)	Ballast Do not use in closed luminaires
	Ballast is not compatible.

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions.

	Ballast type	12nc	Lamps on ballast	CorePro LED PLL HF 8W 4P 2G11 Model number / EOC code: 9290035788 / 8719514486768 9290035789 / 8719514486782 AC (50 Hz) on HF Ballast Compatible
PHILIPS	HF-Performer 1 22-42 PL-T/C/L/TL5C EII 220-240V	913700630766	1	
	HF-Performer 2 22-42 PL-T/C/L/TL5C EII 220-240V	913700630866	2	
	HF-Pi 1 14/21/24/39 TL5 EII 220-240	913700624066	1	
	HF-Pi 2 14/21/24/39 TL5 EII 220-240	913700624266	2	
	HF-Pi 3/4 14/24 TL5/PLL EII	913700657666	4	
	HF-Pi 3/4 14/24 TL5/PLL EII	913700657666	3	
	HF-MATCHBOX BLUE 124 LH TL/TL5/PLL	913700418066	1	* (1)
	HF-MATCHBOX BLUE 124 SH TL/TL5/PLL	913700417966	1	* (1)
	HF-MATCHBOX RED 124 SH TL/TL5/PLL	913700420666	1	*
	HF-P 1 18-24 PL-L	913700193166	1	
OSRAM	QT-ECO 1x18-24/220-240 S		1	
	QT-FIT8 1x18		1	**
	QT-M 1x26-42/230-240 S		1	*
	QTP-M 1X26-42		1	
	QTP-M 2X26-32		2	
	QTP-OPTIMAL 1x18-40		1	*
	QTP-OPTIMAL 2x18-40		2	*
TRIDONIC	PC 1/2x26-42 TC PRO	22176408	2	*
	PC 1/2x26-42 TC PRO	22176408	1	*
	PC 1x18-24W BASIC sl	22176000	1	**
	PC 2x26-42 TC PRO	22176410	2	
	PC 2/14-21/24/39 T5 PRO-M lp	22176185	2	**
VOSSLOH	ELXc 142.872	188700	2	
	ELXc 142.872	188700	1	*
	ELXc 142.876	188888	2	
	ELXc 142.876	188888	1	*
	ELXc 242.837	188643	2	
	ELXc 242.877	188889	2	*
BAG-HUECO	BCS39.1FX-11/220-240	1007 7581	1	*
	BCS39.2FX-11/220-240	1007 7582	2	
	BCS42.1/26.2LS-01/220-240	1009 5045	2	
	BCS42.1/26.2LS-01/220-240	1009 5045	1	*
	BCS42.1/26.2Q-01/220-240	1009 7545	2	
	BCS42.1/26.2Q-01/220-240	1009 7545	1	
	BCS42.1/26.2QI-01/220-240	1009 5745	2	
	BCS42.1/26.2QI-01/220-240	1009 5745	1	*
	BCS42.1Q-01/220-240	1009 7535	1	
	MLS14/24.3-4.FR-11/220-240	1009 5345	4	
	MLS14/24.3-4.FR-11/220-240	1009 5345	3	
	MLS39.1-2FR-11/220-240	10092026	2	** (1)
	MLS39.1-2FR-11/220-240	10092026	1	** (1)

Q3 2026

Philips CorePro LED PLL HF 8W 4P 2G11

Ballast compatibility

Key

	Ballast is compatible.
*	Ballast is compatible. Light output may differ >10% compared to specifications.
**	Ballast is compatible. Light output may differ >10% compared to specifications.
(1)	Ballast Do not use in closed luminaires
	Ballast is not compatible.

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions.

				CorePro LED PLL HF 8W 4P 2G11
				Model number / EOC code: 9290035788 / 8719514486768 9290035789 / 8719514486782
	Ballast type	**12nc**	**Lamps on ballast**	**AC (50 Hz) on HF Ballast Compatible**
TCI	BCC 124	137947HTC	1	**
	BCC 124 SL	137944B/24H	1	**
	BCC 124/2	137969/24MM	1	**
	BCC 124/2 SL	137944H	1	**
	MBQ 224/2	137968/224	2	**
	BTL8 118	137963/118	1	**
	MB 226/2	137989TC	2	
HELVAR	EL1x36/40/18s		1	*
	EL1/2x18-42TCs		2	
	EL1/2x18-42TCs		1	*
HUCO	EVG-HP 1x/2x 15-42W HC	097545	2	
	EVG-HP 1x/2x 15-42W HC	097545	1	*
OTHERS	Direct mains			
	Electro Magnetic Ballast			

Philips CorePro LED PLL

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.
Please note that Philips CorePro LED PLL 4P are only tested with HF ballast on AC operation. The performance of Philips CorePro LED PLL 4P on HF ballasts with DC operation is not tested and is therefore not guaranteed.
Philips CorePro LED PLL 4P range is designed to work on HF ballasts only. For EM ballasts configuration, please contact a Philips sales representative for more information on our EM compatible range.
This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips CorePro LED PLL 4P with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips CorePro LED PLL 4P. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube.

Dimming: Philips CorePro LED PLL 4P are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply.

Q3 2026

Philips CorePro LED PLL HF 12W 4P 2G11

Ballast compatibility

Key

	Ballast is compatible.
*	Ballast is compatible. Light output may differ >10% compared to specifications.
**	Ballast is compatible. Light output may differ >10% compared to specifications.
(1)	Ballast Do not use in closed luminaires
	Ballast is not compatible.

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions.

	Ballast type	12nc	Lamps on ballast	CorePro LED PLL HF 12W 4P 2G11 Model number / EOC code: 9290035790 / 8719514486805 9290035791 / 8719514486829 AC (50 Hz) on HF Ballast Compatible
PHILIPS	HF-Performer 1 22-42 PL-T/C/L/TL5C EII 220-240V	913700630766	1	
	HF-Performer 2 22-42 PL-T/C/L/TL5C EII 220-240V	913700630866	2	
	HF-Pi 1 14/21/24/39 TL5 EII 220-240	913700624066	1	
	HF-Pi 2 14/21/24/39 TL5 EII 220-240	913700624266	2	
	HF-Pi 3/4 14/24 TL5/PLL EII	913700657666	4	
	HF-Pi 3/4 14/24 TL5/PLL EII	913700657666	3	
	HF-MATCHBOX BLUE 124 LH TL/TL5/PLL	913700418066	1	* (1)
	HF-MATCHBOX BLUE 124 SH TL/TL5/PLL	913700417966	1	* (1)
	HF-MATCHBOX RED 124 SH TL/TL5/PLL	913700420666	1	*
	HF-P 1 18-24 PL-L	913700193166	1	
OSRAM	QT-ECO 1x18-24/220-240 S		1	
	QT-M 1x26-42/230-240 S		1	*
	QT-M 2x26-42/220-240 S		2	*
	QTP-M 1X26-42		1	
	QTP-M 2X26-32		2	*
	QT-T/E 2x26/230-240		2	
	QTP-OPTIMAL 1x18-40		1	
	QTP-OPTIMAL 2x18-40		2	*
TRIDONIC	PC 1/2x26-42 TC PRO	22176408	2	*
	PC 1/2x26-42 TC PRO	22176408	1	*
	PC 1x18-24W BASIC sl	22176000	1	*
	PC 2x26-42 TC PRO	22176410	2	*
	PC 1x24 T5 TOP lp	22185159	1	
	PC 2x24 T5 TOP lp	22185160	2	
VOSSLOH	ELXc 142.872	188700	2	
	ELXc 142.872	188700	1	**
	ELXc 142.876	188888	2	
	ELXc 142.876	188888	1	**
	ELXc 242.837	188643	2	*
	ELXc 242.877	188889	2	*
	ELXc 128.869	188589	1	
	ELXc 126.906	188667	1	*
BAG-HUECO	BCS39.1FX-11/220-240	10077581	1	*
	BCS39.2FX-11/220-240	10077582	2	
	BCS42.1/26.2LS-01/220-240	10095045	2	
	BCS42.1/26.2LS-01/220-240	10095045	1	*
	BCS42.1/26.2Q-01/220-240	10097545	2	
	BCS42.1/26.2Q-01/220-240	10097545	1	*
	BCS42.1/26.2QI-01/220-240	10095745	2	
	BCS42.1/26.2QI-01/220-240	10095745	1	*
	BCS42.1Q-01/220-240	10097535	1	*
	MLS14/24.3-4.FR-11/220-240	10095345	4	
	MLS14/24.3-4.FR-11/220-240	10095345	3	*
	MLS39.1-2FR-11/220-240	10092026	2	** (1)
	MLS39.1-2FR-11/220-240	10092026	1	** (1)

Q3 2026

Philips CorePro LED PLL HF 12W 4P 2G11

Ballast compatibility

Key

	Ballast is compatible.
*	Ballast is compatible. Light output may differ >10% compared to specifications.
**	Ballast is compatible. Light output may differ >10% compared to specifications.
(1)	Ballast Do not use in closed luminaires
	Ballast is not compatible.

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions.

				CorePro LED PLL HF 12W 4P 2G11
				Model number / EOC code: 9290035790 / 8719514486805 9290035791 / 8719514486829
	Ballast type	**12nc**	**Lamps on ballast**	**AC (50 Hz) on HF Ballast Compatible**
TCI	BCC 124	137947HTC	1	**
	BCC 124 SL	137944B/24H	1	**
	BCC 124/2	137969/24MM	1	**
	BCC 124/2 SL	137944H	1	**
	MBQ 224/2	137968/224	2	*
	MB 226/2	137989TC	2	
	BCC 126	137949HTC	1	*
HELVAR	EL1/2x18-42TCs		2	
	EL1/2x18-42TCs		1	*
HUCO	EVG-HP 1x/2x 15-42W HC	097545	2	
	EVG-HP 1x/2x 15-42W HC	097545	1	*
OTHERS	Direct mains			
	Electro Magnetic Ballast			

Philips CorePro LED PLL

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.
Please note that Philips CorePro LED PLL 4P are only tested with HF ballast on AC operation. The performance of Philips CorePro LED PLL 4P on HF ballasts with DC operation is not tested and is therefore not guaranteed.
Philips CorePro LED PLL 4P range is designed to work on HF ballasts only. For EM ballasts configuration, please contact a Philips sales representative for more information on our EM compatible range.
This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips CorePro LED PLL 4P with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips CorePro LED PLL 4P. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube.

Dimming: Philips CorePro LED PLL 4P are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply.

Q3 2026

Philips CorePro LED PLL HF 16.5 W 4P 2G11

Ballast compatibility

Key

	Ballast is compatible.
*	Ballast is compatible. Light output may differ >10% compared to specifications.
Dim	Ballast is compatible and conditional released for dimming
	Ballast is not compatible.

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions.

	Ballast type	12nc	Lamps on ballast	CorePro LED PLL HF 16.5W 4P 2G11 Model number / EOC code: 9290013815 / 871869673966200 9290013816 / 871869673974700 9290013817 / 871869673976100 AC (50 Hz) on HF Ballast Compatible
PHILIPS	HF-P 136 TL-D III 220-240V 50/60Hz IDC	913713031566	1	
	HF-P 236 TL-D III 220-240V 50/60Hz IDC	913713031666	2	
	HF-S 136 TL-D II 220-240V 50/60Hz	913713032166	1	
	HF-S 236 TL-D II 220-240V 50/60Hz	913713032466	2	
	HF-E 136 TL-D II 220-240 50/60Hz	913713041066	1	
	HF-E 236 TL-D II 220-240 50/60Hz	913713041166	2	
	HF-S 336 TL-D II 220-240V 50/60Hz	913713032766	3	
	HF-Pi 1 14/21/24/39 TL5 EII 220-240V	913700624066	1	
	HF-Pi 2 14/21/24/39 TL5 EII 220-240V	913700624266	2	
	HF-P 136 PLL EII 220-240V 50/60Hz	913700192066	1	
	HF-P 236 PLL EII 220-240V 50/60Hz	913700192366	2	
	HF-P 136 PLL III 220-240V 50/60Hz	913713028466	1	
	HF-P 236 PLL III 220-240V 50/60Hz	913713028566	2	
	HF-P 136 PLL 220-240	913700114566	1	
	HF-R 236 TL-D EII 220-240V 50/60Hz	913700609366	2	*
	HF-Regulator 236 PLL EII 220-240V 50/60Hz	913700620066	2	*
	HF-R 136 PLL 220-240	913700115666	1	*
	HF-R 236 PLL 220-240	913700115766	2	*
	HF-Ri TD I 14/21/24/39 TL5 E+	913700698366	1	*
	HF-B 136 TLD 220-240	913700112266	1	
	HF-B 136 TLD EII 220-240	913700192666	1	
	HF-B 236 TLD EII 220-240	913700192866	2	
OSRAM	Qti 1x14/24/21/39 GII		1	
	Qti 2x14/24/21/39 GII		2	
	QT-M 2x26-42/220-240 S		2	
	QTP-DL 1x36-40		1	
	QTP-DL 2x36-40		2	
	QTP-M 1x26-42		1	
	QTP-M 2x26-32		2	
	QTP-OPTIMAL 2x18-40		2	
	Quictronic QT 1x36/230		1	
	QT-M 1x26-42/230-240 S		1	
	QT-M 2x26-32/230-240 S		2	
HELVAR	EL1x39/36ngn5		1	
	EL2x39/36ngn5		2	
	EL2x39/36s		2	
	EL1/2x36/38TCs - Single		1	
	EL1/2x36/38TCs - Single		1	
	EL1/2x18-42TCs - Single		1	
VOSSLOH-SCHWABE	ELXc 140.862	188140	1	
	ELXc 240.863	188616	2	
	ELXc 142.872	188700	1	
	ELXc 242.837	188643	2	
	ELXc 236.208	188705	2	
	ELXc 142.876	188888	1	
	ELXc 242.877	188889	2	
TRIDONIC	PC 1/36 TCL PRO	22176141	1	
	PC 2/36 TCL PRO	22176170	2	
	PC 3/36 T8 PRO	22176231	3	
	PC 1/14-35/24/39 T5 PRO-M lp	22176182	1	
	PC 2/14-21/24/39 T5 PRO-M lp	22176185	2	
	PC 1x36 T8 TEC	87500258	1	
	PC 2x36 T8 TEC	87500259	2	
	PC 2x36/4x18 T8 TEC	87500260	2	
	PCA 2/36 TCL ECO	22085516	2	

Q3 2026

Philips CorePro LED PLL HF 16.5 W 4P 2G11

Ballast compatibility

Key

	Ballast is compatible.
*	Ballast is compatible. Light output may differ >10% compared to specifications.
Dim	Ballast is compatible and conditional released for dimming
	Ballast is not compatible.

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions.

				CorePro LED PLL HF 16.5W 4P 2G11
				Model number / EOC code: 9290013815 / 871869673966200 9290013816 / 871869673974700 9290013817 / 871869673976100
	Ballast type	**12nc**	**Lamps on ballast**	**AC (50 Hz) on HF Ballast Compatible**
BAG-HUECO	BCS38.1LS-01/220-240	10097427	1	*
	BCS38.1Q-01/220-240	10097437	1	
	BCS39.1FX-11/220-240	10077581	2	
	BCS42.1Q-01/220-240	10097535	1	
	MLS39.1-2FR-11/220-240 - Single	10092026	1	*
	MLS39.1-2FR-11/220-240 - Single	10092026	2	*
	BCS39.2FX-11/220-240	10077582	1	
	D58.1-23021 E	166072	1	
	BCS36.1SR-01/220-240	10051000	2	
Trilux	D58.1-23021 E		1	
OTHERS	Direct mains			
	Electro Magnetic Ballast			

Philips CorePro LED PLL

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.
Please note that Philips CorePro LED PLL 4P are only tested with HF ballast on AC operation. The performance of Philips CorePro LED PLL 4P on HF ballasts with DC operation is not tested and is therefore not guaranteed.
Philips CorePro LED PLL 4P range is designed to work on HF ballasts only. For EM ballasts configuration, please contact a Philips sales representative for more information on our EM compatible range.
This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips CorePro LED PLL 4P with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips CorePro LED PLL 4P. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube.

Dimming: Philips CorePro LED PLL 4P are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply.

Q3 2026

Philips CorePro LED PLL HF 24 W 4P 2G11

Ballast compatibility

Key

	Ballast is compatible.
*	Ballast is compatible. Light output may differ >10% compared to specifications.
Dim	Ballast is compatible and conditional released for dimming
	Ballast is not compatible.

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions.

	Ballast type	12nc	Lamps on ballast	CorePro LED PLL HF 24W 4P 2G11 Model number / EOC code: 9290019204 / 871869682839700 9290019205 / 871869682841000 9290019206 / 871869682843400 AC (50 Hz) on HF Ballast Compatible
PHILIPS	HF-E 1/2 54 TL5 II 220-240 50/60Hz	913713040866	1	
	HF-E 1/2 54 TL5 II 220-240 50/60Hz	913713040866	2	*
	HF-E 1/2 58 TL-D II 220-240 50/60Hz	913713040966	1	
	HF-E 1/2 58 TL-D II 220-240 50/60Hz	913713040966	2	
	HF-P 158 TL-D III 220-240V 50/60Hz IDC	913713031866	1	
	HF-P 158 TL-D III 220-240V 50/60Hz IDC UBA 2013T	913713031866	1	
	HF-P 258 TL-D III 220-240V 50/60Hz IDC	913713031966	2	
	HF-P 154/155 TL5 HO/PL-L III IDC	913713028266	1	
	HF-P 254/255 TL5 HO/PL-L III IDC	913713028366	2	
	HF-S 154 TL5 II 220-240V 50/60Hz	913713033666	1	*
	HF-S 254 TL5 II 220-240V 50/60Hz	913713033766	2	
	HF-S 158 TL-D II 220-240V 50/60Hz	913713032266	1	*
	HF-S 258 TL-D II 220-240V 50/60Hz	913713032566	2	*
	HF-S 258 TL-D II HT 220-240V 50/60Hz	913700689966	2	
	HF-B 158 TLD EII 220-240	913700192766	1	
	HF-B 258 TLD EII 220-240	91370092966	2	
	HF-Pi 1 28/35/49/54 TL5 EII 220-240V	913700624166	1	*
	HF-Pi 2 28/35/49/54 TL5 EII 220-240V	913700624366	2	*
	HF-P 155 PLL EII 220-240 50/60Hz	913700192266	1	
	HF-P 255 PLL EII 220-240V 50/60Hz	913700192566	2	
	HF-P 255 PLL EII 220-240 50/60Hz	913700651366	2	
	HF-P 155 PLL III IDC 220-240V 50/60Hz	913713028866	1	
	HF-P 155 PLL 220-240	913700121866	1	
	HF-P 255 PLL 220-240	913700115066	2	
OSRAM	QT-FQ 2x80		2	
	Qti 1x35/49/80 GII		1	
	Qti 2x35/49/80 GII		2	
	QTP-DL 2x55 GII		2	*
	QTP-DL 1x55 GII		1	
	QTP-DL 2x55		2	*
	QTP-FC 1x55		1	
	QT 2x55 / 230		2	
	QTP-OPTIMAL 1x54-58		1	
	QTP-OPTIMAL 2x54-58		2	
HELVAR	EL1x55ngn5		1	
	EL2x55ngn5		2	
	EL1x55s		2	*
	EL2x55s		1	*
VOSS-LOH-SCHWABE	ELXc 180.866	188144	1	*
	ELXc 254.865	188618	2	
	ELXc 280.538	188619	2	*
	ELXc 155.378	188680	1	*
TRIDONIC	PC 1x80 T5 PRO lp	22185209	1	*
	PC 2x55 TCL PRO lp	22185286	2	*
	PC 1/55 TCL PRO	22176169	1	
	PC 2/55 TCL PRO	22176233	2	
	PC 1/14-35/49/80 T5 PRO-M lp	22176184	1	
	PC 1x58 T8 PRO lp	22185215	1	
	PC 2x58 T8 PRO sl	22185218	2	
	PC 1x58 T8 TEC	87500150	1	*
	PC 2x58 T8 TEC	87500151	2	

Q3 2026

Philips CorePro LED PLL HF 24 W 4P 2G11

Ballast compatibility

Key

	Ballast is compatible.
*	Ballast is compatible. Light output may differ >10% compared to specifications.
Dim	Ballast is compatible and conditional released for dimming
	Ballast is not compatible.

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions.

				CorePro LED PLL HF 24W 4P 2G11
				Model number / EOC code: 9290019204 / 871869682839700 9290019205 / 871869682841000 9290019206 / 871869682843400
	Ballast type	**12nc**	**Lamps on ballast**	**AC (50 Hz) on HF Ballast Compatible**
BAG-HUECO	BCS54.1FX-11/220-240	10077585	1	*
	BCS55.1Q-01/220-240/T5C	10097634	1	
	BCS54.2FX-11/220-240	10077586	2	*
	MLS80.1/54.2FR-11/220-240	10071609	1	
	MLS80.1/54.2FR-11/220-240	10071609	2	
	BCS54.1FR-01/220/240	10075881	1	
	D58.1-23021 E	166072	1	
	D58.2-23021 E	166082	2	
	BCS58.1SR-01/220-240	10051002	1	
Trilux	D58.1-23021 E		1	
TCI	BTLT 154	137998/154	1	
	BTLT 254	137999/54	2	*
OTHERS	Direct mains			
	Electro Magnetic Ballast			

Philips CorePro LED PLL

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.
Please note that Philips CorePro LED PLL 4P are only tested with HF ballast on AC operation. The performance of Philips CorePro LED PLL 4P on HF ballasts with DC operation is not tested and is therefore not guaranteed.
Philips CorePro LED PLL 4P range is designed to work on HF ballasts only. For EM ballasts configuration, please contact a Philips sales representative for more information on our EM compatible range.
This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips CorePro LED PLL 4P with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips CorePro LED PLL 4P. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube.

Dimming: Philips CorePro LED PLL 4P are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply.

Q3 2026

Philips CorePro LED PLL HF/Mains 8W 4P 2G11

Ballast compatibility

Key

	Ballast is compatible.
*	Ballast is compatible. Light output may differ >10% compared to specifications.
**	Ballast is compatible. Light output may differ >10% compared to specifications.
(1)	Ballast Do not use in closed luminaires
	Ballast is not compatible.

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions.

	Ballast type	12nc	Lamps on ballast	CorePro LED PLL HF/Mains 8W 4P 2G11 Model number / EOC code: 9290042674 / 872110305087800 9290042675 / 872110305089200 AC (50 Hz) on HF Ballast Compatible
PHILIPS	HF-Performer 1 22-42 PL-T/C/L/TL5C EII 220-240V	913700630766	1	
	HF-Performer 2 22-42 PL-T/C/L/TL5C EII 220-240V	913700630866	2	
	HF-Pi 1 14/21/24/39 TL5 EII 220-240	913700624066	1	
	HF-Pi 2 14/21/24/39 TL5 EII 220-240	913700624266	2	
	HF-Pi 3/4 14/24 TL5/PLL EII	913700657666	4	
	HF-Pi 3/4 14/24 TL5/PLL EII	913700657666	3	
	HF-MATCHBOX BLUE 124 LH TL/TL5/PLL	913700418066	1	
	HF-MATCHBOX BLUE 124 SH TL/TL5/PLL	913700417966	1	
	HF-MATCHBOX RED 124 SH TL/TL5/PLL	913700420666	1	
	HF-P 1 18-24 PL-L	913700193166	1	
	EB-S 1 24 TL/PL SH	913710028366	1	
OSRAM	QT-ECO 1x18-24/220-240 S		1	
	QT-FIT8 1x18		1	*
	QT-M 1x26-42/230-240 S		1	
	QTP-M 1X26-42		1	
	QTP-M 2X26-32		2	
	QTP-OPTIMAL 1x18-40		1	
	QTP-OPTIMAL 2x18-40		2	*
HELVAR	EL1x36/40/18s		1	*
	EL1/2x18-42TCs	4219001K47206984	2	
	EL1/2x18-42TCs	4219001K47206984	1	
	EL1/2x18-42TCs	4219001Q09604620	1	
	EL1/2x18-42TCs	4219001Q09604620	2	
VOSSLOH	ELXc 142.872	188700	2	
	ELXc 142.872	188700	1	*
	ELXc 142.876	188888	2	
	ELXc 142.876	188888	1	*
	ELXc 242.837	188643	2	
	ELXc 242.877	188889	2	
TRIDONIC	PC 1/2x26-42 TC PRO	22176408	2	*
	PC 1/2x26-42 TC PRO	22176408	1	*
	PC 1x18-24W BASIC sl	22176000	1	
	PC 2x26-42 TC PRO	22176410	2	*
	PC 2/14-21/24/39 T5 PRO-M lp	22176185	2	
	PC 1/14-35/24/39 T5 PRO-M lp	22176182	1	
	PC 2x36/4x18 T8 TEC	87500260	4	
BAG-HUECO	BCS39.1FX-11/220-240	10077581	1	*
	BCS39.2FX-11/220-240	10077582	2	
	BCS42.1/26.2LS-01/220-240	10095045	2	
	BCS42.1/26.2LS-01/220-240	10095045	1	*
	BCS42.1/26.2Q-01/220-240	10097545	2	
	BCS42.1/26.2Q-01/220-240	10097545	1	
	BCS42.1/26.2QI-01/220-240	10095745	2	
	BCS42.1/26.2QI-01/220-240	10095745	1	*
	BCS42.1Q-01/220-240	10097535	1	
	MLS14/24.3-4.FR-11/220-240	10095345	4	*
	MLS14/24.3-4.FR-11/220-240	10095345	3	
	MLS39.1-2FR-11/220-240	10092026	2	**
	MLS39.1-2FR-11/220-240	10092026	1	**
	BCD57.1/32.2Q-01/220-240/DALI	10096397	1	*
	BCD57.1/32.2Q-01/220-240/DALI	10096397	2	*

Q3 2026

Philips CorePro LED PLL HF/Mains 8W 4P 2G11

Ballast compatibility

Key

	Ballast is compatible.
*	Ballast is compatible. Light output may differ >10% compared to specifications.
**	Ballast is compatible. Light output may differ >10% compared to specifications.
(1)	Ballast Do not use in closed luminaires
	Ballast is not compatible.

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions.

	Ballast type	12nc	Lamps on ballast	CorePro LED PLL HF/Mains 8W 4P 2G11 Model number / EOC code: 9290042674 / 872110305087800 9290042675 / 872110305089200 AC (50 Hz) on HF Ballast Compatible
TCI	BCC 124	137947HTC	1	**(1)
	BCC 124/2	137969/24MM	1	**(1)
	BCC 124/2 SL	137944H	1	**(1)
	MBQ 224/2	137968/224	2	*
	BTL8 118	137963/118	1	*
	MB 226/2	137989TC	2	
HUCO	EVG-HP 1x/2x 15-42W HC	097545	2	
	EVG-HP 1x/2x 15-42W HC	097545	1	
OTHER	Direct mains			
	Electro Magnetic Ballast			

Philips CorePro LED PLL

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.
Please note that Philips CorePro LED PLL 4P are only tested with HF ballast on AC operation. The performance of Philips CorePro LED PLL 4P on HF ballasts with DC operation is not tested and is therefore not guaranteed.
Philips CorePro LED PLL 4P range is designed to work on HF ballasts only. For EM ballasts configuration, please contact a Philips sales representative for more information on our EM compatible range.
This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips CorePro LED PLL 4P with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips CorePro LED PLL 4P. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube.

Dimming: Philips CorePro LED PLL 4P are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply.

Q3 2026

Philips CorePro LED PLL HF/Mains 12W 4P 2G11

Ballast compatibility

Key

	Ballast is compatible.
*	Ballast is compatible. Light output may differ >10% compared to specifications.
**	Ballast is compatible. Light output may differ >10% compared to specifications.
	Ballast is not compatible.

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions.

	Ballast type	12nc	Lamps on ballast	CorePro LED PLL HF/Mains 12W 4P 2G11 Model number / EOC code: 9290042676 / 872110305091500 9290042677 / 872110305093900 AC (50 Hz) on HF Ballast Compatible
PHILIPS	HF-Performer 1 22-42 PL-T/C/L/TL5C EII 220-240V	913700630766	1	
	HF-Performer 2 22-42 PL-T/C/L/TL5C EII 220-240V	913700630866	2	
	HF-Pi 1 14/21/24/39 TL5 EII 220-240	913700624066	1	*
	HF-Pi 2 14/21/24/39 TL5 EII 220-240	913700624266	2	*
	HF-Pi 3/4 14/24 TL5/PLL EII	913700657666	4	
	HF-Pi 3/4 14/24 TL5/PLL EII	913700657666	3	
	HF-MATCHBOX BLUE 124 LH TL/TL5/PLL	913700418066	1	
	HF-MATCHBOX BLUE 124 SH TL/TL5/PLL	913700417966	1	
	HF-MATCHBOX RED 124 SH TL/TL5/PLL	913700420666	1	
	HF-P 1 18-24 PL-L	913700193166	1	
	EB-S 1 24 TL/PL SH	913710028366	1	
	HF-Ri TD 2 14/21/24/39 TL5 E+	913700698466	2	
OSRAM	QT-ECO 1x18-24/220-240 S		1	
	QT-M 1x26-42/230-240 S		1	
	QT-M 2x26-42/220-240 S		2	
	QTP-M 1X26-42		1	
	QTP-M 2X26-32		2	
	QT-T/E 2x26/230-240		2	
	QTP-OPTIMAL 1x18-40		1	
	QTP-OPTIMAL 2x18-40		2	
HELVAR	EL1/2x18-42TCs	4219001K47206984	2	
	EL1/2x18-42TCs	4219001K47206984	1	
	EL1/2x18-42TCs	4219001Q09604620	1	
	EL1/2x18-42TCs	4219001Q09604620	2	
VOSSLOH	ELXc 142.872	188700	2	
	ELXc 142.872	188700	1	*
	ELXc 142.876	188888	2	
	ELXc 142.876	188888	1	*
	ELXc 242.837	188643	2	
	ELXc 242.877	188889	2	
	ELXc 128.869	188589	1	*
	ELXc 126.906	188667	1	
TRIDONIC	PC 1/2x26-42 TC PRO	22176408	2	**
	PC 1/2x26-42 TC PRO	22176408	1	**
	PC 1/2x26-42 TC PRO sr	22176417	1	**
	PC 1/2x26-42 TC PRO sr	22176417	2	**
	PC 1x18-24W BASIC sl	22176000	1	
	PC 2x26-42 TC PRO	22176410	2	**
	PC 2/14-21/24/39 T5 PRO-M lp	22176185	2	
	PC 1/14-35/24/39 T5 PRO-M lp	22176182	1	

Philips CorePro LED PLL HF/Mains 12W 4P 2G11

Ballast compatibility

Key

	Ballast is compatible.
*	Ballast is compatible. Light output may differ >10% compared to specifications.
**	Ballast is compatible. Light output may differ >10% compared to specifications.
(1)	Ballast Do not use in closed luminaires
	Ballast is not compatible.

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions.

	Ballast type	12nc	Lamps on ballast	CorePro LED PLL HF/Mains 12W 4P 2G11 Model number / EOC code: 9290042676 / 872110305091500 9290042677 / 872110305093900 AC (50 Hz) on HF Ballast Compatible
BAG-HUECO	BCS39.1FX-11/220-240	10077581	1	*
	BCS39.2FX-11/220-240	10077582	2	
	BCS42.1/26.2LS-01/220-240	10095045	2	
	BCS42.1/26.2LS-01/220-240	10095045	1	*
	BCS42.1/26.2Q-01/220-240	10097545	2	
	BCS42.1/26.2Q-01/220-240	10097545	1	
	BCS42.1/26.2QI-01/220-240	10095745	2	
	BCS42.1/26.2QI-01/220-240	10095745	1	
	BCS42.1Q-01/220-240	10097535	1	
	MLS14/24.3-4.FR-11/220-240	10095345	4	
	MLS14/24.3-4.FR-11/220-240	10095345	3	
	MLS39.1-2FR-11/220-240	10092026	2	*
	MLS39.1-2FR-11/220-240	10092026	1	*
	BCD57.1/32.2Q-01/220-240/DALI	10096397	1	**
	BCD57.1/32.2Q-01/220-240/DALI	10096397	2	**
TCI	BCC 124	137947HTC	1	*(1)
	BCC 124/2	137969/24MM	1	**(1)
	BCC 124/2 SL	137944H	1	*(1)
	MBQ 224/2	137968/224	2	
	MB 226/2	137989TC	2	
	BCC 126	137949HTC	1	
HUCO	EVG-HP 1x/2x 15-42W HC	097545	2	
	EVG-HP 1x/2x 15-42W HC	097545	1	
OTHERS	Direct mains			
	Electro Magnetic Ballast			

Philips CorePro LED PLL

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.
Please note that Philips CorePro LED PLL 4P are only tested with HF ballast on AC operation. The performance of Philips CorePro LED PLL 4P on HF ballasts with DC operation is not tested and is therefore not guaranteed.
Philips CorePro LED PLL 4P range is designed to work on HF ballasts only. For EM ballasts configuration, please contact a Philips sales representative for more information on our EM compatible range.
This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips CorePro LED PLL 4P with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips CorePro LED PLL 4P. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube.

Dimming: Philips CorePro LED PLL 4P are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply.

Philips CorePro LED PLL HF/Mains 16.5W 4P 2G11

Ballast compatibility

Key

	Ballast is compatible.
*	Ballast is compatible. Light output may differ >10% compared to specifications.
**	Ballast is compatible. Light output may differ >10% compared to specifications.
	Ballast is not compatible.

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions.

	Ballast type	12nc	Lamps on ballast	CorePro LED PLL HF/Mains 16.5W 4P 2G11 Model number / EOC code: 9290042678 / 872110305095300 9290042679 / 872110305097700 AC (50 Hz) on HF Ballast Compatible
PHILIPS	HF-P 136 TL-D III 220-240V 50/60Hz IDC	913713031566	1	
	HF-P 236 TL-D III 220-240V 50/60Hz IDC	913713031666	2	
	HF-P 118/136 TL-D III 220-240V 50/60Hz	913713031566	1	
	HF-P 218/236 TL-D III 220-240V 50/60Hz	913713031666	2	
	HF-S 136 TL-D II 220-240V 50/60Hz	913713032166	1	
	HF-S 236 TL-D II 220-240V 50/60Hz	913713032466	2	
	HF-S 218/236 TL-D II 220-240V 50/60Hz	913713032466	2	
	HF-E 136 TL-D II 220-240 50/60Hz	913713041066	1	
	HF-E 236 TL-D II 220-240 50/60Hz	913713041166	2	
	HF-S 336 TL-D II 220-240V 50/60Hz	913713032766	3	*
	HF-Pi 1 14/21/24/39 TL5 EII 220-240V	913700624066	1	
	HF-Pi 2 14/21/24/39 TL5 EII 220-240V	913700624266	2	**
	HF-P 236 PLL EII 220-240V 50/60Hz	913700192366	2	
	HF-P 236 PL-L III IDC 220-240V 50/60Hz	913713028566	2	
	HF-P 136 PLL 220-240	913700114566	1	
	HF-R 136 TL-D EII 220-240V 50/60Hz	913700609266	1	
	HF-R 236 TL-D EII 220-240V 50/60Hz	913700609366	2	
	HF-Regulator 236 PLL EII 220-240V 50/60Hz	913700620066	2	**
	HF-R 136 PLL 220-240	913700115666	1	*
	HF-R 236 PLL 220-240	913700115766	2	*
	HF-Ri TD I 14/21/24/39 TL5 E+	913700698366	1	**
	HF-Ri TD 2 14/21/24/39 TL5 E+	913700698466	2	**
	HF-B 136 TLD 220-240	913700112266	1	*
	HF-B 136 TLD EII 220-240	913700192666	1	**
	HF-B 236 TLD EII 220-240	913700192866	2	
OSRAM	Qti 1x14/24/21/39 GII		1	
	Qti 2x14/24/21/39 GII		2	
	QT-M 2x26-42/220-240 S	A52675500DG	2	*
	QTP-DL 1x36-40		1	*
	QTP-DL 2x36-40		2	**
	QTP-M 1x26-42	A6979600455	1	
	QTP-M 2x26-32	A6979950455 A69799500DG	2	*
	QTP-OPTIMAL 1x18-40	AA5095703DG		
	QTP-OPTIMAL 2x18-40	AA517320755	2	**
	QT-M 1x26-42/230-240 S	A48989E00DG	1	*
HELVAR	EL1x39/36ngn5		1	
	EL2x39/36ngn5		2	
	EL2x39/36s		2	**
	EL1/2x36/38TCs - Single		1	
	EL1/2x36/38TCs - dual		2	
VOSSLOH	ELXc 140.862	188140	1	
	ELXc 240.863	188616	2	*
	ELXc 142.872	188700	1	
	ELXc 242.837	188643	2	
	ELXc 236.208	188705	2	*
	ELXc 142.876	188888	1	
	ELXc 242.877	188889	2	*

Q3 2026

Philips CorePro LED PLL HF/Mains 16.5W 4P 2G11

Ballast compatibility

Key

	Ballast is compatible.
*	Ballast is compatible. Light output may differ >10% compared to specifications.
**	Ballast is compatible. Light output may differ >10% compared to specifications.
	Ballast is not compatible.

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions.

	Ballast type	12nc	Lamps on ballast	CorePro LED PLL HF/Mains 16.5W 4P 2G11 Model number / EOC code: 9290042678 / 872110305095300 9290042679 / 872110305097700 AC (50 Hz) on HF Ballast Compatible
TRIDONIC	PC 1/36 TCL PRO	87500507	1	*
	PC 2/36 TCL PRO	87500518	2	**
	PC 3/36 T8 PRO	22176231	3	**
	PC 1/14-35/24/39 T5 PRO-M lp	22176182	1	
	PC 2/14-21/24/39 T5 PRO-M lp	22176185	2	*
	PC 2x36/4x18 T8 TEC	87500260	2	**
BAG-HUECO	BCS38.1Q-01/220-240	10097437	1	
	BCS39.1FX-11/220-240	10077581	1	
	BCS42.1Q-01/220-240	10097535	1	
	MLS39.1-2FR-11/220-240 - Single	10092026	1	**
	MLS39.1-2FR-11/220-240 - dual	10092026	2	**
	BCS39.2FX-11/220-240	10077582	2	
	D58.1-23021 E	166072	1	**
Trilux	D58.1-23021 E		1	**
OTHERS	Direct mains			
	Electro Magnetic Ballast			

Philips CorePro LED PLL

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.
Please note that Philips CorePro LED PLL 4P are only tested with HF ballast on AC operation. The performance of Philips CorePro LED PLL 4P on HF ballasts with DC operation is not tested and is therefore not guaranteed.
Philips CorePro LED PLL 4P range is designed to work on HF ballasts only. For EM ballasts configuration, please contact a Philips sales representative for more information on our EM compatible range.
This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips CorePro LED PLL 4P with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips CorePro LED PLL 4P. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube.

Dimming: Philips CorePro LED PLL 4P are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply.

Q3 2026

Philips CorePro LED PLL HF/Mains 24W 4P 2G11

Ballast compatibility

Key

	Ballast is compatible.
*	Ballast is compatible. Light output may differ >10% compared to specifications.
**	Ballast is compatible. Light output may differ >10% compared to specifications.
(1)	Ballast Do not use in closed luminaires
	Ballast is not compatible.

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions.

	Ballast type	12nc	Lamps on ballast	CorePro LED PLL HF/Mains 24W 4P 2G11 Model number / EOC code: 9290042680 / 872110305099100 9290042681 / 872110305101100 AC (50 Hz) on HF Ballast Compatible
PHILIPS	HF-E 1/2 58 TL-D II 220-240 50/60Hz	913713040966	1	
	HF-E 1/2 58 TL-D II 220-240 50/60Hz	913713040966	2	
	HF-P 158 TL-D III 220-240V 50/60Hz IDC	913713031866	1	
	HF-P 258 TL-D III 220-240V 50/60Hz IDC	913713031966	2	
	HF-P 154/155 TL5 HO/PL-L III IDC	913713028266	1	
	HF-P 254/255 TL5 HO/PL-L III IDC	913713028366	2	
	HF-S 154 TL5 II 220-240V 50/60Hz	913713033666	1	*
	HF-S 254 TL5 II 220-240V 50/60Hz	913713033766	2	
	HF-S 158 TL-D II 220-240V 50/60Hz	913713032266	1	
	HF-S 258 TL-D II 220-240V 50/60Hz	913713032566	2	
	HF-S 258 TL-D II HT 220-240V 50/60Hz	913700689966	2	
	HF-B 158 TLD 220-240	913700112366	1	
	HF-B 158 TLD EII 220-240	913700192766	1	
	HF-B 258 TLD EII 220-240	913700192966	2	
	HF-Pi 1 28/35/49/54 TL5 EII 220-240V	913700624166	1	*
	HF-Pi 2 28/35/49/54 TL5 EII 220-240V	913700624366	2	*
	HF-R 154 TL5 EII 220-240V 50/60Hz	913700608866	1	
	HF-R 254 TL5 EII 220-240V 50/60Hz	913700608966	2	
OSRAM	QT-FQ 2x80		2	**(1)
	Qti 1x35/49/80 GII		1	**
	Qti 2x35/49/80 GII		2	*
	QTP-DL 2x55 GII		2	*
	QTP-DL 1x55 GII		1	
	QTP-OPTIMAL 1x54-58		1	
	QTP-OPTIMAL 2x54-58		2	
HELVAR	EL1x55ngn5		1	
	EL2x55ngn5		2	
	EL1x55s		1	*
	EL2x55s		2	*
VOSSLOH	ELXc 180.866	188144	1	*
	ELXc 254.865	188618	2	
	ELXc 280.538	188619	2	
	ELXc 155.378	188680	1	*
TRIDONIC	PC 1x80 T5 PRO lp	22185209	1	*
	PC 2x55 TCL PRO lp	22185286	2	**
	PC 1/55 TCL PRO	22176169	1	
	PC 2/55 TCL PRO	22176233	2	
	PC 1/14-35/49/80 T5 PRO-M lp	22176184	1	
	PC 1x58 T8 PRO lp	22185215	1	
	PC 2x58 T8 PRO sl	22185218	2	
	PC 1x58 T8 TEC	87500150	1	**
	PC 2x58 T8 TEC	87500151	2	
	PC 2/58 T8 PRO	22176095	2	
BAG-HUECO	BCS54.1FX-11/220-240	10077585	1	*
	MLS80.1/54.2FR-11/220-240	10071609	1	*
	MLS80.1/54.2FR-11/220-240	10071609	2	
	BCS54.1FR-01/220/240	10075881	1	
	D58.1-23021 E	166072	1	
	D58.2-23021 E	166082	2	*
	BCS58.1SR-01/220-240	10051002	1	
Trilux	D58.1-23021 E		1	
TCI	BTLT 254	137999/54	2	
OTHERS	Direct mains			
	Electro Magnetic Ballast			

Philips CorePro LED PLL

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.
Please note that Philips CorePro LED PLL 4P are only tested with HF ballast on AC operation. The performance of Philips CorePro LED PLL 4P on HF ballasts with DC operation is not tested and is therefore not guaranteed.
Philips CorePro LED PLL 4P range is designed to work on HF ballasts only. For EM ballasts configuration, please contact a Philips sales representative for more information on our EM compatible range.
This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips CorePro LED PLL 4P with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips CorePro LED PLL 4P. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube.

Dimming: Philips CorePro LED PLL 4P are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply.

Philips CorePro LED PLT HF 6.5W 4P GX24q-2

Ballast compatibility

Key

	Ballast is compatible.
*	Ballast is compatible. Light output may differ >10% compared to specifications.
**	Ballast is compatible. Light output may differ >10% compared to specifications.
(1)	Ballast Do not use in closed luminaires
	Ballast is not compatible.

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions.

	Ballast type	12nc	Lamps on ballast	CorePro LED PLT HF 6.5W 4P GX24Q-2 Model number / EOC code: 9290035763 9290035764 AC (50 Hz) on HF Ballast Compatible
PHILIPS	EB-S 218 PLT/C 220-240	913710065366	2	
	HF-P 118 PL-T/C EII	913700630966	1	
	HF-P 118 PL-T/C III	913700648566	1	
	HF-M RED 118 SH PL-C/PL-T	913700423466	1	*
	HF-P 118 PL-T/C 220-240	913700110466	1	
	HF-P 1/218 PL-T/C III	913700648666	1	*
	HF-P 1/218 PL-T/C III	913700648666	2	*
	HF-P 218 PL-T/C EII	913700631066	2	
	HF-P 218 PL-T/C III 220-240V 50/60Hz	913700648666	2	*
	HF-P 218 PL-T/C 220-240	913700155366	2	
	HF-S 218 PL-T/C II SR	913713035866	2	*
	HF-S 1/218 PL-T/C II SR 220-240V 50/60Hz	913713035866	1	
	HF-S 1/218 PL-T/C II SR 220-240V 50/60Hz	913713035866	2	*
OSRAM	QTP-T/E 1X18, 2X18	A72031900DG	1	
	QTP-T/E 1X18, 2X18	A72031900DG	2	
	QTP-T/E 2x18	A57063200DG	2	
	QT-D/E 1x18/230-240		1	
	QT-ECO T/E 2X18/220-240	A72924F00DG	2	
TRIDONIC	PC 1x18 TC TOP	28000073	1	
	PC 2x18 TC TOP	28000074	2	
	PC 2X18 TC TOP sr	28000078	2	
	PC 1/2x18 TC PRO	22176407	1	
	PC 1/2x18 TC PRO	22176407	2	
	PC 1/2x18 TC PRO sr	22176416	1	
	PC 1/2x18 TC PRO sr	22176416	2	
	PC PRO 18 FSQ b101	22082606	1	*
	PC 1X18-24W BASIC sl	22176000	1	
VOSSLOH	ELXs 121.901	188663	1	*
	ELXs 121.904	188664	1	*
	ELXc 218.871	188699	1	*
	ELXc 218.871	188699	2	*
	ELXc 142.872	188700	1	**(1)
	ELXc 142.872	188700	2	**(1)
BAG-HUECO	BCS18.1-2LS-01 / 220-240	10095044	1	
	BCS18.1-2LS-01 / 220-240	10095044	2	
	BCS18.1-2Q-01 / 220-240	10097544	1	*
	BCS18.1-2Q-01 / 220-240	10097544	2	*
TCI	MBQ 118/2	137968/118	1	
	MBQ 218/2	137968/218	2	
	BCC 121	137946HTC	1	*
HELVAR	EL1/2x18TCs	4217001P30402078 8	1	
	EL1/2x18TCs	4217001P30402078 8	2	
OTHERS	BE 218-TC-5		1	
	BE 218-TC-5		2	*

Philips CorePro LED PLT

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.
Please note that Philips CorePro LED PLT 4P are only tested with HF ballast on AC operation. The performance of Philips CorePro LED PLT 4P on HF ballasts with DC operation is not tested and is therefore not guaranteed.
Philips CorePro LED PLT 4P range is designed to work on HF ballasts only. For EM ballasts configuration, please contact a Philips sales representative for more information on our EM compatible range.
This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips CorePro LED PLT 4P with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips CorePro LED PLT 4P. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube.

Dimming: Philips CorePro LED PLT 4P are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply.

Philips CorePro LED PLT HF 9W 4P GX24q-2

Ballast compatibility

Key

	Ballast is compatible.
*	Ballast is compatible. Light output may differ >10% compared to specifications.
**	Ballast is compatible. Light output may differ >10% compared to specifications.
(1)	Ballast Do not use in closed luminaires
	Ballast is not compatible.

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions.

	Ballast type	12nc	Lamps on ballast	CorePro LED PLT HF 9W 4P GX24Q-2 Model number / EOC code: 9290035765 9290035766 * / *
				AC (50 Hz) on HF Ballast Compatible
PHILIPS	HF-P 126 PL-T/C III	913700648766	1	
	HF-P 1 22-42 PL-T/C/L/T5C EI	913700630766	1	
	HF-P 1 26-42 PL-T/C	913700193266	1	
	HF-P 1/226 PL-T/C III 220-240V 50/60Hz	913700648866	1	
	HF-P 1/226 PL-T/C III 220-240V 50/60Hz	913700648866	2	*
	HF-P 226 PL-T/C III	913700648866	2	
	HF-P 2 22-42 PL-T/C/L/TL5C EII	913700630866	2	
	HF-P 2 26-42 PL-T/C 220-240	913700195066	2	**
	HFP 226 (Philips Luminaires)	441134730331	2	
	HF-S 226 PL-T/C/L/TL5C II SR	913713035666	2	
	HF-S 1/2 26 PL-T/C II SR 220-240V 50/60Hz	913713035666	1	
	HF-S 1/2 26 PL-T/C II SR 220-240V 50/60Hz	913713035666	2	*
	HF-S 226 PL-T/C II SR	913713035666	2	
OSRAM	QTP-M 1X26-42	A6979600455	1	
	QTP-M 2x26-32	A6979950455 A69799500DG	2	
	QTP-T/E 1x26-42, 2x26	A72032500DG	1	
	QTP-T/E 1X26-42,2X26	A72032500DG	2	
	QT-ECO 1X26/220…240 S	A48946102DG	1	
	QT-ECO T/E 2X26/220-240	A53702300DG	2	
	QT-M 2x26-42/220-240 S	A5267550355 A52675500DG	2	
	QT-T/E 2x26/230-240		2	
TRIDONIC	PC 1/2x26 TC PRO sr	22176417	1	
	PC 1/2x26 TC PRO sr	22176417	2	
	PC 1/2 x 26-42 TC PRO	22176408	1	
	PC 1/2 x 26-42 TC PRO	22176408	2	
	PC 1x26-42 TC TOP	28000075	1	
	PC 2x26 TC TOP	28000076	2	
	PC 2x26-42 TC PRO	22176410	2	
VOSSLOH	ELXs 126.906	188667	1	
	CBC-226142	540426	2	
	ELXc 142.872	188700	1	*
	ELXc 142.872	188700	2	
	ELXc 142.876	188888	1	
	ELXc 142.876	188888	2	
	ELXc 242.837	188643	2	*
	ELXc 242.877	188889	2	*

Q3 2026

Philips CorePro LED PLT HF 9W 4P GX24q-2

Ballast compatibility

Key

	Ballast is compatible.
*	Ballast is compatible. Light output may differ >10% compared to specifications.
**	Ballast is compatible. Light output may differ >10% compared to specifications.
(1)	Ballast Do not use in closed luminaires
	Ballast is not compatible.

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions.

				CorePro LED PLT HF 9W 4P GX24Q-2
				Model number / EOC code: 9290035765 9290035766 * / *
	Ballast type	**12nc**	**Lamps on ballast**	**AC (50 Hz) on HF Ballast Compatible**
BAG-HUECO	BCS42.1/26.2LS-01/220-240	10095045	1	
	BCS42.1/26.2LS-01/220-240	10095045	2	
	BCS42.1/26.2QI-01/220-240	10095745	1	
	BCS42.1/26.2QI-01/220-240	10095745	2	
	BCS70.1/42.2Q-01/220-240	10097546	1	
	BCS70.1/42.2Q-01/220-240	10097546	2	
	BCS42.1Q-01/220-240	10097535	1	
	BCS42.1/26.2Q-01/220-240	10097545	1	
	BCS42.1/26.2Q-01/220-240	10097545	2	
TCI	BCC 126.	137949HTC	1	
	MB226/2	137989Tc	2	
	MBQ 226/2	137968/226	2	
	MBQ 142/2	137968/142	1	**
	MBQ 242/2	137962/242	1	**
	MBQ 242/2	137962/242	2	**
HELVAR	EL1/2x18-42TCs	4219001Q09604620 1	1	
	EL1/2x18-42TCs	4219001Q09604620 1	2	
	EL2x32/42TCs	4218001K03102451 9	2	
HUCO	EVG-HP 1x/2x 15-42W HC	097545	1	
	EVG-HP 1x/2x 15-42W HC	097545	2	

Philips CorePro LED PLT

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.
Please note that Philips CorePro LED PLT 4P are only tested with HF ballast on AC operation. The performance of Philips CorePro LED PLT 4P on HF ballasts with DC operation is not tested and is therefore not guaranteed.
Philips CorePro LED PLT 4P range is designed to work on HF ballasts only. For EM ballasts configuration, please contact a Philips sales representative for more information on our EM compatible range.
This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips CorePro LED PLT 4P with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips CorePro LED PLT 4P. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube.

Dimming: Philips CorePro LED PLT 4P are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply.

Philips CorePro LED PLT HF 15W 4P GX24q-2

Ballast compatibility

Key

	Ballast is compatible.
*	Ballast is compatible. Light output may differ >10% compared to specifications.
**	Ballast is compatible. Light output may differ >10% compared to specifications.
(1)	Ballast Do not use in closed luminaires
	Ballast is not compatible.

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions.

	Ballast type	12nc	Lamps on ballast	CorePro LED PLT HF 15W 4P GX24Q-2 Model number / EOC code: 9290035767 9290035768 * / *
				AC (50 Hz) on HF Ballast Compatible
PHILIPS	HF-P 1 22-42 PL-T/C/L/T5C EI	913700630766	1	
	HF-P 1 26-42 PL-T/C	913700193266	1	
	HF-P 2 22-42 PL-T/C/L/TL5C EII	913700630866	2	
	HF-P 2 26-42 PL-T/C 220-240	913700195066	2	**
OSRAM	QTP-M 1X26-42	A6979600455	1	
	QTP-M 2x26-32	A6979950455 A69799500DG	2	
	QTP-T/E 1x26-42, 2x26	A72032500DG	1	
	QT-M 2x26-42/220-240 S	A5267550355	2	
TRIDONIC ATCO	PC 1/2x26 TC PRO sr	22176417	1	
	PC 1/2 x 26-42 TC PRO	22176408	1	
	PC 1x26-42 TC TOP	28000075	1	
	PC 2x26-42 TC PRO	22176410	2	
VOSSLOH	ELXc 142.872	188700	1	
	ELXc 142.876	188888	1	
	ELXc 242.837	188643	2	*
	ELXc 242.877	188889	2	
BAG-HUECO	BCS42.1/26.2LS-01/220-240	10095045	1	
	BCS42.1/26.2QI-01/220-240	10095745	1	
	BCS70.1/42.2Q-01/220-240	10097546	1	
	BCS70.1/42.2Q-01/220-240	10097546	2	
	BCS42.1Q-01/220-240	10097535	1	
	BCS42.1/26.2Q-01/220-240	10097545	1	
TCI	MBQ 142/2	137968/142	1	**
	MBQ 242/2	137962/242	1	**
	MBQ 242/2	137962/242	2	**
HEL-VAR	EL1/2x18-42TCs	4219001Q09604620 1	1	*
	EL2x32/42TCs	4218001K03102451 9	2	
HUCO	EVG-HP 1x/2x 15-42W HC	097545	1	

Philips CorePro LED PLT

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.
Please note that Philips CorePro LED PLT 4P are only tested with HF ballast on AC operation. The performance of Philips CorePro LED PLT 4P on HF ballasts with DC operation is not tested and is therefore not guaranteed.
Philips CorePro LED PLT 4P range is designed to work on HF ballasts only. For EM ballasts configuration, please contact a Philips sales representative for more information on our EM compatible range.
This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips CorePro LED PLT 4P with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips CorePro LED PLT 4P. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube.

Dimming: Philips CorePro LED PLT 4P are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply.

Philips CorePro LED PLT HF 18.5W 4P GX24q-2

Ballast compatibility

Key

	Ballast is compatible.
*	Ballast is compatible. Light output may differ >10% compared to specifications.
**	Ballast is compatible. Light output may differ >10% compared to specifications.
(1)	Ballast Do not use in closed luminaires
	Ballast is not compatible.

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions.

	Ballast type	12nc	Lamps on ballast	CorePro LED PLT HF 18.5W 4P GX24Q-2 Model number / EOC code: 9290035769 9290035770 * / *
				AC (50 Hz) on HF Ballast Compatible
PHILIPS	HF-P 1 22-42 PL-T/C/L/T5C EI	913700630766	1	
	HF-P 1 26-42 PL-T/C	913700193266	1	
	HF-P 2 22-42 PL-T/C/L/TL5C EII	913700630866	2	
	HF-P 2 26-42 PL-T/C 220-240	913700195066	2	**
OSRAM	QTP-M 1X26-42	A6979600455	1	
	QTP-M 2x26-32	A6979950455 A69799500DG	2	
	QTP-T/E 1x26-42, 2x26	A72032500DG	1	
	QT-M 2x26-42/220-240 S	A5267550355	2	
TRIDONIC ATCO	PC 1/2x26 TC PRO sr	22176417	1	
	PC 1/2 x 26-42 TC PRO	22176408	1	
	PC 1x26-42 TC TOP	28000075	1	
	PC 2x26-42 TC PRO	22176410	2	
VOSSLOH	ELXc 142.872	188700	1	**(1)
	ELXc 142.876	188888	1	
	ELXc 242.837	188643	2	
	ELXc 242.877	188889	2	
BAG-HUECO	BCS42.1/26.2LS-01/220-240	10095045	1	
	BCS42.1/26.2QI-01/220-240	10095745	1	
	BCS70.1/42.2Q-01/220-240	10097546	1	
	BCS70.1/42.2Q-01/220-240	10097546	2	
	BCS42.1Q-01/220-240	10097535	1	
	BCS42.1/26.2Q-01/220-240	10097545	1	
TCI	MBQ 142/2	137968/142	1	**(1)
	MBQ 242/2	137962/242	1	**(1)
	MBQ 242/2	137962/242	2	**(1)
HEL-VAR	EL1/2x18-42TCs	4219001Q09604620 1	1	*
	EL2x32/42TCs	4218001K03102451 9	2	
HUCO	EVG-HP 1x/2x 15-42W HC	097545	1	*

Philips CorePro LED PLT

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.
Please note that Philips CorePro LED PLT 4P are only tested with HF ballast on AC operation. The performance of Philips CorePro LED PLT 4P on HF ballasts with DC operation is not tested and is therefore not guaranteed.
Philips CorePro LED PLT 4P range is designed to work on HF ballasts only. For EM ballasts configuration, please contact a Philips sales representative for more information on our EM compatible range.
This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips CorePro LED PLT 4P with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips CorePro LED PLT 4P. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube.

Dimming: Philips CorePro LED PLT 4P are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply.

Philips CorePro LED PLT HF/Mains 6.5W 4P GX24Q-2

Ballast compatibility

Key

	Ballast is compatible.
*	Ballast is compatible. Light output may differ >10% compared to specifications.
**	Ballast is compatible. Light output may differ >10% compared to specifications.
(1)	Ballast Do not use in closed luminaires
	Ballast is not compatible.

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions.

	Ballast type	12nc	Lamps on ballast	CorePro LED PLT HF/Mains 6.5W 4P GX24Q-2 Model number / EOC code: 9290042666 / 872110304973500 9290042667 / 872110304975900 AC (50 Hz) on HF Ballast Compatible
PHILIPS	EB-S 218 PLT/C 220-240	913710065366	2	
	HF-P 118 PL-T/C EII	913700630966	1	
	HF-P 118 PL-T/C III	913700648566	1	
	HF-M RED 118 SH PL-C/PL-T	913700423466	1	**
	HF-P 118 PL-T/C 220-240	913700110466	1	
	HF-P 1/218 PL-T/C III	913700648666	1	*
	HF-P 1/218 PL-T/C III	913700648666	2	
	HF-P 218 PL-T/C EII	913700631066	2	
	HF-P 218 PL-T/C III 220-240V 50/60Hz	913700648666	2	
	HF-P 218 PL-T/C 220-240	913700155366	2	
	HF-S 118 PL-T/C II SR 220-240V 50/60Hz	913713035966	1	
	HF-S 218 PL-T/C II SR	913713035866	2	
	HF-S 1/218 PL-T/C II SR 220-240V 50/60Hz	913713035866	1	*
	HF-S 1/218 PL-T/C II SR 220-240V 50/60Hz	913713035866	2	
OSRAM	QTP-T/E 1X18, 2X18	A72031900DG	1	
	QTP-T/E 1X18, 2X18	A72031900DG	2	
	QTP-T/E 2x18	A57063200DG	2	
	QT-D/E 1x18/230-240		1	
	QT-ECO T/E 2X18/220-240	A72924F00DG	2	
TRIDONIC	PC 1x18 TC TOP	28000073	1	
	PC 2x18 TC TOP	28000074	2	
	PC 2X18 TC TOP sr	28000078	2	
	PC 1/2x18 TC PRO	22176407	1	*
	PC 1/2x18 TC PRO	22176407	2	*(1)
	PC 1/2x18 TC PRO sr	22176416	1	*
	PC 1/2x18 TC PRO sr	22176416	2	*
	PC PRO 18 FSQ b101	22082606	1	**
	PC 1X18-24W BASIC sl	22176000	1	
VOSSLOH	ELXs 121.901	188663	1	
	ELXs 121.904	188664	1	
	ELXc 218.871	188699	1	**
	ELXc 218.871	188699	2	*
	ELXc 142.872	188700	1	
	ELXc 142.872	188700	2	
BAG-HUECO	BCS18.1-2LS-01 / 220-240	10095044	1	**
	BCS18.1-2LS-01 / 220-240	10095044	2	*
	BCS18.1-2Q-01 / 220-240	10097544	1	*
	BCS18.1-2Q-01 / 220-240	10097544	2	
TCI	MBQ 118/2	137968/118	1	
	MBQ 218/2	137968/218	2	
	BCC 121	137946HTC	1	
HELVAR	EL1/2x18TCs	4217001P30402078 8	1	
	EL1/2x18TCs	4217001P30402078 8	2	*
ELT	BE 218-TC-5		1	
	BE 218-TC-5		2	
OTHERS	Direct mains			
	Electro Magnetic Ballast			

Philips CorePro LED PLT

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.
Please note that Philips CorePro LED PLT 4P are only tested with HF ballast on AC operation. The performance of Philips CorePro LED PLT 4P on HF ballasts with DC operation is not tested and is therefore not guaranteed.
Philips CorePro LED PLT 4P range is designed to work on HF ballasts only. For EM ballasts configuration, please contact a Philips sales representative for more information on our EM compatible range.
This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips CorePro LED PLT 4P with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips CorePro LED PLT 4P. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube.

Dimming: Philips CorePro LED PLT 4P are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply.

Philips CorePro LED PLT HF/Mains 9W 4P GX24Q-3

Ballast compatibility

Key

	Ballast is compatible.
*	Ballast is compatible. Light output may differ >10% compared to specifications.
**	Ballast is compatible. Light output may differ >10% compared to specifications.
(1)	Ballast Do not use in closed luminaires
	Ballast is not compatible.

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions.

	Ballast type	12nc	Lamps on ballast	CorePro LED PLT HF/Mains 9W 4P GX24Q-3 Model number / EOC code: 9290042668 / 872110304977300 9290042669 / 872110304979700 AC (50 Hz) on HF Ballast Compatible
PHILIPS	HF-P 126 PL-T/C III	913700648766	1	*
	HF-P 1 22-42 PL-T/C/L/T5C EI	913700630766	1	
	HF-P 1 26-42 PL-T/C	913700193266	1	
	HF-P 1/226 PL-T/C III 220-240V 50/60Hz	913700648866	1	
	HF-P 1/226 PL-T/C III 220-240V 50/60Hz	913700648866	2	
	HF-P 226 PL-T/C III	913700648866	2	*
	HF-P 2 22-42 PL-T/C/L/TL5C EII	913700630866	2	
	HF-P 2 26-42 PL-T/C 220-240	913700195066	2	
	HFP 226 (Philips Luminaires)	441134730331	2	
	HF-S 126 PL-T/C/L/TL5C II SR	913713035766	1	
	HF-S 1/2 26 PL-T/C II SR 220-240V 50/60Hz	913713035666	1	
	HF-S 1/2 26 PL-T/C II SR 220-240V 50/60Hz	913713035666	2	
	HF-S 226 PL-T/C II SR	913713035666	2	
	EB-P 126 PLT/C ICC 220-240V 50/60Hz	913710065466	1	*
OSRAM	QTP-M 1X26-42	A6979600455	1	
	QTP-M 2x26-32	A6979950455 A69799500DG	2	*
	QTP-T/E 1x26-42, 2x26	A72032500DG	1	
	QTP-T/E 1X26-42,2X26	A72032500DG	2	
	QT-ECO 1X26/220…240 S	A48946102DG	1	
	QT-ECO T/E 2X26/220-240	A53702300DG	2	
	QT-M 2x26-42/220-240 S	A5267550355 A52675500DG	2	
	QT-T/E 2x26/230-240		2	
	QT-M 1x26-42/220-240 S	A48989E00DG	1	
TRIDONIC ATCO	PC 1/2x26-42 TC PRO sr	22176417	1	*
	PC 1/2x26-42 TC PRO sr	22176417	2	**
	PC 1/2 x 26-42 TC PRO	22176408	1	*
	PC 1/2 x 26-42 TC PRO	22176408	2	*
	PC 1x26-42 TC TOP	28000075	1	
	PC 2x26 TC TOP	28000076	2	
	PC 2x26-42 TC PRO	22176410	2	*
VOSSLOH	ELXs 126.906	188667	1	
	CBC-226142	540426	2	
	ELXc 142.872	188700	1	
	ELXc 142.872	188700	2	(1)
	ELXc 142.876	188888	1	
	ELXc 142.876	188888	2	(1)
	ELXc 242.837	188643	2	(1)
	ELXc 242.877	188889	2	
BAG-HUECO	BCS42.1/26.2LS-01/220-240	10095045	1	
	BCS42.1/26.2LS-01/220-240	10095045	2	
	BCS42.1/26.2QI-01/220-240	10095745	1	
	BCS42.1/26.2QI-01/220-240	10095745	2	
	BCS70.1/42.2Q-01/220-240	10097546	1	
	BCS70.1/42.2Q-01/220-240	10097546	2	
	BCS42.1Q-01/220-240	10097535	1	
	BCS42.1/26.2Q-01/220-240	10097545	1	
	BCS42.1/26.2Q-01/220-240	10097545	2	

Q3 2026

Philips CorePro LED PLT HF/Mains 9W 4P GX24Q-3

Ballast compatibility

Key

	Ballast is compatible.
*	Ballast is compatible. Light output may differ >10% compared to specifications.
**	Ballast is compatible. Light output may differ >10% compared to specifications.
(1)	Ballast Do not use in closed luminaires
	Ballast is not compatible.

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions.

	Ballast type	12nc	Lamps on ballast	CorePro LED PLT HF/Mains 9W 4P GX24Q-3 Model number / EOC code: 9290042668 / 872110304977300 9290042669 / 872110304979700 **AC (50 Hz) on HF Ballast Compatible**
TCI	BCC 126.	137949HTC	1	(1)
	MB226/2	137989Tc	2	
	MBQ 226/2	137968/226	2	
	MBQ 142/2	137968/142	1	**(1)
	MBQ 242/2	137962/242	1	**(1)
	MBQ 242/2	137962/242	2	
HELVAR	EL1/2x18-42TCs	4219001Q09604620 1	1	*
	EL1/2x18-42TCs	4219001Q09604620 1	2	*
	EL2x32/42TCs	4218001K03102451 9	2	*
HUCO	EVG-HP 1x/2x 15-42W HC	097545	1	
	EVG-HP 1x/2x 15-42W HC	097545	2	
OTHERS	Direct mains			
	Electro Magnetic Ballast			

Philips CorePro LED PLT

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.
Please note that Philips CorePro LED PLT 4P are only tested with HF ballast on AC operation. The performance of Philips CorePro LED PLT 4P on HF ballasts with DC operation is not tested and is therefore not guaranteed.
Philips CorePro LED PLT 4P range is designed to work on HF ballasts only. For EM ballasts configuration, please contact a Philips sales representative for more information on our EM compatible range.
This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips CorePro LED PLT 4P with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips CorePro LED PLT 4P. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube.

Dimming: Philips CorePro LED PLT 4P are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply.

Philips CorePro LED PLT HF/Mains 13.5W 4P GX24Q-3

Ballast compatibility

Key

	Ballast is compatible.
*	Ballast is compatible. Light output may differ >10% compared to specifications.
**	Ballast is compatible. Light output may differ >10% compared to specifications.
(1)	Ballast Do not use in closed luminaires
	Ballast is not compatible.

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions.

	Ballast type	12nc	Lamps on ballast	CorePro LED PLT HF/Mains 13.5W 4P GX24Q-3 Model number / EOC code: 9290042670 / 872110304981000 9290042671 / 872110304983400 AC (50 Hz) on HF Ballast Compatible
PHILIPS	HF-P 1 22-42 PL-T/C/L/T5C EI	913700630766	1	
	HF-P 1 26-42 PL-T/C	913700193266	1	
	HF-P 2 22-42 PL-T/C/L/TL5C EII	913700630866	2	
	HF-P 2 26-42 PL-T/C 220-240	913700195066	2	**
OSRAM	QTP-M 1X26-42	A6979600455	1	
	QTP-M 2x26-32	A6979950455 A69799501DG	2	*
	QTP-T/E 1x26-42, 2x26	A72032500DG	1	
	QT-M 2x26-42/220-240 S	A52675500DG	2	*
	QT-M 1x26-42/220-240 S	A37683900DG	1	*
TRIDONIC ATCO	PC 1/2x26-42 TC PRO sr	22176417	1	
	PC 1/2 x 26-42 TC PRO	22176408	1	
	PC 1x26-42 TC TOP	28000075	1	(1)
	PC 2x26-42 TC PRO	22176410	2	
VOSSLOH	ELXc 142.872	188700	1	
	ELXc 142.876	188888	1	
	ELXc 242.837	188643	2	*
	ELXc 242.877	188889	2	*
BAG-HUECO	BCS42.1/26.2LS-01/220-240	10095045	1	
	BCS42.1/26.2QI-01/220-240	10095745	1	
	BCS70.1/42.2Q-01/220-240	10097546	1	
	BCS70.1/42.2Q-01/220-240	10097546	2	
	BCS42.1Q-01/220-240	10097535	1	
	BCS42.1/26.2Q-01/220-240	10097545	1	
TCI	MBQ 142/2	137968/142	1	** (1)
	MBQ 242/2	137962/242	1	** (1)
	MBQ 242/2	137962/242	2	** (1)
HELVAR	EL1/2x18-42TCs	4219001Q09604620 1	1	** (1)
	EL2x32/42TCs	4218001K03102451 9	2	
HUCO	EVG-HP 1x/2x 15-42W HC	097545	1	
OTHERS	Direct mains			
	Electro Magnetic Ballast			

Philips CorePro LED PLT

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.
Please note that Philips CorePro LED PLT 4P are only tested with HF ballast on AC operation. The performance of Philips CorePro LED PLT 4P on HF ballasts with DC operation is not tested and is therefore not guaranteed.
Philips CorePro LED PLT 4P range is designed to work on HF ballasts only. For EM ballasts configuration, please contact a Philips sales representative for more information on our EM compatible range.
This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips CorePro LED PLT 4P with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips CorePro LED PLT 4P. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube.

Dimming: Philips CorePro LED PLT 4P are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply.

Q3 2026

Philips CorePro LED PLT HF/Mains 16W 4P GX24Q-4

Ballast compatibility

Key

	Ballast is compatible.
*	Ballast is compatible. Light output may differ >10% compared to specifications.
**	Ballast is compatible. Light output may differ >10% compared to specifications.
(1)	Ballast Do not use in closed luminaires
	Ballast is not compatible.

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions.

	Ballast type	12nc	Lamps on ballast	CorePro LED PLT HF/Mains 16W 4P GX24Q-4 Model number / EOC code: 9290042672 / 872110304985800 9290042673 / 872110304987200 AC (50 Hz) on HF Ballast Compatible
PHILIPS	HF-P 1 22-42 PL-T/C/L/T5C EII	913700630766	1	
	HF-P 1 26-42 PL-T/C	913700193266	1	
	HF-P 2 22-42 PL-T/C/L/TL5C EII	913700630866	2	
	HF-P 2 26-42 PL-T/C 220-240	913700195066	2	
OSRAM	QTP-M 1X26-42	A6979600455	1	
	QTP-M 2x26-32	A6979950455 A69799501DG	1	*
	QTP-T/E 1x26-42, 2x26	A72032500DG	1	
	QT-M 2x26-42/220-240 S	A5267550355	2	*
	QT-M 1x26-42/220-240 S	A37683900DG	1	*
TRIDONIC ATCO	PC 1/2x26-42 TC PRO sr	22176417	1	
	PC 1/2 x 26-42 TC PRO	22176408	1	
	PC 1x26-42 TC TOP	28000075	1	
	PC 2x26-42 TC PRO	22176410	2	
VOSSLOH	CBC-226142	540426	2	** (1)
	ELXc 142.872	188700	1	
	ELXc 142.876	188888	1	
	ELXc 242.837	188643	2	
	ELXc 242.877	188889	2	*
BAG-HUECO	BCS42.1/26.2LS-01/220-240	10095045	1	
	BCS42.1/26.2QI-01/220-240	10095745	1	
	BCS70.1/42.2Q-01/220-240	10097546	1	
	BCS70.1/42.2Q-01/220-240	10097546	2	
	BCS42.1Q-01/220-240	10097535	1	
	BCS42.1/26.2Q-01/220-240	10097545	1	
TCI	MBQ 142/2	137968/142	1	** (1)
	MBQ 242/2	137962/242	1	** (1)
	MBQ 242/2	137962/242	2	** (1)
HELVAR	EL1/2x18-42TCs	4219001Q09604620 1	1	**
	EL2x32/42TCs	4218001K03102451 9	2	
HUCO	EVG-HP 1x/2x 15-42W HC	097545	1	
OTHERS	Direct mains			
	Electro Magnetic Ballast			

Philips CorePro LED PLT

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.
Please note that Philips CorePro LED PLT 4P are only tested with HF ballast on AC operation. The performance of Philips CorePro LED PLT 4P on HF ballasts with DC operation is not tested and is therefore not guaranteed.
Philips CorePro LED PLT 4P range is designed to work on HF ballasts only. For EM ballasts configuration, please contact a Philips sales representative for more information on our EM compatible range.
This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips CorePro LED PLT 4P with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips CorePro LED PLT 4P. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube.

Dimming: Philips CorePro LED PLT 4P are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply.

© 2026 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify.

Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V. All other trademarks are owned by Signify Holding or their respective owners.